



L1800 – Wallboard Primer

Technical Specifications

PRODUCT DESCRIPTION			
<p>L1800 Wallboard primer is quality painter friendly primer designed to provide a high-hiding, fast drying undercoat with excellent sealing properties for drywall, dry plaster or previously painted surfaces.</p> <p>L1800 Wallboard primer is formulated to adhere to a variety of interior surfaces.</p>			
SPECIFICATIONS			
Type:	C0-Polymer Acrylic	Dry Time - Touch:	30 Minutes
Sizes:	1's, 5's and Quarts	Dry Time - Recoat:	2 to 4 hours
Bases:	Accent base L-1885	Full Service:	7 Days
Gloss:	3-7% @ 60°	Flash Point:	None
	Less than 3% @ 85°	VOC:	Less than 50 g/l
		% Solids Volume:	34%
		Weight Per Gallon:	11.60 +/- .25
PRODUCT USE			
<p align="center">Surface preparation</p> <p>Clean surface to remove contaminants such as dirt, dust, oil, grease, wax and rust. Patch holes and cracks, sand smooth and remove sanding dust and spot prime.</p> <p>New Plaster & Drywall: Plaster must be completely cured (30 days) before painting. Sand smooth drywall tape joints and other repaired areas and spot prime with L1800 Drywall Primer. Apply one coat L1800 Drywall Primer to entire surface. Finish with one or two coats of the C2 interior finish of your choice.</p> <p>Previously Painted Surfaces: Remove all loose or peeling paint. Repair damaged surfaces and sand smooth. Dull glossy surfaces. Spot prime with L1800 Drywall Primer. When painting over dark colors, best results are achieved by priming entire surface. Finish with one or two coats of the C2 LoVo Interior finish of your choice.</p>		<p align="center">Application</p> <p>L1800 Wallboard Primer may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters) Overspreading can result in hiding problems.</p> <p>Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50° F (10° C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. If disposal is necessary, contact your local C2 dealer for recommendations in your area.</p>	