



# C3000 – Exterior Latex Primer

## Technical Specifications

<b>PRODUCT DESCRIPTION</b>			
C3000 Exterior Latex Primer is a 100% acrylic multi-purpose primer with excellent adhesion, sealing, enamel hold-out and sanding properties. C3000 Exterior Latex Primer will seal most interior stains and adhere tenaciously to a variety of interior surfaces.			
<b>SPECIFICATIONS</b>			
<b>Type:</b>	Acrylic Resin	<b>Dry Time - Touch:</b>	30 Minutes
<b>Sizes:</b>	1's and Quarts	<b>Dry Time - Recoat:</b>	2 to 4 Hours
<b>Bases:</b>	None – White only	<b>Full Service:</b>	7 Days
<b>Gloss:</b>	8%-12% @ 85°	<b>Flash Point:</b>	None
	5%-10% @ 60°	<b>VOC:</b>	75 g/L
		<b>% Solids Volume:</b>	37.1
		<b>Weight Per Gallon:</b>	10.99 +/- .2
<b>PRODUCT USE</b>			
<b>Surface preparation</b>		<b>Application</b>	
<p>Free surface of all contaminants such as dirt, dust, oil, grease, wax, and rust. Remove mildew using a chlorine bleach solution of 1 to 4 ratio of bleach to water. Patch holes and cracks, sand smooth and remove dust.</p> <p>New Wood: Sand smooth and remove dust. Spot prime knots with C2 ProSeries Exterior Alkyd Primer. Apply one coat of C2 ProSeries Exterior Latex Primer to entire surface. Note: For severely tannin staining woods, multiple coats of primer may be required.</p> <p>Painted Surfaces: Remove loose and peeling paint. Dull glossy areas. Apply one coat of C2 ProSeries Exterior Latex Primer.</p> <p>Galvanized Metal: Clean surface thoroughly using a strong solvent. Apply one coat of C2 ProSeries Exterior Latex Primer.</p> <p>Masonry: New masonry must be fully cured (90 days). Fill blocks if required. Apply one coat of C2 ProSeries Exterior Latex Primer.</p>		<p>C3000 ProSeries Exterior Latex Primer may be applied by roller (no less than 3/8-inch nap), brush (synthetic) or spray.</p> <p>Spreading Rate: Product should be applied at a rate of 400 to 450 square feet per gallon. (37 to 42 square meters per 3.78 liters) Thinning: Do not thin.</p> <p>Airless Spray: Use a 12 to 15 mil size tip.</p> <p>Cleanup: Clean painting equipment and spills immediately using warm soapy water.</p> <p>Limitations: Do not apply if product, air or surface temperature is below 50<sup>0</sup> F (10<sup>0</sup> C) - Keep product from freezing. Product application and surface conditions are beyond the manufacturer's control. Liability, if any, is limited to replacement of product only.</p> <p>Disposal: Do not dispose of any paint product or solvent in drains, sewers or municipal garbage. Use all of the paint you purchase or give it to someone who can use it. If disposal is necessary, contact</p>	
<b>C2 Paint is formulated without lead or mercury</b>			