




Moving Head			
Model	Name	Picture	Describe
OK-MH-350W	WATERPROOF 350W 17R Beam Moving Head		Power supply: AC90-245V 50/60Hz Light source: 350W 17R Beam Angle:2° Color wheel: 13 color +blank with rainbow effect Gobo wheel: 13 gobos +white Prism : 24 Prism (16+8) rotating Len diamter: 145mm Focus: Electronic focusing Dimming: 0-100% linear dimming Pan/tilt: 540° /270° DMX channel: 16CH Display: LED display IP rating: IP65 Control mode: DMX512, Auto, master/slave Dimension: 370x300x680mm Net Weight: 23KG Gross weight: 25KG
OK-MH-421	420 Beam Wash Moving Head		Power Supply: 110-240V AC,50/60Hz Power Consumption: 600W Light Source: 420W OSRAM Color wheel: 14 color + blank color wheel Static Gobo wheel: 17 gobos Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX
OK-MH-380	380 Beam Wash Moving Head		Power Supply: 110-240V AC,50/60Hz Power Consumption: 550W Light Source:380W 8000k fenghuang/380WPhilips/371 OSRAM Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16Channels DMX

<p>OK-MH-380A</p>	<p>380 LED Ring Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 550W Light Source:380W 8000k fenghuang/380WPhilips/371 OSRAM LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16Channels DMX</p>
<p>OK-MH-380BSW</p>	<p>380 Beam Spot Wash 3 IN 1 Moving Head Light</p>		<p>Voltage AC : 110-240V,50/60HZ Power:500W LAMP:371W Osram Color wheel: 13 color + blank color wheel,can be half color effect Rotating Gobo wheel: 9 optional plug-in design + white speed jitter / bidirectional flow effec Static Gobo wheel:14 gobos speed jitter / bidirectional flow effec Prism: 2 independently rotating prism, wherein a prism with zoom function, dcan also be equipped with 8+16/16+24/24+32 prism Prism 1: 16-facet circular prism rotating Prism 2: T linear prism rotating/8/16-facet circular prism rotating Frost effect : 8-60°adjustable Wash effects angle Lens: high precision optical lens Motor: 3 phase motor Zoom: parallel beam angel 1.5 degree -20 degree change Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Strobe/shutter: Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/24Channels DMX</p>
<p>OK-MH-350BSW</p>	<p>350 Beam Spot Wash 3 IN 1 Moving Head Light</p>		<p>Voltage AC : 110-240V,50/60HZ Power:500W LAMP:350W 8000K/fenghuang Color wheel: 13 color + blank color wheel,can be half color effect Rotating Gobo wheel: 9 optional plug-in design + white speed jitter / bidirectional flow effec Static Gobo wheel:14 gobos speed jitter / bidirectional flow effec Prism: 2 independently rotating prism, wherein a prism with zoom function, dcan also be equipped with 8+6/16+6/24+6 prism Prism 1: 16-facet circular prism rotating Prism 2: T linear prism rotating 6-facet circular prism rotating Frost effect : adjustable Wash effects angle Lens: high precision optical lens Zoom: parallel beam angel 1.5 degree -20 degree change Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540°</p>
<p>OK-MH-300</p>	<p>280W/300W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 400W Light Source: 280W Philips/300w Philips Long life 6000 hour Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>


<p>OK-MH-300A</p>	<p>LED Ring 280W/300W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 400W Light Source: 280W Philips/300w Philips Long life 6000 hour LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>
<p>OK-MH-280</p>	<p>280W Beam Moving Head Light</p>		<p>Voltage:: 110-240V AC,50/60Hz Power: 350W Lamp:280wfenghuang Lamp Lifetime: 2000H Lumin: 400,000Lux@10m Color Temperature: 8000K±300k Beam Angle: 2° Color wheel: 14 color + blank color wheel, Half color effec, bidirectional flow effec(Can Customize CTO color temperature tablet) Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec (Can customize glass gobo tablet) Prism: Double Prisms,double prism can Overlapped, Bi -direction rotation. Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating 7Colors Effect: An independent wheel with 6colors , can make the gobos in rainbow effect. Frost: adjustable Wash effects angle Lens Diameter: 152mm, high precision optical combination lens Movement: Pan: 540° / Tilt: 270 °, Motor: 3 phase motor, 16bit Fine Pan/Tilt control, Auto X/Y repositioning, fast, quiet and smooth DMX Channel: 16/20CH</p>
<p>OK-MH-280A</p>	<p>280W Beam Moving Head Light with RGB Ring</p>		<p>Voltage:: 110-240V AC,50/60Hz Power: 350W Lamp:280wfenghuang LED halo:30PCSRGB 3in1 LEDs, RGB color mixing, LED chase effect Lamp Lifetime: 2000H Lumin: 400,000Lux@10m Color Temperature: 8000K±300k Beam Angle: 2° Color wheel: 14 color + blank color wheel, Half color effec, bidirectional flow effec(Can Customize CTO color temperature tablet) Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec (Can customize glass gobo tablet) Prism: Double Prisms,double prism can Overlapped, Bi -direction rotation. Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating 7Colors Effect: An independent wheel with 6colors , can make the gobos in rainbow effect. Frost: adjustable Wash effects angle Lens Diameter: 152mm, high precision optical combination lens Movement: Pan: 540° / Tilt: 270 °, Motor: 3 phase motor, 16bit Fine Pan/Tilt control, Auto X/Y repositioning, fast, quiet and smooth</p>

<p>OK-MH-250</p>	<p>250W mini Beam Moving Head Light</p>		<p>Voltage: 110-240V AC,50/60Hz Power: 300W Lamp:250wfenghuang Lamp Lifetime: 2000H Lumin: 350,000Lux@10m Color Temperature: 8000K±300k Beam Angle: 2° DMX Channel: 16CH/20CH Control Mode: DMX 512, Master/Slave, Auto, Sound active Support RDM Dimmer: 0-100% linear adjustment Focus: 0-100% Linear adjustment focus Strobe: 1-15 times/s, pulse and random strobe House: Patent design,Fire-proofing material , high temperature resistance Size: 22x20x46cm Weight: 11.5kgs Display: LCD display IP Rate: IP20 Color wheel: 12 color + blank color wheel, Half color effec, bidirectional flow effect (Can Customize CTO color temperature tablet) Gobo wheel: 14 gobos,speed jitter / bidirectional flow effect (Can customize glass gobo tablet) Prism: Double Prisms,double prism can Overlapped, Bi -direction</p>
<p>OK-MH-250A</p>	<p>250W mini Beam Moving Head Light with RGB Ring</p>		<p>Voltage: 110-240V AC,50/60Hz Power: 300W Lamp:250wfenghuang LED halo:36PCSRGB 3in1 LEDs, RGB color mixing, LED chase effect Color wheel: 12 color + blank color wheel, Half color effec, bidirectional flow effec(Can Customize CTO color temperature tablet) Gobo wheel: 14 gobos,speed jitter / bidirectional flow effec (Can customize glass gobo tablet) Prism: Double Prisms,double prism can Overlapped, Bi -direction rotation. Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating 7Colors Effect: An independent wheel with 6colors , can make the gobos in rainbow effect. Frost: adjustable Wash effects angle Lens Diameter: 128mm, high precision optical combination lens Movement: Pan: 540° / Tilt: 270 °, Motor: 2 phase motor, 16bit Fine Pan/Tilt control, Auto X/Y repositioning, fast, quiet and smooth Lamp Lifetime: 2000H Lumin: 350,000Lux@10m Color Temperature: 8000K±300k Beam Angle: 2°</p>
<p>OK-MH-275</p>	<p>275 Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W Philips/275W fenghuang Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>

<p>OK-MH-275A</p>	<p>275 LED Ring Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W Philips/275W fenghuang LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>
<p>OK-MH-250A</p>	<p>MINI 250 Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W fenghuang LED: 30pcs SMD3in1 halo Color wheel: 12 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 14 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16Channels DMX</p>
<p>OK-MH-230</p>	<p>200W 5R/230W 7R Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 300W Light Source: 230W 8000k /fenghuang 7R/5R Color wheel: 14 color + blank color wheel,can be half color effect Static Gobo wheel:17 gobos speed jitter / bidirectional flow effec Prism : 16-facet circular prism rotating Frost effect : adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 2/3 phase motor Focus: Linear adjustment Beam: multi-class beam adjustment Movement Pan: 540° Optional Tilt: 270° Strobe/shutter: Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX Dimension: 540*440*410mm N.W: 11kg G.W: 12kg</p>

<p>OK-LS-480A</p>	<p>WATERPROOF 461 Beam Spot Wash</p>		<p>Voltage: 100-240V, 50/60Hz Lamp: Original Osram 461W Power: 680W Color: Pure color imported from Italy, a color plate, there are 13 color plates +1 white light Pattern plate: two pattern plate, fixed pattern plate 14 patterns + white light, rotating pattern plate 9 pattern pieces, customizable LOGO, pattern can be linear infinite zoom Rotating pattern diameter :12mm effective inner diameter :11mm Effect Wheel: A round 8 prism, 0-100% mechanical dimming, support mechanical stroboscopic and adjustable stroboscopic effect, support strobe macro function. Lens group optical system, electric focus, beam Angle 2.5 ~ 45°. Photoelectric reset system, when accidental misoperation, can automatically retrieve reset. Rotation Angle 540° horizontal, 8Bit/16Bit resolution, 270° vertical, 8Bit/16Bit resolution. Overheat protection. Electronic rectifier. Focusing: Electronic linear HD dynamic focusing, using high density glass optical lens. Linear dimming curve: 0%-100% linear dimming Luminaire intelligence: Intelligent gyroscope induction position state, intelligent adjustment of fan speed, so as to effectively increase the service life of the bulb, fan driving performance is excellent, very low noise. Channel: 16 /20 international standard DMX512 channels. System heat dissipation: Large copper tube is used for heat dissipation, so as to ensure water resistance and heat dissipation of high-power bulbs</p>
<p>OK-LS-480</p>	<p>WATERPROOF 461W Beam Wash Moving Head</p>		<p>Voltage: 110V-240V 50-60Hz Lamp: Original Osram 461W Power factor: 0.985 Total power: 680W Color: Imported from Italy pure color: 13+1+ colorful rainbow effect + Atomization function, Pattern: Pattern Plate: 14 fixed pattern +1 white light Focusing: Electronic linear HD dynamic focusing, using high density glass optical lens. Linear dimming curve: 0%-100% linear dimming Stroboscopic: 1-25Hz fast stroboscopic, with pulse stroboscopic, synchronous and asynchronous stroboscopic effect Beam Angle: 0-1.8° Luminaire intelligence: Intelligent gyroscope induction position state, intelligent adjustment of fan speed, so as to effectively increase the service life of the bulb, fan driving performance is excellent, very low noise. Channel: 16 /20 international standard DMX512 channels. System heat dissipation: Large copper tube is used for heat dissipation, so as to ensure water resistance and heat dissipation of high-power bulbs Temperature intelligent monitoring technology, automatic adjustment of heat dissipation system, effective control of lamp temperature. Dehumidification system: Intelligent dehumidification system, air pressure compensation design, Effectively ensure the life of lamps and lanterns Modular design: From production to assembly, replacement parts are more reasonable Lens diameter: 185mm XY motor: Three electric drive, strong, faster, more stable, more silent. Lamps and lanterns material: Adopt the national standard die-cast aluminum, die-cast magnesium alloy high-end material shell! Without plastic, it can be used in harsh outdoor environment such as rain, high</p>
<p>OK-LS-380</p>	<p>WATERPROOF 380W Beam Wash Moving Head</p>		<p>Voltage: 110V-240V 50-60Hz Lamp: Original Osram 371W Power factor: 0.985 Total power: 680W Color: Imported from Italy pure color: 13+1+ colorful rainbow effect + Atomization function, Pattern: Pattern Plate: 14 fixed pattern +1 white light Focusing: Electronic linear HD dynamic focusing, using high density glass optical lens. Linear dimming curve: 0%-100% linear dimming Stroboscopic: 1-25Hz fast stroboscopic, with pulse stroboscopic, synchronous and asynchronous stroboscopic effect Beam Angle: 0-1.8° Luminaire intelligence: Intelligent gyroscope induction position state, intelligent adjustment of fan speed, so as to effectively increase the service life of the bulb, fan driving performance is excellent, very low noise. Channel: 16 /20 international standard DMX512 channels. System heat dissipation: Large copper tube is used for heat dissipation, so as to ensure water resistance and heat dissipation of high-power bulbs Temperature intelligent monitoring technology, automatic adjustment of heat dissipation system, effective control of lamp temperature</p>

<p>OK-LED-600</p>	<p>LED 600W Beam Spot Wash Framing Moving Headwith CMY&CTO</p>		<p>Input voltage: AC100-240V, 50/60Hz Amount of power: 900W Light source: 600W LED module LED life: 20,000 hours Color temperature: 6800K Diameter: 135mm Color rendering index: standard mode Ra>72, high display mode Ra>90 Luminous flux: 24000LM Power interface: 16A power plug Signal interface: three-core XLR Control mode: DMX512, RDM Channel mode: 36 international standard DMX512 channels Display: 2.7-inch touch LCD display, Chinese and English display, 180-degree rotation Fixed color: 6 colors + Open Color mixing system: independent CMY color mixing system Color temperature adjustment: independent CTO2500-7000K linear adjustment Prism: 3 prisms Animation plate: dazzling simulation of dynamic swaying flames, gurgling water and other dynamic effects Fixed Gobo Plate: 7 metal fixed Gobos + Open Rotating Gobo Plate: 7 Gobos (pluggable) outer diameter 22.9mm,</p>
<p>OK-MH-LED700</p>	<p>LED 700W Beam Spot Wash Framing Moving Headwith CMY&CTO</p>		<p>Input voltage: AC100-240V, 50/60Hz Power: 980W Light source: 700W LED module LED life: 20,000 hours Diameter: 138mm Color temperature: 6800K Color rendering index: standard mode Ra>75, high display mode Ra>90 Luminous flux: 24000LM Power interface: 16A power plug Signal interface: three-core XLR Control mode: DMX512, RDM Channel mode: 36chs international standard DMX512 channels Display system: 2.5-inch touch LCD display, Chinese and English display, 180-degree rotation Fixed color: 7 colors + Open Color mixing system: independent CMY color mixing system Color temperature adjustment: independent CTO 2700K-7000K linear adjustment Prism: rotating 3 prisms + 6 Linear Prims Effect panel: dazzling simulation of dynamic swaying flames, gurgling water and other dynamic effects Fixed Gobo: 8 plug-in fixed gobos with an outer diameter of 25.4mm + white circle Rotating Gobo: 6 Gobos (pluggable) outer diameter 26.9mm, effective diameter 16.5mm, thickness 1.1mm Cutting system: 4 independent cutting blades, each of which can be closed individually and can be rotated 90° Atomization system: 0~100% linear atomization</p>

LED Moving Head			
Model	Name	Picture	Describe
<p>OK-MHLED-400</p>	<p>LED 400W Beam Wash Spot Moving Head with CMY</p>		<p>voltage: AC110V-240V/50-60HZ Power : 450W LED: import LED Module 350W LED: 50000 hours illuminance: 5 meters 100,000 lm LED: 8000K CRI>85 Dimming system: 0-100% linear adjustment Focusing system: linear adjustment from 4° -50 ° Frost: adjustable Wash effects angle Spot zoom angle: 4-35 ° Wash angle:10-50° High-speed strobe: 0-30 times/sec. Adjustable speed strobe effect. Strobe macro function. CONTROL AND PROGRAMMING Channel mode: 22 channels Display mode: LCD display Control signal: International standard DMX512. With RDM function, online software upgrade Color: 8 colors + open. Color half-color function Color mixing system: linear CMY+CTO color mixing system Fixed gobos: 12 fixed patterns + ioen Rotating gobos: 7 glass patterns, each glass pattern can be independently forward and reverse Prism system: standard single 3-facet prism and 8 prism, each prism can be independently forward and reverse Macro function: console reset function, self-propelled mode, master-slave mode</p>

<p>OK-MHLED-250</p>	<p>250W LED Spot Beam Wash Hybrid Moving Head Light</p>		<p>Input Voltage: 100-240V 50/60 Hz Light Source: 250W white LED COB LED: 50000 hours LED: 8000K CRI>85 Gobos: one static gobo wheel: 9 static gobos+ open one rotating gobo wheel: 7 interchangeable, rotating, indexable gobos + open Color: one color wheel, 9 colors + Open, half-color and rainbow effect Prism: 3 facet prism Zoom: 11° ~ 27° linear zoom Dimming: 0 ~ 100% linear dimming Strobe: With strobe effect Frost: Fine wash effect Display: LCD display Channel: 18CH Control Mode: DMX 512,Auto-running ,Master/salve, Sound active, Built-in program Movement: Pan 540°; Tilt 270°; Auto X/Y repositioning, fast, quiet and smooth</p>
<p>OK-MHLED-200</p>	<p>LED 200W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 300W Light Source: import LED Module 200W Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>
<p>OK-MHLED-100C</p>	<p>LED100W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: import LED Module 100W Color wheel: 12 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 14 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16Channels DMX</p>

OK-MHLED-230	230W Spot Moving Head Light		<p>Input power:AC100-240V 50/60 Hz Power consumption :260W DMX channel:6/18 channels Pan scan: 540°(16bit) Electric correction Tilt scan: 270° (16bit) Electric correction Color wheel: one color wheel, 7 kinds of color chips in one color wheel Static Gobo: 7gobos+open Rotation Gobo:7 gobos+open Effect Wheel: two Effect prism,one Rotation six prism,one Rotation five prism effect move Lens optical system mechanical focus .beam Zoom angle 11°-24° Control mode:DMX512/Master-Slave/Auto run Display:LCD display WEIGHT&SIZE N.W: 12.5KG G.W: 14 KG Packing size: 48.5*35.5*39cm</p>
OK-MHLED-150	150W Spot Moving Head Light		<p>Input power:AC100-240V 50/60 Hz Power consumption :170W LED source: 1 x 150W LED DMX channel:16 channels Pan scan: 540°(16bit) Electric correction Tilt scan: 270° (16bit) Electric correction Color wheel: one color wheel, 7 kinds of color chips in one color wheel Static Gobo: 7gobos+open Rotation Gobo:6 gobos+open Beam angle:16 degree Effect Wheel: one Rotation three-faced prism Frost RDM function Effect move , Bi-directional rotation Lens optical system mechanical focus Control mode:DMX512/Master-Slave/Auto run/IR Over heat protection Dimmer : 0- 100 % Strobe:0-20 HZ Display:LCD display WEIGHT&SIZE N.W: 9.5 KG G.W: 11 KG</p>
OK-MHLED-100	100W Spot Moving Head Light		<p>Voltage: AC110-240V, 50/60Hz Power: 120W LED: 1pcs*100W LED white Beam angle: 18° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color wheel: 7 color + open ,rainbow -flow effect Static Gobo: 6gobos+open Rotation Gobo:6 gobos+open Prism: 3-facet prism , adjustable rotation speed &double Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 13CH Dimension: 480*290*290mm N.W: 8kg G.W: 9kg</p>
OK-MHLED-150A	150W LED BEAM Moving Head		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 180W Light Source: 150W 8000k Color wheel: 13 color + blank color wheel Static Gobo wheel: 17 gobos Prism : 8-facet circular prism rotating or 16-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16 Channels DMX</p>

<p>OK-MHLED-120</p>	<p>120W LEDBEAM</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 120W Light Source: 120W 8000k Color wheel: 13 color + blank color wheel Static Gobo wheel: 12 gobos Prism : 16-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX</p>
<p>OK-MHLED-100A</p>	<p>100W LED BEAM Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 120W Light Source: 100W 8000k Color wheel: 13 color + blank color wheel Static Gobo wheel: 12 gobos Prism : 16-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270° Beam Angle: Parallel beam angel 0-2.3° Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe DMX Channels: 16/20Channels DMX Dimension: 580*460*460mm N.W: 11kg G.W: 12kg</p>
<p>OK-MH-1</p>	<p>37PCS 15W LED Zoom Moving Head</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 500W LED:37*15W Osram RGBW 4IN1 Beam angle: 4.5° -45° Pan Tilt movement: X-axis:540° , Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: 0-20 HZ Operation: RDM,Auto, DMX512, Sound, Master/Slave Channel:24/36/48CH</p>
<p>OK-MH-2</p>	<p>36pcs*10W LED Moving Head Light With Zoom</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 400W LED: 36*10W RGBW 4-in-1 led LED: 36*18W RGBW 6-in-1 led Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Zoom: 12° - 58° Total Output: 2000 lux at 2 meter for maximum beam angel 58°,22600 lux at 2 meter for minimum beam angel 11° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 16CH Dimension:: 420*300*390mm N.W: 9kg G.W: 10kg</p>
<p>OK-MH-3</p>	<p>19pcs*12W Beam LED Zoom Moving Head Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 300W LED: 19*12W 4 in 1 RGBW CREE led Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Zoom: 10° - 60° Total Output: 2000 lux at 2 meter for maximum beam angel 58°,22600 lux at 2 meter for minimum beam angel 11° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 16CH Dimension:: 420*270*290mm N.W: 9kg G.W: 10kg</p>

<p>OK-MH-3A</p>	<p>19pcs*12W Beam LED Zoom Moving Head Light with RGB Ring</p>		<p>Voltage: AC 100V~240V, 50/60Hz Power Consumption: 300W LED Source: 19pcs * 15W RGBW 4in1 LED LED Ring:48pcs RGB 3in1 SMD Beam Angel: 8 ~50 degree Dimming: 0-100% electronic dimming Strobe: 1-25times per second Movement: Pan 540°, Tilt 270°, speed adjustable. Control Mode: DMX512, master-slave, auto, sound DMX Channel: 24/32CH Color: RGBW infinite mixing system, Uniform and bright colors Effects: 3 LED rings control, rainbow effects, outstanding color macro effect. Display: Colorful LCD display for easy navigation.</p>
<p>OK-MH-4</p>	<p>LED EYE Beam Wash Moving Head Light</p>		<p>Voltage:AC110-240V,50/60HZ Power:400W LED:19PCS CREE 15W RGBW 4IN1 Zoom:3.8-35° Optical lens: light guide rod + integrated high guide lens Front lens disc: bidirectional endless rotation, seamless splicing lens disc, aspheric lens structure Effect mode: beam, digital (vortex, kaleidoscope, etc.) Strobe:1-25 times/second electronic strobe and random stroboe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis:540°,Y-axis:270° Z-axis:infinite tilt Display:LCD display,Chinese/English(optional), Auto rotate screen Operation: Auto,DMX512,Sound,Master/Slave Feature:Fan intelligent control;Electronic sensor detection; Monitoring of the level of the channel Communication protocol:Standard DMX512 protocol Channel:21/23/35/78/92/97/99CH Shell: high strength fire and temperature resistant engineering plastic shell and metal powder spray technology, streamline appearance design</p>
<p>OK-MH-5</p>	<p>LED EYE Beam Wash Moving Head Light</p>		<p>Voltage:AC110-240V,50/60HZ Power:350W LED:7PCS OSRAM 40W RGBW 4IN1 Zoom:3.8-35° Optical lens: light guide rod + integrated high guide lens Front lens disc: bidirectional endless rotation, seamless splicing lens disc, aspheric lens structure Effect mode: beam, digital (vortex, kaleidoscope, etc.) Strobe:1-25 times/second electronic strobe and random stroboe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis:540°,Y-axis:270° Z-axis:infinite tilt Display:LCD display,Chinese/English(optional), Auto rotate screen Operation: Auto,DMX512,Sound,Master/Slave Feature: Fan intelligent control;Electronic sensor detection; Monitoring of the level of the channel Communication protocol:Standard DMX512 protocol Channel:21/42CH Shell: high strength fire and temperature resistant engineering plastic</p>
<p>OK-MH-5mini</p>	<p>300W Mini LED Beam Wash Moving Head Light</p>		<p>Voltage:AC110-240V,50/60HZ Power:300W LED Source: 7pcs 40W 4in1 high power LEDs Over 50000hrs working life. Beam Zoom Angle :3.8-35° lens : light guide rod + integrated high guide lens,bidirectional endless rotation, seamless splicing lens disc, aspheric lens structure Effect mode: beam, digital (vortex, kaleidoscope, etc.) Strobe: 1~25Hz, multiple strobe effects Dimmer: 0-100% linear dimming Pan/Tilt movement: X-axis:540°,Y-axis:270° Z-axis:infinite tilt Control Mode: DMX 512, Master/Slave, Auto, Sound active Support RDM DMX Channel:23/35/51CH Display:LCD display,Chinese/English(optional), Fan:Fan intelligent control Size: 24x20x34cm N. W.: 3kg, G.W.: 4kg Shell: high strength fire and temperature resistant engineering plastic</p>





OK-MH-6	740 LED Zoom Moving Head		Voltage: AC110-240V, 50/60Hz Power: 350W LED:7*40W Osram RGBW 4IN1 Beam angle: 4.5° -45° Pan Tilt movement: X-axis:540° , Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: 0-20 HZ Operation: RDM,Auto, DMX512, Sound, Master/Slave Channel:11/18/58CH
OK-MH-7	715 LED Zoom Moving Head		Voltage:AC110-240V,50/60HZ Power:120W LED:7PCS CREE 15W RGBW 4IN1 Zoom:5-35° Optical lens: integrated high guide lens Front lens disc: wash beam Strobe:1-25 times/second electronic strobe and random stroboe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis:540°,Y-axis:270° Auto rotate screen Operation: Auto,DMX512,Sound,Master/Slave DMX512 protocol Channel:15/CH
OK-MH-8	knife		Voltage:AC110-240V,50/60HZ Power:1000W LED BEAM:5PCS OSRAM 60W RGBW 4IN1 LED STROBE: 36PCS 18W WHITE STROBE Zoom:2.8-55° Optical lens: light guide rod + integrated high guide lens Strobe:1-25 times/second electronic strobe and random stroboe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis:infinite tilt ,Y-axis:infinite tilt Display:LCD display,Chinese/English(optional), Auto rotate screen Operation: Auto,DMX512,Sound,Master/Slave Feature:Fan intelligent control;Electronic sensor detection; Monitoring of the level of the channel Communication protocol:Standard DMX512 protocol Channel:23/61CH Shell: high strength fire and temperature resistant engineering plastic shell and metal powder spray technology, streamline appearance design
OK-MH-9	1030 BEAM Moving Head Light		Voltage:AC110-240V,50/60HZ Power:300W LED:High Power 10PCS 30W RGBW 4IN1 OSRAM LED Beam Angle:3.8° Pan movement: Y-axis:150° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation:Auto,DMX512,Sound,Master/Slave Channel:7/13/43CH
OK-MH-10	Super Beam Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED:4pcs*25W high brightness white leds. Beam angle: 5-40 degree Pan Tilt movement: X-axis:540° , Y-axis: 270° Z-axis:infinite tilt Color wheel: with a Red Blue Yellow color wheel create colorful effect with running water effect Feature: 8pcs lens Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/15 CH Dimension: 460*320*250mm N.W: 6kg G.W: 6.5kg
OK-MH-11	Double BEAM LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED:14pcs*10W RGBW 4IN1 CREE Beam angle: 6° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/16 CH Dimension: 360*310*210mm N.W: 6kg G.W: 6.5kg







OK-MH-12	LED Beam Strobe Moving Head		<p>Voltage: AC110-240V, 50/60Hz Power: 150W LED:12*10W RGBW CREE 4IN1 LED Strobe:6*10W White COB Beam angle: 6° Pan Tilt movement: X-axis:infinite tilt , Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: Electric strobe, 0.3-25 times second Operation: Auto, DMX512, Sound, Master/Slave Channel:12CH</p>
OK-MH-13	LED Beam SMD Moving Head		<p>Voltage: AC110/220V 50-60HZ Power: 120W LED:8*10W RGBW CREE 4IN1 SMD:5050*96PCS Operation: Auto, sound , master-slave, DMX512, SIZE:26.5*20*38cm net weight: 4KG gross weight: 5KG packing size: 67*53*45cm 4pcs/Ctn (22KG)</p>
OK-PL-94F	3-facet prism Spot Wash Moving Light		<p>Voltage: AC110-240V, 50/60Hz Power: 100W LED: 1pcs*60W LED white Beam angle: 18° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color : 6color + blank color wheel Gobo : Gobo: 7gobos+open Prism: 3-facet prism , adjustable rotation speed &double Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave</p>
OK-PL-94E	Spot Wash Moving Light		<p>Voltage: AC110-240V,50/60HZ Power:70W LED:30W White LED:6*8W RGBW 4IN1 Color : 6color + blank color wheel Gobo : Gobo: 7gobos+open Angle: 13° Pan Tilt movement: X-axis:540° , Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: Electric strobe, 0.3-25 times second Operation: Auto, DMX512, Sound, Master/Slave Channel:13CH</p>
OK-PL-94A	60W LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz Power: 60W LED: 1pcs*60W CREE LED white Beam angle: 13° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color wheel: 7 color + open ,rainbow -flow effect Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/11CH Dimension: 290*260*210mm N.W: 3.5kg G.W: 4.5kg</p>
OK-PL-94	30W LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED: 1pcs*30W CREE LED white Beam angle: 13° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color wheel: 7 color + open ,rainbow -flow effect Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/11CH Dimension: 290*260*210mm N.W: 3.5kg G.W: 4.5kg</p>






<p>OK-PL-94B</p>	<p>30W SMD LED Moving Head Spot Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED: 1pcs*30W LED white LED: 8PCS*5050SMD Beam angle: 13° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color wheel: 7 color + open ,rainbow -flow effect Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/11CH Dimension: 290*260*210mm N.W: 3.5kg G.W: 4.5kg</p>
<p>OK-PL-74</p>	<p>12W LED Moving Head Spot Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 20W LED: 1pcs*12W CREE LED white Beam angle: 13° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color wheel: 7 color + open ,rainbow -flow effect Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/11CH Dimension: 260*240*210mm N.W: 3kg G.W: 4kg</p>
<p>OK-PL-58B</p>	<p>2-in-1 LED Effect Light LED BALL+BEAM Moving Head</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds LED BEAM: 1pcs*10W 4in1 RGBW CREE leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° LEDBALL Angle: 2° Beam Angle: 4° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 13/16CH</p>
<p>OK-PL-58C</p>	<p>3-in-1 LED Effect Light LED BALL+SMD+LASER Moving Head</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds LED SMD: 36pcs SMD 0.2W RGB 3IN1 Laser: Greed 50mw Pan/Tilt movement: X-axis: 540°, Y-axis:270° LEDBALL Angle: 2° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 19/24CH</p>
<p>OK-PL-58D</p>	<p>2-in-1 LED Wash + beam moving head light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED WASH: 3pcs*6W 4in1 RGBW leds LED BEAM: 1pcs*10W 4in1 RGBW CREE leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° LEDWASH Angle: 25° Beam Angle: 4° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 13/16CH</p>
<p>OK-PL-58E</p>	<p>2-in-1 LED Effect Light LEDBALL+ Wash moving head light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 40W LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds LED WASH: 4pcs*6W 4in1 RGBW leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° LEDBALL Angle: 2° LEDWASH Angle: 25° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 13/16CH</p>




OK-PL-58F	Mini 7pcs LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 40W LED WASH: 7pcs*6W 4in1 RGBW leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° LEDWASH Angle: 25° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9CH
OK-PL-94G	Two-head beam laser		Voltage: AC110-240V, 50/60Hz Power: 100W LED:8pcs*10W RGBW 4IN1 CREE laser:R:100MW G:50MW Beam angle: 2° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave
OK-PL-94H	Three-head beam laser		Voltage: AC110-240V, 50/60Hz Power: 150W LED:12pcs*10W RGBW 4IN1 CREE laser:R:100MW G:50MW B: 150MW Beam angle: 2° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave
OK-PL-94N	Four-head beam laser		Voltage: AC110-240V, 50/60Hz Power: 180W LED:16pcs*10W RGBW 4IN1 CREE laser:R:100MW G:50MW Beam angle: 2° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave
OK-PL-94M	3in1 beam laser Strobe		Voltage: AC110-240V, 50/60Hz Power: 180W LED:8pcs*10W RGBW 4IN1 CREE Strobe:4pcs*10W CW/Y laser:2PCS R:100MW ,2PCS G:50MW Beam angle: 2° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave
OK-PL-87A	wash + beam moving head light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 4pcs*10W 4in1 RGBW+1pcs*10W 4in1 RGBW high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: infinite tilt Beam Angle: 6° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/17CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg
OK-PL-14A	18PCS*3W LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18pcs RGB high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Beam Angle: 25° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/13CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg

OK-PL-14	7pcs*10W LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7pcs*10W 4IN1 RGBW high brightness leds LED: 7pcs*15W 5IN1 RGBWA high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Beam Angle: 45° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/14CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg
OK-PL-14	7pcs*15W LED Moving Head Light		

Waterproof Par Light			
Model	Name	Picture	Describe
OK-PL-69AW	200WCOB RGBW /W LED Par Aluminum		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 200W 4in1 COB RGB LED LED: 200W White COB LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH WATERPROOF:IP65 Dimension:250*250*350mm N.W: 6kg G.W: 7kg
OK-PL-69D	4*50W Waterproof PAR LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 4PCS* 50W Warm White Cool White(2pcsWW+2pcsCW) Color Temperature: 3000K-5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH Dimension:250*250*250mm N.W: 5kg G.W: 6kg
OK-PL-44	mini 7PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7PCS*8W RGBW 4IN1 LED: 7PCS*10W RGBWA/RGBWUV 5IN1 LED: 7PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:160*160*90mm N.W: 1.8kg G.W: 2kg
OK-PL-45	mini 9PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 9PCS*8W RGBW 4IN1 LED: 9PCS*10W RGBWA/RGBWUV 5IN1 LED: 9PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:160*160*90mm N.W: 1.8kg G.W: 2kg

OK-PL-46	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 18PCS*4W RGBW 4IN1 LED: 18PCS*5W RGBWA/RGBWUV 5IN1 LED: 18PCS*6W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 285x275x115mm N.W: 3.5kg G.W: 3.75kg
OK-PL-47	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 120W LED: 54PCS*1W RGBW LED: 54PCS*1.5W RGB3IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 220*220*90mm N.W: 2kg G.W: 2.5kg
OK-PL-51	mini 7PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 120W LED: 7PCS*12W RGBW 4IN1 LED: 7PCS*15W RGBWA/RGBWUV 5IN1 LED: 7PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 190*190*180mm N.W: 2kg G.W: 2.5kg
OK-PL-52	mini 9PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 9PCS*10W RGBW 4IN1 LED: 9PCS*15W RGBWA/RGBWUV 5IN1 LED: 9PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 190*190*180mm N.W: 2kg G.W: 2.5kg
OK-PL-53	mini 12PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 12PCS*10W RGBW 4IN1 LED: 12PCS*15W RGBWA/RGBWUV 5IN1 LED: 12PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 190*190*180mm N.W: 2kg G.W: 2.5kg
OK-PL-2	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 54PCS*3W RGBW LED: 54PCS*3W RGB3in1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH waterproof level: IP65 Dimension: 290*290*250mm N.W: 6kg G.W: 7kg
OK-PL-2			

OK-PL-55	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*250mm N.W: 6kg G.W: 7kg
OK-PL-55			
OK-PL-55			
OK-PL-15	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*250mm N.W: 6kg G.W: 7kg
OK-PL-21A	18PCS Waterproof connector LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*8W RGBW LED: 18PCS*10W RGBWA/RGBWUV LED: 18PCS*12W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: RDM, Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH
OK-PL-20A	12PCS Waterproof connector LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 12PCS*10W RGBW LED: 12PCS*15W RGBWA/RGBWUV LED: 12PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: RDM, Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH
OK-PL-24	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg








<p>OK-PL-54A</p>	<p>44PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 550W LEDs: 44PCS 12W (RGBW 4in1)CREE LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>
<p>OK-PL-54C</p>	<p>960PCS 2in1 Waterproof LED Strobe Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 600W LED: 1080*5050 LED Life: about 50,000 hours Color: RGB Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, 12-segment Channel: 5/10/38CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling Material: cold-rolled sheet + aluminum alloy + tempered glass Dimensions: 540x320x205mm Weight: 8.5 Kg</p>
<p>OK-LP-90E</p>	<p>40PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 750W LEDs: 60PCS 12W (RGBW 4in1)CREE LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>
<p>OK-PL-18</p>	<p>80PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 450W LEDs: 36PCS 12W (RGBW 4in1)CREE LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>







<p>OK-LP-90E</p>	<p>60PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 750W LEDs: 60PCS 12W (RGBW 4in1)CREE LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>
<p>OK-PL-54</p>	<p>96PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 800W LEDs: 96PCS *10W RGBW 4IN1 LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>
<p>OK-OL-8</p>	<p>180PCS Waterproof LED WALL WASH Light</p>		<p>Voltage: AC110-240V 50-60Hz Power: 500W LEDs: 180PCS 3W (RGB3in1)LEDs Light life:50000 hours Dimmer: 0-100% Stroboscopic:1-20 time/sec Beam Angle : 40° (optional) digital Control: Standard DMX512 signal, master-slave, auto-running. DMX channel: 4/8CH Cooling system: Natural convection heat transfer. Body and color: Aluminum and black. Tempreture: -20° C ~ 40° C. Effect distance: 30m Dimmension:58*30*40cm 16kg Packing size:70*35*46cm 19kg</p>
<p>OK-PL-25</p>	<p>18PCS Led Wall Washer (pixel controller)</p>		<p>Voltage:AC110-240V 50-60Hz Power consumption:200W Light source:18PCS 8WRGBW 4in1 LEDs Light source:18PCS 10WRGBWA 5in1 LEDs Light source:18PCS 12WRGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/72CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Waterproof rate:IP65 Dimensions: 100*8.8*17cm 7.2kg Packing Size: 105*15*21cm 7.6kg 1pcs</p>

OK-PL-25A	24*18W RGBWA+UV 6in1 LED Outdoor Wash Light Bar		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 24PCS*6W RGBWAUV CREE 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming Operation: Auto, RDM, DMX512, Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg
OK-PL-16	MINI COB Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 1PCS*60W RGBWA 5in1 Beam Angle: 65° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9CH Dimension: 190*190*250mm N.W: 3kg G.W: 4kg
OK-PL-17	MINI 7PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/100/120W LED: 7PCS*10W RGBW LED: 7PCS*15W RGBWA/RGBWUV LED: 7PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 190*190*250mm N.W: 3kg G.W: 4kg
OK-PL-18	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/100/120W LED: 54PCS*3W RGBW LED: 54PCS*3W RGB3IN1 LED: 54PCS*4W RGBW4IN1 Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-20	12PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 140/180/240W LED: 12PCS*10W RGBW LED: 12PCS*15W RGBWA/RGBWUV LED: 12PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-21	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg


OK-PL-22	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-24	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-69-1	90WCOB LED Par Aluminum		Voltage: AC110-240V, 50/60Hz Power: 100W/150W/200W LED: 90W 3in1 COB RGB LED LED: 100W White COB LED LED: 200W 4in1 COB RGBW LED LED: 200W White COB LED Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-69-2	100WCOB WHITE LED Par Aluminum		
OK-PL-69-3	200WCOB RGBW LED Par Aluminum		
OK-PL-69-4	200WCOB WHITE LED Par Aluminum		
OK-PL-19	24x10W RGBW Strip-light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-6	LED Zoom PAR LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 19*12W 4 in 1 RGBW CREE led Beam Zoom: 10° - 60° Dimmer: 0-100% linear dimming Strobe: Electric strobe, 0.3-25 times second Operation: Auto, DMX512, Sound, Master/Slave Channel: 10/18CH Size: 280x228x296mm N.W: 4.1kg G.W: 4.35kg
OK-PL-35E	24PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 24PCS*8WRGBW 4IN1 LED: 24PCS*10WRGBWA 5IN1 LED: 24PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm
OK-PL-35F	18PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 18PCS*8WRGBW 4IN1 LED: 18PCS*10WRGBWA 5IN1 LED: 18PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9/10CH Dimension: 220*220*100mm




OK-PL-35G	24PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 24PCS*8WRGBW 4IN1 LED: 24PCS*10WRGBWA 5IN1 LED: 24PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 220*220*100mm
OK-PL-34	14PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 180W/200W LED: 18PCS*10WRGBW 4IN1 LED: 14PCS*15WRGBWA 5IN1 LED: 14PCS*18W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg
OK-PL-35	18PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/250W LED: 18PCS*10WRGBW 4IN1 LED: 18PCS*15WRGBWA 5IN1 LED: 18PCS*18W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg
OK-PL-36	54PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 180W LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg
OK-PL-1	54PCS Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/200W LED: 54PCS*1W RGBW LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-2	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/200W LED: 54PCS*1W RGBW LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH waterproof level: IP65 Dimension:290*290*350mm N.W: 7kg G.W: 8.5kg
OK-PL-3	36PCS Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 50/150W LED: 36PCS*1W RGB LED: 36PCS*3W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 7CH Dimension:250*250*360mm N.W: 7kg G.W: 8.5kg

<p>OK-PL-4</p>	<p>36PCS Waterproof LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 50/150W LED: 36PCS*1W RGB LED: 36PCS*3W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg</p>
<p>OK-PL-15</p>	<p>24PCS Waterproof LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg</p>
<p>OK-PL-43</p>	<p>18PCS Aluminum LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-PL-55</p>	<p>18PCS Waterproof LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg</p>
<p>OK-PL-48</p>	<p>36*3in1 LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 120/180W LED: 36PCS*3IN1 RGB LED: 36PCS*4IN1 RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7/8CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-PL-40A</p>	<p>24PCS Aluminum LED Par Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-PL-69E</p>	<p>COB WHITE LED Par Aluminum</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED: 4PCS* 50W Warm White Cool White(WW/CW) LED: 4PCS* 60W RGBW 4IN1 Color Temperature: 3000K/ 5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature: temperature display Operation: RDM control Auto, DMX512, Sound, Master/Slave Channel: 2CH</p>

OK-PL-69A ZOOM	LED COB ZOOM PAR LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 110W LED: 1 x 100W WW/CW LED module Color Temperature: 3000K/ 5700K ZOOM : 9°/15°/20°/25°/30° Luminous Flux: 4973lm CRI: ≥96 DMX channel: 1/2/3 channels Control Mode: DMX512,Manual Display: LED display Data In/Out: 3-pin or 5-pin XLR Power In/Out: Power cord out Dimensions: 418x281x452mm Weight: 4.5kg</p>
OK-SL-100 ZOOM	LED COB ZOOM PAR LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1 x 200W COBWW/CW LED module Color Temperature: 3000K/ 5700K Zoom: 15°-52° CRI: ≥96 DMX Channel: 3CHs Control mode: Master/Slave; DMX512 control, Sound control and Stand-alone. Dimension: 278x455x292mm N.W.: 10.1KGs</p>
OK-SL-106	630 COB PAR Video LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 6PCS*30W RGBWA5 IN 1 COB LED: 6PCS*30W RGBWA UV 6 IN 1 COB Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM control ,Auto, DMX512,Sound, Master/Slave Channel: 9/10CH size: 20x20x20 (barn doors fold) net weight:4.3KG</p>
OK-SL-107	1810 PAR Video LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 350W LED: 18PCS*15W RGBWA5 IN 1 LED: 18PCS*18W RGBWA UV 6 IN 1 Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM control. Auto, DMX512,Sound, Master/Slave Channel: 9/10CH size: 20x20x20 (barn doors fold) net weight:4.2KG</p>
OK-SL-108	450 PAR Video LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 280W LED: 4PCS* 50W Warm White Cool White(WW/CW) LED: 4PCS* 60W RGBW 4IN1 Color Temperature: 3000K/ 5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH size: 20x20x20 (barn doors fold) net weight: 5.0KG</p>
OK-SL-109	200 PAR Video LIGHT		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K/ 5600K CRI: ≥96 Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH Size:23x20x20cm</p>

<p>OK-SL-110</p>	<p>200 Zoom PAR Video LIGHT</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K/ 5600K Zoom: 10°-55° CRI: ≥96 Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 3CH Size: 200*200*200mm</p>
<p>OK-SL-111</p>	<p>4812 PAR Video LIGHT</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 550W LED: 48PCS* 8W RGBW 4IN1 LED: 48PCS* 10W RGBWA 5IN1 LED: 48PCS* 12W RGBWA UV 6IN1 Beam Angle: 35° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH</p>
<p>OK-SL-110A</p>	<p>200W Zoom PAR LIGHT</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K-5600K Zoom: 8°-55° CRI: ≥95 Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 3CH</p>
<p>OK-SL-103S</p>	<p>MINI 2 Eyes LED Audience Ligh</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 100W LED:2pcs*50W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 6CH</p>
<p>OK-SL-104S</p>	<p>MINI 4 Eyes LED Audience Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED: 4pcs *50W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH</p>
<p>OK-SL-103</p>	<p>2 Eyes LED Audience Ligh</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED:2pcs * 100W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 2/6CH Dimension:: 440*210*210mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-SL-104</p>	<p>4 Eyes LED Audience Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 400W LED: 4pcs * 100W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 6/12CH Dimension:: 400*400*300mm N.W: 4kg G.W: 4.5kg</p>




OK-SL-101	LED Video Light		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED: White 200W COB LED 3200K (6500K available) Lamp luminous flux(lm) :95 Lamp luminous efficiency(lm/w) :8400 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 19°/36°are available) Dimmer: 0-100% linear dimming Operation: Auto, DMX512,, Master/Slave Channel: 2CH Dimension:: 640*280*220mm N.W: 7kg G.W: 7.5kg</p>
OK-SL-102	LED Video Light		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED: SMD LED 3200K (6500K available) Lamp luminous flux(lm) :95 Lamp luminous efficiency(lm/w) :8400 Dimmer: 0-100% linear dimming Operation: Auto, DMX512,, Master/Slave Channel: 2CH Dimension:: 640*280*220mm N.W: 7kg G.W: 7.5kg</p>
OK-PL-103B	Truss LED QUAD Lighting		<p>Voltage: AC110-240V, 50/60Hz Power: 20W LED: 3PCS*4W RGBW 4 IN 1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 8CH Dimension:: 150*140*140mm N.W: 1.5kg G.W: 2kg</p>


LED Plastic Par Light			
Model	Name	Picture	Describe
OK-PL-60R	60LED RGB 3in1 par light		<p>Voltage: AC110-240V, 50/60Hz Power: 80W LED: 60PCS*1.5W RGB 3in1 Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 7CH Dimension: 240x240x75mm N.W: 0.8kg G.W: 1.05kg</p>
OK-PL-9RN	9x4W LED Par light		<p>Voltage: AC110-240V, 50/60Hz Power: 36W LED: 9PCS*4W RGBA 4in1 mixed color Beam Angle: 25° Current: constant current Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Remote control Channel: 8CH Dimension:: 185*185*85mm N.W: 0.7kg G.W: 1kg</p>
OK-PL-61A	7PCS 4IN1 LED Par Light		<p>Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7PCS*8W RGBW 4IN1 LED: 7PCS*8W RGBWA/RGBWUV 5IN1 LED: 7PCS*8W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9CH Dimension: 190*190*150mm N.W: 1kg G.W: 1.5kg</p>
	7PCS 5IN1 LED Par Light		
	7PCS 6IN1 LED Par Light		

OK-PL-61C	4in1 COB Par light		Voltage: AC110-240V, 50/60Hz Power: 50W LED: 50W COB RGBWA 5IN1 Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension: 190*190*150mm N.W: 1.2kg G.W: 1.5kg
OK-PL-101	6PCS LED COB PAR		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 6PCS*30W RGB 3 IN 1 COB LED: 6PCS*30W RGBW 4 IN 1 COB Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 7/8CH Dimension:: 215*210*100mm N.W: 1.5kg G.W: 2kg
OK-PL-71	9PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 9PCS*6W RGBW 4 IN 1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-71A	18PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 18PCS*6W RGBW 4 IN 1 LED: 18PCS*6W RGBWA 5 IN 1 LED: 18PCS*6W RGBWAUV 6 IN 1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-100-II	54PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 54PCS*1W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-62	18PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 20W LED: 18PCS*1W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Remote control Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-PL-62A	24PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 24PCS*1W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Remote control Channel: 8CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg

OK-PL-62B	36PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 40W LED: 36PCS*1W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-PL7R4	7x4W LED Par light		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 7PCS*4W RGBW 4in1 LED Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Master/ Slave, Static Color, Hopping, Color Fade, Pulse, Auto Channel: 5/8CH Dimension:: 175*175*100mm N.W: 0.9kg G.W: 1.1kg
OK-PL6R4	6x4W LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 24W LED: 6PCS*4W RGBW 4in1 LED Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Master/ Slave, Static Color, Hopping, Color Fade, Pulse, Auto Channel: 8CH Dimension:: 130*130*130mm N.W: 0.9kg G.W: 1.0kg



Battery powered stage light





Model	Name	Picture	Describe
OK-3RB	3x4W RGBW 4in1 LED battery par		Voltage: AC110-240V, 50/60Hz. Power: 20-Watt Battery: 11.6V/ 4400MA Angle:35° LED Source:3x4-Watt 4IN1 RGBW LED Battery Life: 6-26 hours Charging time: 4-5 hours DMX Channel: 4/6/8 CH Size: 19.5x15x14.5cm / 7.7x5.9x5.7in Weight: 1.2KG /2.6LB
OK-6RB	APP control 6x18w RGBWA UV 6in1 Wireless Battery LED Par Light		Input voltage: AC100V-250V/50-60HZ / Power: 108W Light source: 6x18W high brightness LED lamp beads (6 in 1) Waterproof rating: IP22 Light source life: 50,000 hours Lens angle: 25° Control: DMX512, master-slave control, self-propelled, 2.4G wireless DMX512 Infrared Remote control, WiFi mobile APP control (support Apple, Android) Battery: Imported 18650 lithium battery * 12 sections 3 string 4 and 4 * 2400 = 9600 capacity Charge and discharge can reach more than 500 times Charging time: 5 hours full charge
OK-BAT-12	Battery + wireless DMX Waterproof connector 9PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 14000MA Power: 120W LED: 9PCS*8W RGBW 4 IN 1 LED: 9PCS*10W RGBWA 5 IN 1 LED: 9PCS*12W RGBWAUV 6 IN 1 Working time: 6-8 hours Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: RDM With Built- in fast 2.4G wireless DMX signal receiver / IR Control, master/slave, auto, sound active/Phone control Channel: 8/9/10CH

OK-BAT-12A	Battery + wireless DMX Waterproof connector 12PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 14000MA Power: 150W LED: 12PCS*8W RGBW 4 IN 1 LED: 12PCS*10W RGBWA 5 IN 1 LED: 12PCS*12W RGBWAUV 6 IN 1 Working time: 4-7 hours Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: • RDM With Built- in fast 2.4G wireless DMX signal receiver] / IR Control, master/slave, auto, sound active/Phone control Operation menu Channel: 8/9/10CH
OK-BAT-12AW	APP control + wireless DMX outdoor battery powered par light		Input voltage: AC100V-240V 50-60HZ Power: 200W Light Source: 12 *18W RGBWA UV 6in1 LED IP rating: IP65 DMX channels: 6/8/10CH Life span: 50,000 hours Lens angle: 40° (15° and 25° are also customizable) Control: DMX512, master-slave, auto mode, 2.4G wireless DMX512, Infrared remote control, APP control Battery: 9600mAh capacity Charging time: full charge in 6 hours Play time: RGBWAUV all on for 6 hours and single color for 15 hours. auto mode 5 hours Net weight: 4.5KG Gross Weight: 5.2KG
OK-BAT-5	18PCS Battery LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 4400MA Power: 20W LED: 18PCS*1W RGB Working time: 3-6 hours Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-BAT-6	24PCS Battery LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 5500MA Power: 30W LED: 24PCS*1W RGBW Working time: 3-6 hours Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-PL-31BAT	Battery LED PARTY BAR Derby Light		Battery: 12V 5800ma LED: 2*3PCS * RGB 3IN1 High brightness leds LED STROBE: 2*18PCS 5730 WHITE LEDDerby :2*4*3W (RGBW) LED. Working time: 4 hours Operation: Auto, DMX512, Sound, Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg







LED Lighting Package



Model	Name	Picture	Describe
-------	------	---------	----------

OK-PL-31P	LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED PAR:2*3PCS *4W RGBW leds LED BALL:2*4*3W (RGBW) LED. LED UV STROBE: 6*4W UV+W LEDS Laser power: 30mW 532nm green diode 100mW 650nm red diode Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31O	LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED PAR:2*3PCS *4W RGBW leds LED Derby :2*4*3W (RGBW) LED. Laser power: 30mW 532nm green diode 100mW 650nm red diode Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31Q	LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 96PCS/1W R.G.B.W(R*24.G*24.B*24 W*24) Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 8CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31A-RGBW	48PCS LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 48PCS/1W R.G.B.W(R*12.G*12.B*12.W*12) Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Remote control Channel: 8CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31A- RGB	48PCS LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 48PCS/3W R.G.B.W(R*48.G*48.B*48.W*48) Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Remote control Channel: 7CH Dimension: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31H	12PCS*4IN1 LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 12PCS/4W 4IN1RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 8CH Separate control Channel: 5/8/16/20 Dimension:: 900*340*160mm
OK-PL-31K	4PCS*COB LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 4PCS/30W 3IN1 COB RGB Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 7CH Separate control Channel: 4/7/12/16 Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31B	LED PARTY BAR Kaleido Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W) LED: 2*1*10W 4 IN 1 (RGBW)CREE LED. Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg







OK-PL-31B-1	6x4W LED par+moonflower		Voltage: AC110-240V, 50/60Hz Power: 60W LED:6PCS *4W RGB UV High brightness leds LED: 2*10W 4 IN 1 (RGBW) LED. Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31C	LED PARTY BAR Derby Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W) LED:2*4*3W (RGBW) LED. Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31D	LED PARTY BAR BEAM Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W) LED:2*60*5MM LEDs(red , green ,blue , white ,amber) Operation: Auto, DMX512,Sound,,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31F	LED PARTY BAR Ball Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W) LED:2*4*3W (RGBW) LED. Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31G	LED Magic Ball Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 36PCS/1W R.G.B.W(R*12.G*12.B*12) LED:4*3*1W (R*4G*4B*4) LED. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 8CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg
OK-PL-31S	LED Magic Ball Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 72PCS/1W R.G.B.W(R*24.G*24.B*24) LED:8*3*1W (R*8G*8B*8) LED. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound,Remote control Channel: 8CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg








LED Black Light			
Model	Name	Picture	Describe
OK-9BL	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 500*70*70mm N.W: 0.8kg G.W: 1kg
OK-005-36W	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 36W LED: 36PCS*1W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 410*46*48mm N.W: 0.3kg G.W: 0.4kg







OK-097-18BL	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 18W LED: 18PCS*1W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 410*125*90mm N.W: 1kg G.W: 1.2kg
OK-12BL	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 40W LED: 12PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 650*70*70mm N.W: 1kg G.W: 1.2kg
OK-18BL	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 105*70*70mm N.W: 1.3kg G.W: 1.5kg
OK-18BL-N	Power Linkable LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 900*105*80mm N.W: 1.5kg G.W: 1.8kg
OK-18BL-A	LED UV LIGHT		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimmer: 0-100% linear dimming Operation: Auto,DMX512,Sound,Master/Slave Channel: 7CH Dimension:: 380*170*170mm N.W: 1.8kg G.W: 2kg
OK-9BL-WP	9x3W IP65 LED UV LIGHT Bar		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9PCS*3W UV LED Angle: 120° IP rating: IP65 wavelength: 390-410nm Dimension:: 493*55*50mm N.W: 0.7kg G.W: 0.9kg


LED Wash Bar			
Model	Name	Picture	Describe
OK-24WL	24 x 3W RGB LED wall washer		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 24PCS*3W RGB3IN1 Beam Angle: 40° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 3/6/24/28CH Dimension:: 1020*105*80mm N.W: 2.5kg G.W: 2.8kg
OK-24WL-1	24x4W RGBA led wall washer		Voltage: AC110-240V, 50/60Hz Power: 96W LED: 24PCS*4W RGBA 4IN1 Beam Angle: 40° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 3/6/12/24/48CH Dimension:: 1020*105*80mm N.W: 2.5kg G.W: 2.8kg





OK-096-18WL	18x3W RGB 3in1 led wall washer		Voltage: AC110-240V, 50/60Hz Power: 60W Light Source: 18x3W RGB 3in1 LED Control Mode: Auto run, sound activated, DMX-512 Mode, and master slave mode DMX channels: 3/7/13 DMX Connection: 3-Pin XLR In/Out Beam Angle: 40° Display: LED Display Dimming: Electronic 0-100% Dimension: 102x6.5x6.5cm N.W.: 2.5kg
OK-PL-32M	Led Wall Bar		Voltage: AC110-240V, 50/60Hz Power: 50W LED: 9PCS* 4W RGBW 4IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming, Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH
OK-PL-32Y	720pcs Led pixelcontroller RGB+W Wall Strobe Bar		Voltage: AC110-240V, 50/60Hz Consumption: 200W LED RGB: 480*5050 LED RGB3IN1, LED White: 240*5730LED White, Operation: Operation: Auto, DMX512, Sound, Master/Slave Channel: 4/16/168CHs, Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 135° Dimmer: 0-100% linear dimming DMX in/out, Power in & Power out.
OK-PL-32CW	24 x 4 W TRI LED Bar		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 24PCS*4W RGBW 4IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg
OK-PL-32C BAT	BAT 24 x 3 W TRI LED Bar		Voltage: AC110-240V, 50/60Hz Power: 80/100W LED: 24PCS*3W RGB3IN1 LED: 24PCS*4W RGBW 4IN1 BAT: 11.6V 10000MA Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 3/6/24/28CH
OK-PL-32C BAT	BAT 24 x 4 W TRI LED Bar		Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg







OK-PL-32D	18pcs LED Wall Light		Voltage: AC110-240V, 50/60Hz Power: 180W LED: 18PCS*8W RGBW 4NI LED: 18PCS*10W RGBWA 5NI LED: 18PCS*12W RGBWA UV 6NI Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/27/72/82CH Dimension:: 1130*150*210mm N.W: 8kg G.W: 8.5kg
OK-095-24APPWL	72W LED APP Control Outdoor LED Wall Washer Light		Power: 72W Voltage: AC110-240V, 50/60Hz Light Source: 24pcs RGB 3in1 5050LED, 24pcs warm white LED, 24pcs cold white LED Control: app control APP: Fi Light IP rating: IP65 Dimming: Electronic 0-100% Dimension: 80x6x5cm N.W.: 1.5kg
OK-003-APPWL4	4-pack, APP control LED RGB wash light bar		Input: AC100V-240V,50Hz-60Hz Output:DC5V/4A Power: 12W Light Source: 96pcs 5050 RGB LED Beam Angle: 25° Control Mode: App or Remote(included) APP: LED LAMP Run mode: Auto run, static color, sound active mode Housing material: Aluminum alloy Dimension: 410x28x32cm x4 N.W.: 1.5kg
OK-007-60APP	60pcs led RGB app control light bar		Input: AC100V-240V,50Hz-60Hz Output:DC5V/4A Power: 12W Light Source: 60pcs 5050 RGB LED Beam Angle: 25° Control Mode: App or Remote(included) APP: LED LAMP Run mode: Auto run, static color, sound active mode Housing material: Aluminum alloy Dimension: 100x2.8x3.2cm N.W.: 1.0kg
OK-PL-25A	24pcs waterproof LED wash light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 24PCS*6W RGBW 4IN1 LED: 24PCS*6W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° IP rating: IP65 Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg
OK-PL-25	18PCS Led Wall Washer (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:200W Light source:18PCSx8 RGBW 4in1 LEDs Light source:18PCSx10 RGBWA 5in1 LEDs Light source:18PCSx12 RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/72CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Waterproof rate:IP65 Dimensions: 100*8.8*17cm 7.2kg Packing Size: 105*15*21cm 7.6kg 1pcs





OK-PL-26	14PCS Led Wall Washer (pixel controller)		Voltage:AC110-240V 50-60Hz Power consumption:200W Light source:14PCSx8 RGBW 4in1 LEDs Light source:14PCSx10 RGBWA 5in1 LEDs Light source:14PCSx12 RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/72CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Waterproof rate:IP65 Dimensions: 100*8.8*17cm 7.2kg Packing Size: 105*15*21cm 7.6kg 1pcs
OK-PL-32D	18pcs LED Wall Washer Light		Voltage: AC110-240V, 50/60Hz Power: 180W LED: 18PCS*10W RGBW 4NI LED: 18PCS*15W RGBWA 5NI Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/27/72/82CH Dimension:: 1130*150*210mm N.W: 8kg G.W: 8.5kg
OK-PL-32 E	24 PCS 5in1 Led Wall bar		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:24PCS RGBWA/RGBWUV 5in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:7/10/19/37/69CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32 F	24 PCS 6in1 Led Wall bar		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:24PCS RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:8/11/20/38/74CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32G	18PCS 5in1 Led Wall bar (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:18PCS RGBWA 5in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/94CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32H	18PCS 6in1 Led Wall bar (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:18PCS RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:10/23/112CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-25A	24pcs waterpoof LED wash light IP65		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 24PCS*6W RGBW 4IN1 LED: 24PCS*6W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg

OK-WL-W0721-IP65	72*3W RGBW LED Wall Washer IP65		Light source: 3W x 72pcs Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:25° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm Weight:7 kg
OK-WL-W0184-IP65	18*10W RGBW 4IN1 Wall Washer IP65, Pixel control		Light source: 10W RGBW 4IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm Weight:8kg
OK-WL-W0184-IP65-1	18*10W RGBW 4IN1 Wall Washer IP65, Non-Pixel control		
OK-WL-W0185-IP65	18*12W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA 5IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 5CH /9CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm Weight:8kg
OK-WL-W0185-IP65-1	18*12W RGBWA 5IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0186-IP65	18*12W RGBWAUV 6IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWAUV 6IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 6CH /10CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm Weight:8 kg
OK-WL-W0186-IP65-1	18*12W RGBWAUV 6IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0094-IP65	9*12W RGBW 4IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBW 4IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption: 160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm Weight: 5kg
OK-WL-W0094-IP65-1	9*12W RGBW 4IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0095-IP65	9*12W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA 5IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption:160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 5CH /9CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm Weight: 5 kg
OK-WL-W0095-IP65-1	9*12W RGBWA 5IN1 Wall Washer IP65, Non-Pixel Control		

OK-WL-W0096-IP65	9*12W RGBWA+UV 6IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA UV 6IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption: 160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 6CH /10CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm Weight:4.3 kg
OK-WL-W0096-IP65-1	9*12W RGBWA+UV 6IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0145-IP65	14*30W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 30W RGBWA 5IN1 x 14pcs Voltage: 100V~240V, 50/60Hz Power consumption: 320W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:45° Display: LED display DMX Channels: 24/10/80/70CH Electronic dimming: 0-100% Dimension: 1000 x 150x170 mm Weight:8.7 kg

LED Effect Light			
Model	Name	Picture	Describe
OK- E100	12PCSCW+ SMD RGB+STROBE TRI LED BAR		Voltage: AC110-240V, 50/60Hz Power: 100W Light Source: 12x5W 6° LED warm white+84x0.5W 5370 LED White+106x0.2W 5050 LED RGB Tri-color Control Mode: Auto run, color changing, sound active, DMX-512 Mode, and master slave mode DMX Connection: 3-Pin XLR In/Out DMX Channel: 5/14/75CH Display: LED Display Dimming: Electronic 0-100% Dimension: 110x8x15cm N.W.: 3.5kg
OK-105-36WL	36LED RGBW 4in1 beam light		Voltage: AC110-240V, 50/60Hz Consumption: 150W LED Wash: 36*4W CREE RGBW 4IN1 Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:4/6/9/48CHs, Color: RGB color can be mixed to more than 16.7 million kinds of color. Angle: Beam 1.5° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*9cm NW: 2.25KG /GW:2.65KG
OK-063-12WL	12pcs LED RGB 3in1 wash light & 12pcs LED warm white beam light		Voltage: AC110-240V, 50/60Hz Consumption: 80W LED Wash: 12*3W LED RGB3IN1, LED Beam: 12*3W CREE CW Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:4/6/10/11/48CHs, Color: RGB color can be mixed to more than 16.7 million kinds of color. Angle: Beam 3°+Wash 35° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*7cm NW: 2.25KG /GW:2.65KG
OK-23-144LED	144pcs RGB 3in1 LED pixel light bar		Voltage: AC110-240V, 50/60Hz Consumption: 60W LEDs: 144Pcs (12*12Pcs) SMD 5050 3IN1 RGB LEDs Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:3/5/8/36/40CHs, Beam Angle: 90° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*9cm NW: 1.75KG /GW:2.15KG

<p>OK-062-224WL</p>	<p>224pcs RGB 3in1 pixel light bar</p>		<p>Voltage:AC110-240V,50/60HZ Power:60W LED:224PCS SMD 5050 3IN1 RGB Operation:Operation:Auto,DMX512,Sound,Master/Slave DMX Channel:3/5/8/24/48/53 CH Beam Angle: 120° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*6.5*8.5cm NW: 1.5KG /GW:1.85KG</p>
<p>OK-103-288WL</p>	<p>288pcs RGBW led light bar</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 100W Light Source: 192x0.2W RGB 5050LED, 96x0.5W 5730 white LED DMX channels: 6/9/12/32/64 DMX Connection: 3-Pin XLR In/Out Display: LED Display Dimension: 110x10.2x10.2cm N.W.: 2.5kg</p>
<p>OK-VS-67B</p>	<p>960pcs RGB+W LED pixel control strobe light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 500W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5730LED White, Life: about 50,000 hours Flood angle: 135 ° Channel: 4/11/32/39CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode:Auto,Sound, DMX mode, master-slave mode, Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling</p>
<p>OK-006-384SL</p>	<p>384pcs RGBW led strobe light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 120W Light Source: 256pcs 5050 RGB LED, 128pcs 5730 white LED Control Mode: Auto run, sound active, DMX-512 Mode, and master slave mode DMX Connection: 3-Pin XLR In/Out DMX Channel: 6/9/64/112CH Dimension: 38x23x12cm N.W.: 2.5kg</p>
<p>OK-PL-54C</p>	<p>Waterproof 2in1 W+RGB STROBE Light</p>		<p>Voltage: AC110-240V, 50/60Hz Waterproof :IP65 Power: 500W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5757LED White, Life: about 50,000 hours Flood angle: 135 ° Channel: 4/16/48CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling</p>
<p>OK-PL-54E</p>	<p>2in1 W+RGB STROBE Moving Head Light</p>		<p>Voltage:AC110-240V,50/60HZ Waterproof :IP65 Power:600W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5757LED White, LED Beam Flood angle: 135 ° Pan movement: Y-axis:270° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C coolingOperation:Auto,DMX512,Sound,Master/Slave Channel: 8/20/52CH</p>

<p>OK-PL-1024</p>	<p>Led 1024PCS Strobe</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 400W LED RGBW: 1024*5050 LED RGBW4IN1 Life: about 50,000 hours Color: RGBW4in1 Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/6/9/16/32CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C</p>
<p>OK-PL-4326</p>	<p>36 PCS Diamond Beam+Strobe</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 400W LED RGB: 432pcs SMD 5050 RGB3IN1 LED LED Beam: 36pcs 3W CW CREE LED Life: about 50,000 hours Flood angle: 135 ° Beam angle: 2 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/6/15/144/252CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling</p>
<p>OK-VS-67</p>	<p>8-segment 960pcs 12-segment 1080pcs STROBE Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 500W LED: 960/1080*5050 LED Life: about 50,000 hours Color: RGB Flood angle: 135 ° 4-segment Channel: 5/26CH 12-segment Channel: 5/10/38CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, 4-segment Channel: 14/16CH 12-segment Channel: 5/10/38CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling Material: cold-rolled sheet + aluminum alloy + tempered glass Dimensions: 540x320x205mm Weight: 8.5 Kg</p>
<p>OK-PL-28</p>	<p>Led 1080PCS pixelcontroller Wall Strobe Bar</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 800W LED RGB: 1080*5050 LED 48-segment Life: about 50,000 hours Color: RGB Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/5/6/10/84CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling Material: cold-rolled sheet + aluminum alloy + tempered glass</p>

<p>OK-PL-28A</p>	<p>2in1 W+RGB Led 1092PCS pixelcontroller Wall Strobe Bar</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 800W LED RGB: 672*5050 LED 24-segment LED White:420*5730 LED 12-segment Life: about 50,000 hours Color: RGB+W Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/5/6/10/84CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling Material: cold-rolled sheet + aluminum alloy + tempered glass</p>
<p>OK-PL-32A</p>	<p>14x3W pixel control LED+SMD light bar</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 80W LED: 14PCS*3W CREE CW White(2600K) 56PCS*5050 SMD RGB Beam Angle: 4° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 6/9/51CH Dimension:: 1050*105*80mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-VS-38</p>	<p>LED STROBE Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 80W LED: 168pcs5730SMD WHITE LED LED :72PCS 5050SMD RGB LED Operation: Auto, DMX512, Sound, Channel: 5/14CH</p>
<p>OK-PL-5SW</p>	<p>mini Strobe white</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 9W LED: 54PCS*0.2W 2835 SMD WHITE Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 135° Dimmer: 0-100% linear dimming Operation: Auto, Sound, Remote control</p>
<p>OK-PL-5SR</p>	<p>mini Strobe RGB</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 10W LED: 78PCS*0.2W SMD2835 white 16.7 million kinds of color. Beam Angle: 135° Dimmer: 0-100% linear dimming Operation: Auto, Sound, Remote control</p>
<p>OK-008-72SL</p>	<p>72pcs RGB 3in1 5050LED light bar</p>		<p>Voltage: AC100-240V, 50/60Hz Power: 18W Light Source: 72pcs RGB 3in1 5050LED Control Mode: Auto run, sound active, DMX, remote control DMX channels: 8/24 DMX Connection: 3-Pin XLR In/Out Beam Angle: 120° Housing: aluminum alloy Dimension: 39x6.2x 5.8cm N.W.: 0.9kg</p>
<p>OK-VS-15</p>	<p>Gobo Effect, Ball Effect, Strobe/Chase and green & red laser effect</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 50W LED Strobe: 1PCS *20W White LED BALL Effect: 3PCS*3W LED RGB LED Gobo Effect: 6PCS*3W LED RGBW Laser Effect: Red 120mw & Green 30mw Beam Angle: 15° Operation: Auto, DMX512, Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 12CH Dimension:: 450*300*210mm N.W: 4kg G.W: 4.5kg</p>

OK-VS-6	Derby effect Strobe and Laser Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED Strobe:6PCS *3W White LED Derby Effect1: 4PCS*3W LED RGBW LED Derby Effect2: 4PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Operation: Auto,Sound Standalone modes: auto programs, sound programs
OK-VS-37	LED Waterwave Effect Light		Voltage:AC110-240V,50/60HZ Power:80W LED:6x12W CREE RGBW LED Beam Angle:4-35° Operation:Auto,DMX512,Sound, Channel:10CH
OK-VS-80	Derby Matrix Beam Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED:24pcs * 3W RGBW LEDs Beam Angle: 8° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 4/26CH Dimension:: 320*290*290mm N.W: 4kg G.W: 4.5kg
OK-VS-81	Derby and Strobe Effect Light		Voltage: AC110-240V, 50/60Hz Power: 100W Derby LED : 20pcs *3W RGBA Strobe: 12PCS*1W white LEDs Beam Angle: 8° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 4/28CH Dimension:: 320*350*290mm N.W: 4kg G.W: 4.5kg
OK-VS-82	Derby Matrix Beam Light		Voltage: AC110-240V, 50/60Hz Power: 90W LED:24pcs * 3W RGBW LEDs Beam Angle: 8° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 4/26CH Dimension:: 320*350*290mm N.W: 4kg G.W: 4.5kg
OK-VS-83	5-in-1 LED Effect Light		Voltage: AC110-240V, 50/60Hz Power: 90W LED:9PCS 4W RGBW 4IN1 LEDs Flower Effect: 84PCS 5mmLED Laser Effect: Red 120mw& Green 30mw Beam Angle: 45° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 11/23CH Dimension:: 320*350*290mm N.W: 4kg G.W: 4.5kg
OK-VS-84	Ball , Strobe /Chase and Laser		Voltage: AC110-240V, 50/60Hz Power: 60W LED Strobe:8PCS *3W RGBA LED BALL Effect: 6PCS*3W LED RGBWAP Laser Effect: Red 120mw& Green 30mw Beam Angle: 15° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 15CH Dimension:: 350*250*210mm N.W: 4kg G.W: 4.5kg
OK-VS-85	Gobo Effect, Strobe/Chase and Laser effect		Voltage: AC110-240V, 50/60Hz Power: 60W LED Strobe:8PCS *3W RGBW LED GOBO Effect: 8PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 15° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 17CH Dimension:: 350*250*210mm N.W: 4kg G.W: 4.5kg

<p>OK-VS-86</p>	<p>Gobo Effect, Derby Effect, Strobe/Chase and green & red laser effect</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 100W LED Strobe:8PCS *3W RGBW LED GOBO Effect: 8PCS*3W LED RGBW LED Derby Effect: 4PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 15° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 23CH Dimension:: 450*300*210mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-VS-87</p>	<p>Ball, Derby effect Strobe and Laser Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 100W LED Strobe:8PCS *3W RGBW LED BALL Effect: 6PCS*3W LED RGBWAP LED Derby Effect: 4PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 15° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 22CH Dimension:: 450*300*210mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-SM10</p>	<p>LED Magic Ball Gobo Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 50W LED BALL Effect: 8PCS*3W LED RGBW LED GOBO Effect: 4PCS*3W LED RGBW Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 8CH Dimension:: 270*260*330mm N.W: 4kg G.W: 4.5kg</p>
<p>OK-VS-5B</p>	<p>3in1 LED Strobe/UV Derby Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 60W LED: 2pcs * 10W RGBW 4IN1 CREE LEDs LED: 12pcs UV+WHITE 2IN1 LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 10CH Dimension:: 330*220*200mm N.W: 1.5kg G.W: 2kg</p>
<p>OK-VS-58D</p>	<p>3in1 LED Strobe/UV Derby Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 10CH Dimension:: 230*220*200mm N.W: 1.5kg G.W: 2kg</p>
<p>OK-VS-59A</p>	<p>4in1 LED Strobe/UV Derby Laser Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs Laser Effect: Red 120mw& Green 30mw Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave Laser Effect: Red 120mw& Green 30mw Channel: 12CH Dimension:: 250*230*210mm N.W: 1.5kg G.W: 2kg</p>
<p>OK-VS-16</p>	<p>6IN1 LED LIGHT</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 60W LED BALL: 6pcs * 3W RGB LEDs BEAM:12PCS*3w RGBW UV:8PCS*3W UV LED Strobe:80pcs SMD 5730 LED LED Effect: 8PCS *3W RGBW LED Laser Effect: Red 120mw& Green 30mw Operation: Auto, DMX512,Sound, Master/Slave</p>
<p>OK-VS-17</p>	<p>4IN1 LED LIGHT</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 60W LED BEAM: 4pcs * 10W RGBW CREE LEDs UV:12PCS*3W UV LED Strobe:2pcs *20W COB LED Laser Effect: Red 200mw& Green 80mw Blue:150mw Operation: Auto, DMX512,Sound, Master/Slave</p>

<p>OK-VS-18</p>	<p>5IN1 LED Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 30W LED: 6pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs WATERWAVE:1*5W RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave</p>
<p>OK-VS-58-9C</p>	<p>9 Colors LED Derby Light With Plastic Lens</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 8CH Dimension:: 230*220*200mm N.W: 1.5kg G.W: 2kg</p>
<p>OK-VS-59</p>	<p>Laser Derby Light</p>		<p>Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs Laser Effect: Red 120mw& Green 30mw Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave Laser Effect: Red 120mw& Green 30mw Channel: 8CH Dimension:: 250*230*210mm N.W: 1.5kg G.W: 2kg</p>