

## Shenzhen HUAYINGTONG Electronic Co., Ltd.

B08, 2/F, Block B, Wanzhongrunfeng Business Park, Minzhi Road,, Minzhi Road, Longhua Dist. Shenzhen, China

Contact: Ada Deng

Phone: 86-755-23056465 Tel/wechat: 86-19926401381 Email: ada@oppsk.com

Website: <https://www.oppsk.com/>

Alibaba site: <https://oppsk.en.alibaba.com>



Moving Head Beam			
Model	Name	Picture	Describe
OK-MH-350W	<b>WATERPROOF 350W 17R Beam Moving Head</b>		Power supply: AC90-245V 50/60Hz Light source: 350W 17R Beam Angle:2° Color wheel: 13 color +blank with rainbow effect Gobo wheel: 13 gobos +white Prism : 24 Prism (16+8) rotating Len diamter: 145mm Focus: Electronic focusing Dimming: 0-100% linear dimming Pan/tilt: 540° /270° DMX channel: 16CH Display: LED display IP rating: IP65 Control mode: DMX512, Auto, master/slave Dimension: 370x300x680mm Net Weight: 23KG Gross weight: 25KG
OK-MH-421	<b>420 Beam Wash Moving Head</b>		Power Supply: 110-240V AC,50/60Hz Power Consumption: 600W Light Source: 420W OSRAM Color wheel: 14 color + blank color wheel Static Gobo wheel: 17 gobos Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: multi-class beam adjustment Movement: Pan: 540° Optional Tilt: 270°
OK-MH-380	<b>380 Beam Wash Moving Head</b>		Power Supply: 110-240V AC,50/60Hz Power Consumption: 550W Light Source:380W 8000k fenghuang/380WPhilips/371 OSRAM Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment
OK-MH-380A	<b>380 LED Ring Beam Wash Moving Head</b>		Power Supply: 110-240V AC,50/60Hz Power Consumption: 550W Light Source:380W 8000k fenghuang/380WPhilips/371 OSRAM LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: 8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo

<p>OK-MH-380BSW</p>	<p>380 Beam Spot Wash 3 IN 1 Moving Head Light</p>		<p>Voltage AC : 110-240V,50/60HZ Power:500W LAMP:371W Osram Color wheel: 13 color + blank color wheel,can be half color effect Rotating Gobo wheel: 9 optional plug-in design + white speed jitter / bidirectional flow effec Static Gobo wheel:14 gobos speed jitter / bidirectional flow effec Prism: 2 independently rotating prism, wherein a prism with zoom function, dcan also be equipped with 8+16/16+24/24+32 prism Prism 1: 16-facet circular prism rotating Prism 2: T linear prism rotating/8/16-facet circular prism rotating Frost effect : 8-60°adjustable Wash effects angle Lens: <u>high precision optical lens</u></p>
<p>OK-MH-350BSW</p>	<p>350 Beam Spot Wash 3 IN 1 Moving Head Light</p>		<p>Voltage AC : 110-240V,50/60HZ Power:500W LAMP:350W 8000K/fenghuang Color wheel: 13 color + blank color wheel,can be half color effect Rotating Gobo wheel: 9 optional plug-in design + white speed jitter / bidirectional flow effec Static Gobo wheel:14 gobos speed jitter / bidirectional flow effec Prism: 2 independently rotating prism, wherein a prism with zoom function, dcan also be equipped with 8+6/16+6/24+6 prism Prism 1: 16-facet circular prism rotating Prism 2: T linear prism rotating 6-facet circular prism rotating Frost effect : adjustable Wash effects angle Lens: <u>high precision optical lens</u></p>
<p>OK-MH-300</p>	<p>280W/300W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60HZ Power Consumption: 400W Light Source: 280W Philips/300w Philips Long life 6000 hour Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment Beam: <u>multi-class beam adjustment</u></p>
<p>OK-MH-300A</p>	<p>LED Ring 280W/300W Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 400W Light Source: 280W Philips/300w Philips Long life 6000 hour LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: <u>3 phase motor</u></p>
<p>OK-MH-275</p>	<p>275 Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W Philips/275W fenghuang Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment</p>

<p>OK-MH-275A</p>	<p>275 LED Ring Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W Philips/275W fenghuang LED: 30pcs SMD3in1 halo Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Prism effect 3:color Prism Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo</p>
<p>OK-MH-250A</p>	<p>MINI 250 Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 350W Light Source: 250W fenghuang LED: 30pcs SMD3in1 halo Color wheel: 12 color + blank color wheel Half color, bidirectional flow effec Static Gobo wheel: 14 gobos,speed jitter / bidirectional flow effec Prism 1: 24-facet circular prism rotating Prism 2: T linear prism rotating/8-facet circular prism rotating Frost: adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 3 phase motor Fixed zoom: Fixed zoom beam/gobo Focus: Linear adjustment</p>
<p>OK-MH-230</p>	<p>200W 5R/230W 7R Beam Wash Moving Head</p>		<p>Power Supply: 110-240V AC,50/60Hz Power Consumption: 300W Light Source: 230W 8000k /fenghuang 7R/5R Color wheel: 14 color + blank color wheel,can be half color effect Static Gobo wheel:17 gobos speed jitter / bidirectional flow effec Prism : 16-facet circular prism rotating Frost effect : adjustable Wash effects angle Lens: 3in1 optical high precision optical combination lens Motor: 2/3 phase motor Focus: Linear adjustment Beam: multi-class beam adjustment Movement Pan: 540° Optional Tilt: 270° Strobe/shutter: Double lens strobe, 0-13 Hz or random</p>
<p>OK-LS-480A</p>	<p>WATERPROOF 461 Beam Spot Wash</p>		<p>Voltage: 100-240V, 50/60Hz Lamp: Original Osram 461W Power: 680W Color: Pure color imported from Italy, a color plate, there are 13 color plates +1 white light Pattern plate: two pattern plate, fixed pattern plate 14 patterns + white light, rotating pattern plate 9 pattern pieces, customizable LOGO, pattern can be linear infinite zoom Rotating pattern diameter :12mm effective inner diameter :11mm Effect Wheel: A round 8 prism, 0-100% mechanical dimming, support mechanical stroboscopic and adjustable stroboscopic effect, support strobe macro function. Lens group optical system, electric focus, beam Angle 2.5 ~ 45°. Photoelectric reset system, when accidental misoperation, can automatically retrieve reset. Rotation Angle 540° horizontal, 8Bit/16Bit resolution, 270° vertical, 8Bit/16Bit resolution. Overheat protection. Electronic rectifier.</p>

<p>OK-LS-480</p>	<p>WATERPROOF 461W Beam Wash Moving Head</p>		<p>Voltage: 110V-240V 50-60Hz Lamp: Original Osram 461W Power factor: 0.985 Total power: 680W Color: Imported from Italy pure color: 13+1+ colorful rainbow effect + Atomization function, Pattern: Pattern Plate: 14 fixed pattern +1 white light Focusing: Electronic linear HD dynamic focusing, using high density glass optical lens. Linear dimming curve: 0%-100% linear dimming Stroboscopic: 1-25Hz fast stroboscopic, with pulse stroboscopic, synchronous and asynchronous stroboscopic effect Beam Angle: 0-1.8° Luminaire intelligence: Intelligent gyroscope induction position state, intelligent adjustment of fan speed, so as to effectively increase the service life of the bulb, fan driving performance is excellent, very low noise. Channel: 16 /20 international standard DMX512 channels. System heat dissipation: Large copper tube is used for heat dissipation, so as to ensure water resistance and heat dissipation of high-power bulbs Temperature intelligent monitoring technology, automatic adjustment of heat dissipation system, effective control of lamp temperature. Dehumidification system: Intelligent dehumidification system, air pressure compensation design, Effectively ensure the life of lamps and lanterns Modular design: <del>From production to assembly, replacement parts are</del></p>
<p>OK-LS-380</p>	<p>WATERPROOF 380W Beam Wash Moving Head</p>		<p>Voltage: 110V-240V 50-60Hz Lamp: Original Osram 371W Power factor: 0.985 Total power: 680W Color: Imported from Italy pure color: 13+1+ colorful rainbow effect + Atomization function, Pattern: Pattern Plate: 14 fixed pattern +1 white light Focusing: Electronic linear HD dynamic focusing, using high density glass optical lens. Linear dimming curve: 0%-100% linear dimming Stroboscopic: 1-25Hz fast stroboscopic, with pulse stroboscopic, synchronous and asynchronous stroboscopic effect Beam Angle: 0-1.8° Luminaire intelligence: Intelligent gyroscope induction position state, intelligent adjustment of fan speed, so as to effectively increase the service life of the bulb, fan driving performance is excellent, very low noise. Channel: 16 /20 international standard DMX512 channels. System heat dissipation: Large copper tube is used for heat dissipation, so as to ensure water resistance</p>
<p>OK-LED-600</p>	<p>LED 600W Beam Spot Wash Framing Moving Headwith CMY&amp;CTO</p>		<p>Input voltage: AC100-240V, 50/60Hz Amount of power: 900W Light source: 600W LED module LED life: 20,000 hours Color temperature: 6800K Diameter: 135mm Color rendering index: standard mode Ra&gt;72, high display mode Ra&gt;90 Luminous flux: 24000LM Power interface: 16A power plug Signal interface: three-core XLR Control mode: DMX512, RDM Channel mode: 36 international standard DMX512 channels Display: 2.7-inch touch LCD display, Chinese and English display, 180-degree rotation Fixed color: 6 colors + Open Color mixing system: independent CMY color mixing system Color temperature adjustment: independent CTO2500-7000K linear adjustment Prism: 3 prisms Animation plate: dazzling simulation of dynamic</p>

OK-MH-LED700	LED 700W Beam Spot Wash Framing Moving Headwith CMY&CTO		<p>Input voltage: AC100-240V, 50/60Hz  Power: 980W  Light source: 700W LED module  LED life: 20,000 hours  Diameter: 138mm  Color temperature: 6800K  Color rendering index: standard mode Ra&gt;75, high display mode Ra&gt;90  Luminous flux: 24000LM  Power interface: 16A power plug  Signal interface: three-core XLR  Control mode: DMX512, RDM  Channel mode: 36chs international standard DMX512 channels  Display system: 2.5-inch touch LCD display, Chinese and English display, 180-degree rotation  Fixed color: 7 colors + Open  Color mixing system: independent CMY color mixing system  Color temperature adjustment: independent  CTO 2700K-7000K linear adjustment  Prism: rotating 3 prisms + 6 Linear Prims  Effect panel: dazzling simulation of dynamic swaying flames, gurgling water and other dynamic effects  Fixed Gobo: 8 plug-in fixed gobos with an outer diameter of 25.4mm + white circle</p>
--------------	--	---	--

LED Moving Head			
Model	Name	Picture	Describe
OK-MHLED-400	LED 400W Beam Wash Spot Moving Head with CMY		<p>voltage: AC110V-240V/50-60HZ  Power : 450W  LED: import LED Module 350W  LED: 50000 hours  illuminance: 5 meters 100,000 lm  LED: 8000K  CRI&gt;85  Dimming system: 0-100% linear adjustment  Focusing system: linear adjustment from 4° -50 °  Frost: adjustable Wash effects angle  Spot zoom angle: 4-35 °  Wash angle:10-50°  High-speed strobe: 0-30 times/sec. Adjustable speed  strobe effect. Strobe macro function. CONTROL</p>
OK-MHLED-250	250W LED Spot Beam Moving Head Light		<p>Input Voltage: 100-240V 50/60 Hz  Light Source: 250W white LED COB  LED: 50000 hours  LED: 8000K  CRI&gt;85  Gobos: one static gobo wheel: 9 static gobos+ open  one rotating gobo wheel: 7 interchangeable,  rotating, indexable gobos + open  Color: one color wheel, 9 colors + Open, half-color and  rainbow effect  Prism: 3 facet prism  Zoom: 11° ~ 27° linear zoom  Dimming: 0 ~ 100% linear dimming  Strobe: With strobe effect  Frost: Fine wash effect  Display: LCD display  Channel: 18CH  Control Mode: DMX 512,Auto-running ,Master/salve,  Sound active, Built-in program  Movement: Pan 540°; Tilt 270°;  Auto X/Y repositioning, fast, quiet and smooth</p>

OK-MHLED-200	LED 200W Beam Wash Moving Head		<p>Power Supply: 110-240V AC,50/60Hz  Power Consumption: 300W  Light Source: import LED Module 200W  Color wheel: 14 color + blank color wheel Half color, bidirectional flow effec  Static Gobo wheel: 17 gobos,speed jitter / bidirectional flow effec  Prism 1: 24-facet circular prism rotating  Prism 2: T linear prism rotating/8-facet circular prism rotating  Prism effect 3:color Prism  Frost: adjustable Wash effects angle  Lens: 3in1 optical high precision optical combination lens  Motor: 3 phase motor  Fixed zoom: Fixed zoom beam/gobo  Focus: Linear adjustment  Beam: multi-class beam adjustment  Movement: Pan: 540°  Optional Tilt: 270°  Beam Angle: Parallel beam angel 0-2.3°  Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe  DMX Channels: 16/20Channels DMX</p>
OK-MHLED-100C	LED100W Beam Wash Moving Head		<p>Power Supply: 110-240V AC,50/60Hz  Power Consumption: 350W  Light Source: import LED Module 100W  Color wheel: 12 color + blank color wheel Half color, bidirectional flow effec  Static Gobo wheel: 14 gobos,speed jitter / bidirectional flow effec  Prism 1: 24-facet circular prism rotating  Prism 2: T linear prism rotating/8-facet circular prism rotating  Frost: adjustable Wash effects angle  Lens: 3in1 optical high precision optical combination lens  Motor: 3 phase motor  Fixed zoom: Fixed zoom beam/gobo  Focus: Linear adjustment</p>
OK-MHLED-230	230W Spot Moving Head Light		<p>Input power:AC100-240V 50/60 Hz  Power consumption :260W  DMX channel:6/18 channels  Pan scan: 540°(16bit) Electric correction  Tilt scan: 270° (16bit) Electric correction  Color wheel: one color wheel, 7 kinds of color chips in one color wheel  Static Gobo: 7gobos+open  Rotation Gobo:7 gobos+open  Effect Wheel: two Effect prism,one Rotation six prism,one Rotation five prism effect move  Lens optical system mechanical focus .beam Zoom angle 11°-24°  Control mode:DMX512/Master-Slave/Auto run  Display:LCD display  WEIGHT&amp;SIZE</p>
OK-MHLED-150	150W Spot Moving Head Light		<p>Input power:AC100-240V 50/60 Hz  Power consumption :170W  LED source: 1 x 150W LED  DMX channel:16 channels  Pan scan: 540°(16bit) Electric correction  Tilt scan: 270° (16bit) Electric correction  Color wheel: one color wheel, 7 kinds of color chips in one color wheel  Static Gobo: 7gobos+open  Rotation Gobo:6 gobos+open  Beam angle:16 degree  Effect Wheel: one Rotation three-faced prism  Frost  RDM function  Effect move , Bi-directional rotation  Lens optical system mechanical focus</p>








OK-MHLED-100	100W Spot Moving Head Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 120W  LED: 1pcs*100W LED white  Beam angle: 18°  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Color wheel: 7 color + open ,rainbow -flow effect  Static Gobo: 6gobos+open  Rotation Gobo:6 gobos+open  Prism: 3-facet prism , adjustable rotation speed &amp;double  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 13CH  Dimension: 480*290*290mm  N.W: 8kg G.W: 9kg</p>
OK-MHLED-150A	150W LED BEAM Moving Head		<p>Power Supply: 110-240V AC,50/60Hz  Power Consumption: 180W  Light Source: 150W 8000k  Color wheel: 13 color + blank color wheel  Static Gobo wheel: 17 gobos  Prism : 8-facet circular prism rotating  or 16-facet circular prism rotating  Frost: adjustable Wash effects angle  Lens: 3in1 optical high precision optical combination lens  Fixed zoom: Fixed zoom beam/gobo</p>
OK-MHLED-120	120W LEDBEAM		<p>Power Supply: 110-240V AC,50/60Hz  Power Consumption: 120W  Light Source: 120W 8000k  Color wheel: 13 color + blank color wheel  Static Gobo wheel: 12 gobos  Prism : 16-facet circular prism rotating  Frost: adjustable Wash effects angle  Lens: 3in1 optical high precision optical combination lens  Fixed zoom: Fixed zoom beam/gobo  Focus: Linear adjustment</p>
OK-MHLED-100A	100W LED BEAM Moving Head		<p>Power Supply: 110-240V AC,50/60Hz  Power Consumption: 120W  Light Source: 100W 8000k  Color wheel: 13 color + blank color wheel  Static Gobo wheel: 12 gobos  Prism : 16-facet circular prism rotating  Frost: adjustable Wash effects angle  Lens: 3in1 optical high precision optical combination lens  Fixed zoom: Fixed zoom beam/gobo  Focus: Linear adjustment  Beam: multi-class beam adjustment  Movement: Pan: 540°  Optional Tilt: 270°  Beam Angle: Parallel beam angel 0-2.3°  Strobe/shutter:Double lens strobe, 0-13 Hz or random strobe  DMX Channels: 16/20Channels DMX  Dimension: 580*460*460mm  N.W: 11kg G.W: 12kg</p>
OK-MH-1	37PCS 15W LED Zoom Moving Head	36pcs*10W LED Moving Head Light With Zoom	<p>Voltage: AC110-240V, 50/60Hz  Power: 500W  LED:37*15W Osram RGBW 4IN1  Beam angle: 4.5° -45°  Pan Tilt movement: X-axis:540° , Y-axis: 270°  Dimmer: 0-100% linear dimming  Strobe: 0-20 HZ Operation: RDM,Auto, DMX512, Sound, Master/Slave  Channel:24/36/48CH</p>
OK-MH-2	36pcs*10W LED Moving Head Light With Zoom		<p>Voltage: AC110-240V, 50/60Hz  Power: 400W  LED: 36*10W RGBW 4-in-1 led  LED: 36*18W RGBW 6-in-1 led  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Zoom: 12° - 58°  Total Output: 2000 lux at 2 meter for maximum beam angel 58°,22600 lux at 2 meter for minimum beam angel 11°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 16CH  Dimension:: 420*300*390mm  N.W: 9kg G.W: 10kg</p>

OK-MH-3	19pcs*12W Beam LED Zoom Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 300W LED: 19*12W 4 in 1 RGBW CREE led Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Zoom: 10° - 60° Total Output: 2000 lux at 2 meter for maximum beam angel 58°, 22600 lux at 2 meter for minimum beam angel 11° Dimmer: 0-100% linear dimming Strobe: Electric strobe, 0.3-25 times second Operation: Auto, DMX512, Sound, Master/Slave Channel: 16CH
OK-MH-4	LED EYE Beam Wash Moving Head Light		Voltage: AC110-240V, 50/60HZ Power: 400W LED: 19PCS CREE 15W RGBW 4IN1 Zoom: 3.8-35° Optical lens: light guide rod + integrated high guide lens Front lens disc: bidirectional endless rotation, seamless splicing lens disc, aspheric lens structure Effect mode: beam, digital (vortex, kaleidoscope, etc.) Strobe: 1-25 times/second electronic strobe and random strobe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Z-axis: infinite tilt Display: LCD display, Chinese/English (optional),
OK-MH-5	LED EYE Beam Wash Moving Head Light		Voltage: AC110-240V, 50/60HZ Power: 350W LED: 7PCS OSRAM 40W RGBW 4IN1 Zoom: 3.8-35° Optical lens: light guide rod + integrated high guide lens Front lens disc: bidirectional endless rotation, seamless splicing lens disc, aspheric lens structure Effect mode: beam, digital (vortex, kaleidoscope, etc.) Strobe: 1-25 times/second electronic strobe and random strobe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Z-axis: infinite tilt
OK-MH-6	740 LED Zoom Moving Head		Voltage: AC110-240V, 50/60Hz Power: 350W LED: 7*40W Osram RGBW 4IN1 Beam angle: 4.5° -45° Pan Tilt movement: X-axis: 540°, Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: 0-20 HZ Operation: RDM, Auto, DMX512, Sound, Master/Slave Channel: 11/18/58CH
OK-MH-7	715 LED Zoom Moving Head		Voltage: AC110-240V, 50/60HZ Power: 120W LED: 7PCS CREE 15W RGBW 4IN1 Zoom: 5-35° Optical lens: integrated high guide lens Front lens disc: wash beam Strobe: 1-25 times/second electronic strobe and random strobe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Auto rotate screen Operation: Auto, DMX512, Sound, Master/Slave DMX512 protocol Channel: 15/CH
OK-MH-8	knife		Voltage: AC110-240V, 50/60HZ Power: 1000W LED BEAM: 5PCS OSRAM 60W RGBW 4IN1 LED STROBE: 36PCS 18W WHITE STROBE Zoom: 2.8-55° Optical lens: light guide rod + integrated high guide lens Strobe: 1-25 times/second electronic strobe and random strobe Dimming: electronic dimming, super smooth and flicker free Pan/Tilt movement: X-axis: infinite tilt, Y-axis: infinite tilt Display: LCD display, Chinese/English (optional), Auto rotate screen Operation: Auto, DMX512, Sound, Master/Slave Feature: Fan intelligent control; Electronic sensor detection; Monitoring of the level of the channel Communication protocol: Standard DMX512 protocol Channel: 23/61CH Shell: high strength fire and temperature resistant engineering plastic shell and metal powder spray technology, streamline appearance design




OK-MH-9	1030 BEAM Moving Head Light		Voltage:AC110-240V,50/60HZ Power:300W LED:High Power 10PCS 30W RGBW 4IN1 OSRAM LED Beam Angle:3.8° Pan movement: Y-axis:150° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation:Auto,DMX512,Sound,Master/Slave Channel:7/13/43CH
OK-MH-10	Super Beam Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED:4pcs*25W high brightness white leds. Beam angle: 5-40 degree Pan Tilt movement: X-axis:540° , Y-axis: 270° Z-axis:infinite tilt Color wheel: with a Red Blue Yellow color wheel create colorful effect with running water effect Feature: 8pcs lens Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/15 CH Dimension: 460*320*250mm N.W: 6kg G.W: 6.5kg
OK-MH-11	Double BEAM LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED:14pcs*10W RGBW 4IN1 CREE Beam angle: 6° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/16 CH Dimension: 360*310*210mm N.W: 6kg G.W: 6.5kg
OK-MH-12	LED Beam Strobe Moving Head		Voltage: AC110-240V, 50/60Hz Power: 150W LED:12*10W RGBW CREE 4IN1 LED Strobe:6*10W White COB Beam angle: 6° Pan Tilt movement: X-axis:infinite tilt , Y-axis: 270° Dimmer: 0-100% linear dimming Strobe: Electric strobe, 0.3-25 times second Operation: Auto, DMX512, Sound, Master/Slave Channel:12CH
OK-MH-13	LED Beam SMD Moving Head		Voltage: AC110/220V 50-60HZ Power: 120W LED:8*10W RGBW CREE 4IN1 SMD:5050*96PCS Operation: Auto, sound , master-slave, DMX512, SIZE:26.5*20*38cm net weight: 4KG gross weight: 5KG packing size: 67*53*45cm 4pcs/Ctn (22KG)
OK-PL-94F	3-facet prism Spot Wash Moving Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 1pcs*60W LED white Beam angle: 18° Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Color : 6color + blank color wheel Gobo : Gobo: 7gobos+open Prism: 3-facet prism , adjustable rotation speed &double Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave







OK-PL-94E	Spot Wash Moving Light		<p>Voltage: AC110-240V,50/60HZ  Power:70W  LED:30W White  LED:6*8W RGBW 4IN1  Color : 6color + blank color wheel  Gobo : Gobo: 7gobos+open Angle: 13°  Pan Tilt movement: X-axis:540° , Y-axis: 270°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe, 0.3-25 times second  Operation: Auto, DMX512, Sound, Master/Slave  Channel:13CH</p>
OK-PL-94A	60W LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED: 1pcs*60W CREE LED white  Beam angle: 13°  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Color wheel: 7 color + open ,rainbow -flow effect  Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9/11CH  Dimension: 290*260*210mm  N.W: 3.5kg G.W: 4.5kg</p>
OK-PL-94	30W LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED: 1pcs*30W CREE LED white  Beam angle: 13°  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Color wheel: 7 color + open ,rainbow -flow effect  Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9/11CH  Dimension: 290*260*210mm  N.W: 3.5kg G.W: 4.5kg</p>
OK-PL-94B	30W SMD LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED: 1pcs*30W LED white  LED: 8PCS*5050SMD  Beam angle: 13°  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Color wheel: 7 color + open ,rainbow -flow effect  Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9/11CH  Dimension: 290*260*210mm  N.W: 3.5kg G.W: 4.5kg</p>
OK-PL-74	12W LED Moving Head Spot Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 20W  LED: 1pcs*12W CREE LED white  Beam angle: 13°  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  Color wheel: 7 color + open ,rainbow -flow effect  Gobo wheel: 7 gobo +open, gobo - flow effect, gobo shake  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9/11CH  Dimension: 260*240*210mm  N.W: 3kg G.W: 4kg</p>
OK-PL-58B	2-in-1 LED Effect Light LED BALL+BEAM Moving Head		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds  LED BEAM: 1pcs*10W 4in1 RGBW CREE leds  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  LEDBALL Angle: 2°  Beam Angle: 4°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 13/16CH</p>






OK-PL-58C	3-in-1 LED Effect Light LED BALL+SMD+LASER Moving Head		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds  LED SMD: 36pcs SMD 0.2W RGB 3IN1  Laser: Greed 50mw  Pan/Tilt movement: X-axis: 540°, Y-axis:270°  LEDBALL Angle: 2°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 19/24CH</p>
OK-PL-58D	2-in-1 LED Wash + beam moving head light		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED WASH: 3pcs*6W 4in1 RGBW leds  LED BEAM: 1pcs*10W 4in1 RGBW CREE leds  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  LEDWASH Angle: 25°  Beam Angle: 4°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 13/16CH</p>
OK-PL-58E	2-in-1 LED Effect Light LEDBALL+ Wash moving head light		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED BALL: 1pcs*10W 4in1 RGBW OSRMA leds  LED WASH: 4pcs*6W 4in1 RGBW leds  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  LEDBALL Angle: 2°  LEDWASH Angle: 25°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 13/16CH</p>
OK-PL-58F	Mini 7pcs LED Moving Head Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED WASH: 7pcs*6W 4in1 RGBW leds  Pan/Tilt movement: X-axis: 540°, Y-axis: 270°  LEDWASH Angle: 25°  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9CH</p>
OK-PL-94G	Two-head beam laser		<p>Voltage: AC110-240V, 50/60Hz  Power: 100W  LED:8pcs*10W RGBW 4IN1 CREE  laser:R:100MW G:50MW  Beam angle: 2°  Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave</p>
OK-PL-94H	Three-head beam laser		<p>Voltage: AC110-240V, 50/60Hz  Power: 150W  LED:12pcs*10W RGBW 4IN1 CREE  laser:R:100MW G:50MW B: 150MW  Beam angle: 2°  Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave</p>
OK-PL-94N	Four-head beam laser		<p>Voltage: AC110-240V, 50/60Hz  Power: 180W  LED:16pcs*10W RGBW 4IN1 CREE  laser:R:100MW G:50MW  Beam angle: 2°  Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt  Dimmer: 0-100% linear dimming  Strobe: Electric strobe,0.3-25 times second  Operation: Auto, DMX512,Sound, Master/Slave</p>

OK-PL-94M	3in1 beam laser Strobe		Voltage: AC110-240V, 50/60Hz Power: 180W LED:8pcs*10W RGBW 4IN1 CREE Strobe:4pcs*10W CW/Y laser:2PCS R:100MW ,2PCS G:50MW Beam angle: 2° Pan Tilt movement: X-axis: infinite tilt , Y-axis: infinite tilt Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave
OK-PL-87A	wash + beam moving head light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 4pcs*10W 4in1 RGBW+1pcs*10W 4in1 RGBW high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: infinite tilt Beam Angle: 6° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/17CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg
OK-PL-14A	18PCS*3W LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18pcs RGB high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Beam Angle: 25° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/13CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg
OK-PL-14	7pcs*10W LED Moving Head Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7pcs*10W 4IN1 RGBW high brightness leds LED: 7pcs*15W 5IN1 RGBWA high brightness leds Pan/Tilt movement: X-axis: 540°, Y-axis: 270° Beam Angle: 45° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/14CH Dimension:: 290*210*260mm N.W: 3kg G.W: 4kg
OK-PL-14	7pcs*15W LED Moving Head Light		

## Waterproof Par Light

Model	Name	Picture	Describe
OK-PL-69AW	200WCOB RGBW /W LED Par Aluminum		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 200W 4in1 COB RGB LED LED: 200W White COB LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH WATERPROOF:IP65 Dimension:250*250*350mm N.W: 6kg G.W: 7kg

OK-PL-69D	4*50W Waterproof PAR LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 4PCS* 50W Warm White Cool White(2pcsWW+2pcsCW) Color Temperature: 3000K-5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH Dimension:250*250*250mm
OK-PL-44	mini 7PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7PCS*8W RGBW 4IN1 LED: 7PCS*10W RGBWA/RGBWUV 5IN1 LED: 7PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:160*160*90mm N.W: 1.8kg G.W: 2kg
OK-PL-45	mini 9PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 9PCS*8W RGBW 4IN1 LED: 9PCS*10W RGBWA/RGBWUV 5IN1 LED: 9PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:160*160*90mm N.W: 1.8kg G.W: 2kg
OK-PL-46	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 18PCS*4W RGBW 4IN1 LED: 18PCS*5W RGBWA/RGBWUV 5IN1 LED: 18PCS*6W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension: 285x275x115mm N.W: 3.5kg G.W: 3.75kg
OK-PL-47	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 120W LED: 54PCS*1W RGBW LED: 54PCS*1.5W RGB3IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:220*220*90mm N.W: 2kg G.W: 2.5kg
OK-PL-51	mini 7PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 120W LED: 7PCS*12W RGBW 4IN1 LED: 7PCS*15W RGBWA/RGBWUV 5IN1 LED: 7PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:190*190*180mm N.W: 2kg G.W: 2.5kg








OK-PL-52	mini 9PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 9PCS*10W RGBW 4IN1 LED: 9PCS*15W RGBWA/RGBWUV 5IN1 LED: 9PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:190*190*180mm N.W: 2kg G.W: 2.5kg
OK-PL-53	mini 12PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 12PCS*10W RGBW 4IN1 LED: 12PCS*15W RGBWA/RGBWUV 5IN1 LED: 12PCS*18W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:190*190*180mm N.W: 2kg G.W: 2.5kg
OK-PL-2	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 54PCS*3W RGBW LED: 54PCS*3W RGB3in1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH waterproof level: IP65 Dimension:290*290*250mm N.W: 6kg G.W: 7kg
OK-PL-2			
OK-PL-55	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:290*290*250mm N.W: 6kg G.W: 7kg
OK-PL-55			
OK-PL-55			
OK-PL-15	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:290*290*250mm N.W: 6kg G.W: 7kg








OK-PL-21A	18PCS Waterproof connector LEDPar Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 200/280/350W  LED: 18PCS*8W RGBW  LED: 18PCS*10W RGBWA/RGBWUV  LED: 18PCS*12W RGBWAUV  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: RDM,Auto, DMX512,Sound, Master/Slave  Channel: 8/9/10CH</p>
OK-PL-20A	12PCS Waterproof connector LED Par Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 200/280/350W  LED: 12PCS*10W RGBW  LED: 12PCS*15W RGBWA/RGBWUV  LED: 12PCS*18W RGBWAUV  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: RDM,Auto, DMX512,Sound, Master/Slave  Channel: 8/9/10CH</p>
OK-PL-24	24PCS Waterproof LED Par Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 200/280/350W  LED: 24PCS*10W RGBW  LED: 24PCS*15W RGBWA/RGBWUV  LED: 24PCS*18W RGBWAUV  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 45°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 8/9/10CH  Dimension:260*260*300mm  N.W: 3kg G.W: 4kg</p>
OK-PL-54A	44PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 550W  LEDs: 44PCS 12W (RGBW 4in1)CREE LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>
OK-PL-54C	960PCS 2in1 Waterproof LED Strobe Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 600W  LED: 1080*5050 LED  Life: about 50,000 hours  Color: RGB  Flood angle: 135 °  Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable  Strobe: 0 to 25 times / second  Operation mode: DMX mode, master-slave mode, 12-segment Channel: 5/10/38CH  Projection distance: 4-30 meters  Ambient temperature: -25 °C ~ 40 °C</p>
OK-LP-90E	40PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 750W  LEDs: 60PCS 12W (RGBW 4in1)CREE LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>








OK-PL-18	80PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 450W  LEDs: 36PCS 12W (RGBW 4in1)CREE LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>
OK-LP-90E	60PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 750W  LEDs: 60PCS 12W (RGBW 4in1)CREE LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>
OK-PL-54	96PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 800W  LEDs: 96PCS *10W RGBW 4IN1 LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>
OK-OL-8	180PCS Waterproof LED WALL WASH Light		<p>Voltage: AC110-240V 50-60Hz  Power: 500W  LEDs: 180PCS 3W (RGB3in1)LEDs  Light life:50000 hours  Dimmer: 0-100%  Stroboscopic:1-20 time/sec  Beam Angle : 40° (optional)  digital  Control: Standard DMX512 signal, master-slave, auto-running.  DMX channel: 4/8CH  Cooling system: Natural convection heat transfer.  Body and color: Aluminum and black.</p>
OK-PL-25	18PCS Led Wall Washer (pixel controller)		<p>Voltage:AC110-240V 50-60Hz  Power consumption:200W  Light source:18PCS 8WRGBW 4in1 LEDs  Light source:18PCS 10WRGBWA 5in1 LEDs  Light source:18PCS 12WRGBWAUV 6in1 LEDs  Control SignalDMX 512,Master&amp;slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode  DMX controller mode:9/23/72CH  Each LED can be Controlled individually  LCD Display,4 buttons operate  Lens degree:40°/25°  Waterproof rate:IP65  Dimensions: 100*8.8*17cm 7.2kg</p>
OK-PL-16	MINI COB Waterproof LED Par Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 80W  LED: 1PCS*60W RGBWA 5in1  Beam Angle: 65°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 9CH  Dimension:190*190*250mm  N.W: 3kg G.W: 4kg</p>
OK-PL-17	MINI 7PCS Waterproof LED Par Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 80/100/120W  LED: 7PCS*10W RGBW  LED: 7PCS*15W RGBWA/RGBWUV  LED: 7PCS*18W RGBWAUV  Beam Angle: 45°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, Master/Slave  Channel: 8/9/10CH  Dimension:190*190*250mm  N.W: 3kg G.W: 4kg</p>



OK-PL-18	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/100/120W LED:54PCS*3W RGBW LED: 54PCS*3W RGB3IN1 LED: 54PCS*4W RGBW4IN1 Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-20	12PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 140/180/240W LED: 12PCS*10W RGBW LED: 12PCS*15W RGBWA/RGBWUV LED: 12PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-21	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-22	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-24	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:260*260*300mm N.W: 3kg G.W: 4kg
OK-PL-69-1	90WCOB LED Par Aluminum		Voltage: AC110-240V, 50/60Hz Power: 100W/150W/200W LED: 90W 3in1 COB RGB LED LED: 100W White COB LED LED: 200W 4in1 COB RGBW LED LED: 200W White COB LED Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-69-2	100WCOB WHITE LED Par Aluminum		
OK-PL-69-3	200WCOB RGBW LED Par Aluminum		
OK-PL-69-4	200WCOB WHITE LED Par Aluminum		
OK-PL-19	Strip-light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:: 250*250*360mm N.W: 4kg G.W: 4.5kg

OK-PL-6	LED Zoom PAR LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 19*12W 4 in 1 RGBW CREE led Beam Zoom: 10° - 60° Dimmer: 0-100% linear dimming Strobe: Electric strobe,0.3-25 times second Operation: Auto, DMX512,Sound, Master/Slave Channel: 10/18CH Size: 280x228x296mm N.W: 4.1kg G.W: 4.35kg
OK-PL-35E	24PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 24PCS*8WRGBW 4IN1 LED: 24PCS*10WRGBWA 5IN1 LED: 24PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm
OK-PL-35F	18PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 18PCS*8WRGBW 4IN1 LED: 18PCS*10WRGBWA 5IN1 LED: 18PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 220*220*100mm
OK-PL-35G	24PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 24PCS*8WRGBW 4IN1 LED: 24PCS*10WRGBWA 5IN1 LED: 24PCS*12W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 220*220*100mm
OK-PL-34	14PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 180W/200W LED: 18PCS*10WRGBW 4IN1 LED: 14PCS*15WRGBWA 5IN1 LED: 14PCS*18W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg
OK-PL-35	18PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/250W LED: 18PCS*10WRGBW 4IN1 LED: 18PCS*15WRGBWA 5IN1 LED: 18PCS*18W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 9/10CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg
OK-PL-36	54PCS Silent panel Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 180W LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension: 290*290*250mm N.W: 4kg G.W: 4.5kg



OK-PL-1	54PCS Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/200W LED: 54PCS*1W RGBW LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-2	54PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80/200W LED: 54PCS*1W RGBW LED: 54PCS*3W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH waterproof level: IP65 Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg
OK-PL-3	36PCS Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 50/150W LED: 36PCS*1W RGB LED: 36PCS*3W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7CH Dimension: 250*250*360mm N.W: 7kg G.W: 8.5kg
OK-PL-4	36PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 50/150W LED: 36PCS*1W RGB LED: 36PCS*3W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg
OK-PL-15	24PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg
OK-PL-43	18PCS Aluminum LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 250*250*360mm N.W: 4kg G.W: 4.5kg
OK-PL-55	18PCS Waterproof LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 18PCS*10W RGBW LED: 18PCS*15W RGBWA/RGBWUV LED: 18PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8/9/10CH Dimension: 290*290*350mm N.W: 7kg G.W: 8.5kg

<p><b>OK-PL-48</b></p>	<p><b>36*3in1 LED Par Light</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 120/180W LED: 36PCS*3IN1 RGB LED: 36PCS*4IN1 RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 7/8CH Dimension:: 250*250*360mm N.W: 4kg G.W: 4.5kg</p>
<p><b>OK-PL-40A</b></p>	<p><b>24PCS Aluminum LED Par Light</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200/280/350W LED: 24PCS*10W RGBW LED: 24PCS*15W RGBWA/RGBWUV LED: 24PCS*18W RGBWAUV Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH Dimension:: 250*250*360mm N.W: 4kg G.W: 4.5kg</p>
<p><b>OK-PL-69E</b></p>	<p><b>COB WHITE LED Par Aluminum</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 200W LED: 4PCS* 50W Warm White Cool White(WW/CW) LED: 4PCS* 60W RGBW 4IN1 Color Temperature: 3000K/ 5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH</p>
<p><b>OK-PL-69A ZOOM</b></p>	<p><b>LED COB ZOOM PAR LIGHT</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 110W LED: 1 x 100W WW/CW LED module Color Temperature: 3000K/ 5700K ZOOM : 9°/15°/20°/25°/30° Luminous Flux: 4973lm CRI: ≥96 DMX channel: 1/2/3 channels Control Mode: DMX512,Manual Display: LED display Data In/Out: 3-pin or 5-pin XLR Power In/Out: Power cord out Dimensions: 418x281x452mm Weight: 4.5kg</p>
<p><b>OK-SL-100 ZOOM</b></p>	<p><b>LED COB ZOOM PAR LIGHT</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1 x 200W COBWW/CW LED module Color Temperature: 3000K/ 5700K Zoom: 15°-52° CRI: ≥96 DMX Channel: 3CHs Control mode: Master/Slave; DMX512 control, Sound control and Stand-alone. Dimension: 278x455x292mm N.W: 10.1KG</p>
<p><b>OK-SL-106</b></p>	<p><b>630 COB PAR Video LIGHT</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 250W LED: 6PCS*30W RGBWA5 IN 1 COB LED: 6PCS*30W RGBWA UV 6 IN 1 COB  Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM control ,Auto, DMX512,Sound, Master/Slave Channel: 9/10CH size: 20x20x20 (barn doors fold)</p>
<p><b>OK-SL-107</b></p>	<p><b>1810 PAR Video LIGHT</b></p>		<p>Voltage: AC110-240V, 50/60Hz Power: 350W LED: 18PCS*15W RGBWA5 IN 1 LED: 18PCS*18W RGBWA UV 6 IN 1  Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM control. Auto, DMX512,Sound, Master/Slave Channel: 9/10CH size: 20x20x20 (barn doors fold)</p>

OK-SL-108	450 PAR Video LIGHT		Voltage: AC110-240V, 50/60Hz Power: 280W LED: 4PCS* 50W Warm White Cool White(WW/CW) LED: 4PCS* 60W RGBW 4IN1 Color Temperature: 3000K/ 5600K CRI: ≥90 Beam Angle: 36° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH Size: 20x20x20 (beam doors fold)
OK-SL-109	200 PAR Video LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K/ 5600K CRI: ≥96 Beam Angle: 60° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: RDM controlAuto, DMX512,Sound, Master/Slave Channel: 2CH
OK-SL-110	200 Zoom PAR Video LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K/ 5600K Zoom: 10°-55° CRI: ≥96 Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 3CH Size: 20x20x20mm
OK-SL-111	4812 PAR Video LIGHT		Voltage: AC110-240V, 50/60Hz Power: 550W LED: 48PCS* 8W RGBW 4IN1 LED: 48PCS* 10W RGBWA 5IN1 LED: 48PCS* 12W RGBWA UV 6IN1 Beam Angle: 35° Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 8/9/10CH
OK-SL-110A	200W Zoom PAR LIGHT		Voltage: AC110-240V, 50/60Hz Power: 250W LED: 1PCS* 200W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color Temperature: 3000K-5600K Zoom: 8°-55° CRI: ≥95 Dimmer: 0-100% linear dimming, 4 dimming curves, temperature:temperature display Operation: Auto, DMX512,Sound, Master/Slave Channel: 3CH
OK-SL-103S	MINI 2 Eyes LED Audience Ligh		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 2pcs*50W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 6CH
OK-SL-104S	MINI 4 Eyes LED Audience Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 4pcs *50W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH

OK-SL-103	2 Eyes LED Audience Ligh		Voltage: AC110-240V, 50/60Hz Power: 200W LED: 2pcs * 100W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 2/6CH Dimension:: 440*210*210mm
OK-SL-104	4 Eyes LED Audience Light		Voltage: AC110-240V, 50/60Hz Power: 400W LED: 4pcs * 100W Warm White Cool White(WW/CW) 2in1 COB(Chip on board) LED Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 6/12CH Dimension:: 400*400*300mm
OK-SL-101	LED Video Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: White 200W COB LED 3200K (6500K available) Lamp luminous flux(lm) :95 Lamp luminous efficiency(lm/w) :8400 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 19°/36°are available) Dimmer: 0-100% linear dimming Operation: Auto, DMX512,, Master/Slave Channel: 2CH
OK-SL-102	LED Video Light		Voltage: AC110-240V, 50/60Hz Power: 200W LED: SMD LED 3200K (6500K available) Lamp luminous flux(lm) :95 Lamp luminous efficiency(lm/w) :8400 Dimmer: 0-100% linear dimming Operation: Auto, DMX512,, Master/Slave Channel: 2CH Dimension:: 640*280*220mm N.W: 7kg G.W: 7.5kg
OK-PL-103B	Truss LED QUAD Lighting		Voltage: AC110-240V, 50/60Hz Power: 20W LED: 3PCS*4W RGBW 4 IN 1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 35° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 8CH Dimension:: 150*140*140mm N.W: 1.5kg G.W: 2kg

## LED Plastic Par Light

Model	Name	Picture	Describe
OK-PL-60R	60LED RGB 3in1 par light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 60PCS*1.5W RGB 3in1 Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7CH Dimension: 240x240x75mm N.W: 0.8kg G.W: 1.05kg
OK-PL-9RN	9x4W LED Par light		Voltage: AC110-240V, 50/60Hz Power: 36W LED: 9PCS*4W RGBA 4in1 mixed color Beam Angle: 25° Current: constant current Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 8CH Dimension:: 185*185*85mm N.W: 0.7kg G.W: 1kg






OK-PL-61A	7PCS 4IN1 LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 7PCS*8W RGBW 4IN1 LED: 7PCS*8W RGBWA/RGBWUV 5IN1 LED: 7PCS*8W RGBWAUV 6IN1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9CH Dimension: 190*190*150mm N.W: 1kg G.W: 1.5kg
	7PCS 5IN1 LED Par Light		
	7PCS 6IN1 LED Par Light		
OK-PL-61C	4in1 COB Par light		Voltage: AC110-240V, 50/60Hz Power: 50W LED: 50W COB RGBWA 5IN1  Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension: 190*190*150mm N.W: 1.2kg G.W: 1.5kg
OK-PL-101	6PCS LED COB PAR		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 6PCS*30W RGB 3 IN 1 COB LED: 6PCS*30W RGBW 4 IN 1 COB Beam Angle: 60° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 7/8CH Dimension:: 215*210*100mm N.W: 1.5kg G.W: 2kg
OK-PL-71	9PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED: 9PCS*6W RGBW 4 IN 1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-71A	18PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 18PCS*6W RGBW 4 IN 1 LED: 18PCS*6W RGBWA 5 IN 1 LED: 18PCS*6W RGBWAUV 6 IN 1 Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-100-II	54PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 54PCS*1W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 8CH Dimension:: 215*210*100mm N.W: 1kg G.W: 1.5kg
OK-PL-62	18PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 20W LED: 18PCS*1W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg

<b>OK-PL-62A</b>	<b>24PCS LED Par Light</b>		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 24PCS*1W RGBW Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 8CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
<b>OK-PL-62B</b>	<b>36PCS LED Par Light</b>		Voltage: AC110-240V, 50/60Hz Power: 40W LED: 36PCS*1W RGB Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Remote control Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
<b>OK-PL7R4</b>	<b>7x4W LED Par light</b>		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 7PCS*4W RGBW 4in1 LED Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Master/ Slave, Static Color, Hopping, Color Fade, Pulse, Auto Channel: 5/8CH Dimension:: 175*175*100mm N.W: 0.9kg G.W: 1.1kg
<b>OK-PL6R4</b>	6x4W LED Par Light		Voltage: AC110-240V, 50/60Hz Power: 24W LED: 6PCS*4W RGBW 4in1 LED Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Master/ Slave, Static Color, Hopping, Color Fade, Pulse, Auto Channel: 8CH Dimension:: 130*130*130mm N.W: 0.9kg G.W: 1.0kg


### Battery powered stage light










Model	Name	Picture	Describe
<b>OK-3RB</b>	3x4W RGBW 4in1 LED battery par		Voltage: AC110-240V, 50/60Hz, Power: 20-Watt Battery: 11.6V/ 4400MA Angle:35° LED Source:3x4-Watt 4IN1 RGBW LED Battery Life: 6-26 hours Charging time: 4-5 hours DMX Channel: 4/6/8 CH Size: 19.5x15x14.5cm / 7.7x5.9x5.7in Weight: 1.2KG /2.6LB
<b>OK-BAT-12</b>	Battery + wireless DMX Waterproof connector 9PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 14000MA Power: 120W LED: 9PCS*8W RGBW 4 IN 1 LED: 9PCS*10W RGBWA 5 IN 1 LED: 9PCS*12W RGBWAUV 6 IN 1 Working time: 6-8 hours Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: RDM With Built- in fast 2.4G wireless DMX signal receiver] / IR Control, master/slave, auto,



OK-BAT-12A	Battery + wireless DMX Waterproof connector 12PCS LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 14000MA Power: 150W LED: 12PCS*8W RGBW 4 IN 1 LED: 12PCS*10W RGBWA 5 IN 1 LED: 12PCS*12W RGBWAUV 6 IN 1 Working time: 4-7 hours Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: • RDM With Built- in fast 2.4G wireless DMX signal receiver] / IR Control, master/slave, auto,
OK-BAT-12AW	APP control + wireless DMX outdoor battery powered par light		Input voltage: AC100V-240V 50-60HZ Power: 200W Light Source: 12 *18W RGBWA UV 6in1 LED IP rating: IP65 DMX channels: 6/8/10CH Life span: 50,000 hours Lens angle: 40° (15° and 25° are also customizable) Control: DMX512, master-slave, auto mode, 2.4G wireless DMX512, Infrared remote control, APP control Battery: 9600mAh capacity Charging time: full charge in 6 hours Play time: RGBWAUV all on for 6 hours and single color for 15 hours. auto mode 5 hours Net weight: 4.5KG Gross Weight: 5.2KG
OK-BAT-5	18PCS Battery LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 4400MA Power: 20W LED: 18PCS*1W RGB Working time: 3-6 hours  Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 7CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-BAT-6	24PCS Battery LED Par Light		Voltage: AC110-240V, 50/60Hz Lithium battery: 11.6V 5500MA Power: 30W LED: 24PCS*1W RGBW Working time: 3-6 hours  Beam Angle: 25° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 8CH Dimension:: 190*190*130mm N.W: 0.6kg G.W: 1kg
OK-PL-31BAT	Battery LED PARTY BAR Derby Light		Battery:12V 5800ma LED:2*3PCS * RGB 3IN1 High brightness leds LED STROBE: 2*18PCS 5730 WHITE LEDDerby :2*4*3W (RGBW) LED. Working time: 4 hours Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg

## LED Lighting Package

Model	Name	Picture	Describe
OK-PL-31P	LED Par Can Set		Voltage: AC110-240V, 50/60Hz Power: 60W LED PAR:2*3PCS *4W RGBW leds LED BALL:2*4*3W (RGBW) LED. LED UV STROBE: 6*4W UV+W LEDS Laser power: 30mW 532nm green diode 100mW 650nm red diode Operation: Auto, DMX512,Sound,Remote control Channel: 3/6/15CH Dimension:: 900*340*160mm N.W: 5kg G.W: 6kg

OK-PL-310	LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED PAR:2*3PCS *4W RGBW leds  LED Derby :2*4*3W (RGBW) LED.  Laser power: 30mW 532nm green diode  100mW 650nm red diode  Operation: Auto, DMX512,Sound,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31Q	LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED: 96PCS/1W R.G.B.W(R*24.G*24.B*24 W*24)  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound,Remote control  Channel: 8CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31A-RGBW	48PCS LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED: 48PCS/1W R.G.B.W(R*12.G*12.B*12.W*12)  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, ,Remote control  Channel: 8CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31A- RGB	48PCS LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 150W  LED: 48PCS/3W R.G.B.W(R*48.G*48.B*48.W*48)  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound, ,Remote control  Channel: 7CH  Dimension: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31H	12PCS*4IN1 LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED: 12PCS/4W 4IN1RGBW  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound,Remote control  Channel: 8CH  Separate control Channel: 5/8/16/20  Dimension:: 900*340*160mm</p>
OK-PL-31K	4PCS*COB LED Par Can Set		<p>Voltage: AC110-240V, 50/60Hz  Power: 150W  LED: 4PCS/30W 3IN1 COB RGB  Beam Angle: 60°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound,Remote control  Channel: 7CH  Separate control Channel: 4/7/12/16  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31B	LED PARTY BAR Kaleido Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W)  LED: 2*1*10W 4 IN 1 (RGBW)CREE LED.  Operation: Auto, DMX512,Sound,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31B-1	6x4W LED par+moonflower		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED:6PCS *4W RGB UV High brightness leds  LED: 2*10W 4 IN 1 (RGBW) LED.  Operation: Auto, DMX512,Sound,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
OK-PL-31C	LED PARTY BAR Derby Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W)  LED:2*4*3W (RGBW) LED.  Operation: Auto, DMX512,Sound,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>




<b>OK-PL-31D</b>	<b>LED PARTY BAR BEAM Light</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W)  LED:2*60*5MM LEDs( red , green ,blue , white ,amber )  Operation: Auto, DMX512,Sound,,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
<b>OK-PL-31F</b>	<b>LED PARTY BAR Ball Light</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED:2*12PCS *1W RGBW High brightness leds (3R,3G,3B,3W)  LED:2*4*3W (RGBW) LED.  Operation: Auto, DMX512,Sound,Remote control  Channel: 3/6/15CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
<b>OK-PL-31G</b>	<b>LED Magic Ball Par Can Set</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED: 36PCS/1W R.G.B.W(R*12.G*12.B*12)  LED:4*3*1W (R*4G*4B*4) LED.  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound,Remote control  Channel: 8CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>
<b>OK-PL-31S</b>	<b>LED Magic Ball Par Can Set</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 100W  LED: 72PCS/1W R.G.B.W(R*24.G*24.B*24)  LED:8*3*1W (R*8G*8B*8) LED.  Beam Angle: 25°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512,Sound,Remote control  Channel: 8CH  Dimension:: 900*340*160mm  N.W: 5kg G.W: 6kg</p>

## LED Black Light

<b>Model</b>	<b>Name</b>	<b>Picture</b>	<b>Describe</b>
<b>OK-9BL</b>	<b>LED UV LIGHT</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 30W  LED: 9PCS*3W UV LED  Angle: 120°  wavelength: 390-410nm  Dimension:: 500*70*70mm  N.W: 0.8kg G.W: 1kg</p>
<b>OK-005-36W</b>	<b>LED UV LIGHT</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 36W  LED: 36PCS*1W UV LED  Angle: 120°  wavelength: 390-410nm  Dimension:: 410*46*48mm  N.W: 0.3kg G.W: 0.4kg</p>
<b>OK-097-18BL</b>	<b>LED UV LIGHT</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 18W  LED: 18PCS*1W UV LED  Angle: 120°  wavelength: 390-410nm  Dimension:: 410*125*90mm  N.W: 1kg G.W: 1.2kg</p>
<b>OK-12BL</b>	<b>LED UV LIGHT</b>		<p>Voltage: AC110-240V, 50/60Hz  Power: 40W  LED: 12PCS*3W UV LED  Angle: 120°  wavelength: 390-410nm  Dimension:: 650*70*70mm  N.W: 1kg G.W: 1.2kg</p>

<b>OK-18BL</b>	<b>LED UV LIGHT</b>		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 105*70*70mm N.W: 1.3kg G.W: 1.5kg
<b>OK-18BL-N</b>	<b>Power Linkable LED UV LIGHT</b>		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimension:: 900*105*80mm N.W: 1.5kg G.W: 1.8kg
<b>OK-18BL-A</b>	<b>LED UV LIGHT</b>		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 18PCS*3W UV LED Angle: 120° wavelength: 390-410nm Dimmer: 0-100% linear dimming Operation: Auto,DMX512,Sound,Master/Slave Channel: 7CH Dimension:: 380*170*170mm N.W: 1.8kg G.W: 2kg
<b>OK-9BL-WP</b>	<b>9x3W IP65 LED UV LIGHT Bar</b>		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9PCS*3W UV LED Angle: 120° IP rating: IP65 wavelength: 390-410nm Dimension:: 493*55*50mm N.W: 0.7kg G.W: 0.9kg








## LED Wash Bar

<b>Model</b>	<b>Name</b>	<b>Picture</b>	<b>Describe</b>
<b>OK-24WL</b>	<b>24 x 3W RGB LED wall washer</b>		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 24PCS*3W RGB3IN1 Beam Angle: 40° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 3/6/24/28CH Dimension:: 1020*105*80mm N.W: 2.5kg G.W: 2.8kg
<b>OK-24WL-1</b>	<b>24x4W RGBA led wall washer</b>		Voltage: AC110-240V, 50/60Hz Power: 96W LED: 24PCS*4W RGBA 4IN1 Beam Angle: 40° Dimmer: 0-100% linear dimming Operation: Auto, DMX512,Sound, Master/Slave Channel: 3/6/12/24/48CH Dimension:: 1020*105*80mm N.W: 2.5kg G.W: 2.8kg
<b>OK-096-18WL</b>	<b>18x3W RGB 3in1 led wall washer</b>		Voltage: AC110-240V, 50/60Hz Power: 60W Light Source: 18x3W RGB 3in1 LED Control Mode: Auto run, sound activated, DMX-512 Mode, and master slave mode DMX channels: 3/7/13 DMX Connection: 3-Pin XLR In/Out Beam Angle: 40° Display: LED Display Dimming: Electronic 0-100% Dimension: 102x6.5x6.5cm N.W.: 2.5kg

OK-PL-32M	Led Wall Bar		<p>Voltage: AC110-240V, 50/60Hz  Power: 50W  LED: 9PCS* 4W RGBW 4IN1  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 35°  Dimmer: 0-100% linear dimming,  Operation: Auto, DMX512, Sound, Master/Slave  Channel: 8CH</p>
OK-PL-32Y	720pcs Led pixelcontroller RGB+W Wall Strobe Bar		<p>Voltage: AC110-240V, 50/60Hz  Consumption: 200W  LED RGB: 480*5050 LED RGB3IN1,  LED White: 240*5730LED White,  Operation: Operation: Auto, DMX512, Sound, Master/Slave  Channel: 4/16/168CHs,  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 135°  Dimmer: 0-100% linear dimming  DMX in/out, Power in &amp; Power out.</p>
OK-PL-28	Led 1080PCS pixelcontroller Wall Strobe Bar		<p>Voltage: AC110-240V, 50/60Hz  Power: 800W  LED RGB: 1080*5050 LED 48-segment  Life: about 50,000 hours  Color: RGB  Flood angle: 135 °  Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable  Strobe: 0 to 25 times / second  Operation mode: DMX mode, master-slave mode,  Channel: 4/5/6/10/84CH  Projection distance: 4-30 meters  Ambient temperature: -25 °C ~ 40 °C</p>
OK-PL-28A	2in1 W+RGB Led 1092PCS pixelcontroller Wall Strobe Bar		<p>Voltage: AC110-240V, 50/60Hz  Power: 800W  LED RGB: 672*5050 LED 24-segment  LED White: 420*5730 LED 12-segment  Life: about 50,000 hours  Color: RGB+W  Flood angle: 135 °  Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable  Strobe: 0 to 25 times / second  Operation mode: DMX mode, master-slave mode,  Channel: 4/5/6/10/84CH  Projection distance: 4-30 meters</p>
OK-PL-32CW	24 x 4 W TRI LED Bar		<p>Voltage: AC110-240V, 50/60Hz  Power: 100W  LED: 24PCS*4W RGBW 4IN1  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 35°  Dimmer: 0-100% linear dimming  Operation: Auto, DMX512, Sound, Master/Slave  Channel: 4/8/28/36CH  Dimension: 1050*105*80mm  N.W: 4kg G.W: 4.5kg</p>
OK-PL-32C BAT	BAT 24 x 3 W TRI LED Bar		<p>Voltage: AC110-240V, 50/60Hz  Power: 80/100W  LED: 24PCS*3W RGB3IN1  LED: 24PCS*4W RGBW 4IN1  BAT: 11.6V 10000MA  Color: RGB color can be mixed to more than 16.7 million kinds of color.  Beam Angle: 35°</p>




OK-PL-32C BAT	BAT 24 x 4 W TRI LED Bar		 <p>Beam Angle: 33° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 3/6/24/28CH Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg</p>
OK-PL-32D	18pcs LED Wall Light		<p>Voltage: AC110-240V, 50/60Hz Power: 180W LED: 18PCS*8W RGBW 4NI LED: 18PCS*10W RGBWA 5NI LED: 18PCS*12W RGBWA UV 6NI Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9/27/72/82CH Dimension: 1130*150*210mm N.W: 8kg G.W: 8.5kg</p>
OK-095-24APPWL	72W LED APP Control Outdoor LED Wall Washer Light		<p>Power: 72W Voltage: AC110-240V, 50/60Hz Light Source: 24pcs RGB 3in1 5050LED, 24pcs warm white LED, 24pcs cold white LED Control: app control APP: Fi Light IP rating: IP65 Dimming: Electronic 0-100% Dimension: 80x6x5cm N.W.: 1.5kg</p>
OK-003-APPWL4	4-pack, APP control LED RGB wash light bar		<p>Input: AC100V-240V, 50Hz-60Hz Output: DC5V/4A Power: 12W Light Source: 96pcs 5050 RGB LED Beam Angle: 25° Control Mode: App or Remote (included) APP: LED LAMP Run mode: Auto run, static color, sound active mode Housing material: Aluminum alloy Dimension: 410x28x32cm x4 N.W.: 1.5kg</p>
OK-007-60APP	60pcs led RGB app control light bar		<p>Input: AC100V-240V, 50Hz-60Hz Output: DC5V/4A Power: 12W Light Source: 60pcs 5050 RGB LED Beam Angle: 25° Control Mode: App or Remote (included) APP: LED LAMP Run mode: Auto run, static color, sound active mode Housing material: Aluminum alloy Dimension: 100x2.8x3.2cm N.W.: 1.0kg</p>
OK-PL-25A	24pcs waterproof LED wash light		<p>Voltage: AC110-240V, 50/60Hz Power: 150W LED: 24PCS*6W RGBW 4IN1 LED: 24PCS*6W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° IP rating: IP65 Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg</p>

OK-PL-25	18PCS Led Wall Washer (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:200W Light source:18PCSx8 RGBW 4in1 LEDs Light source:18PCSx10 RGBWA 5in1 LEDs Light source:18PCSx12 RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/72CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Waterproof rate:IP65 Dimensions: 100*8.8*17cm 7.2kg Packing Size: 105*15*21cm 7.6kg 1pcs
OK-PL-26	14PCS Led Wall Washer (pixel controller)		Voltage:AC110-240V 50-60Hz Power consumption:200W Light source:14PCSx8 RGBW 4in1 LEDs Light source:14PCSx10 RGBWA 5in1 LEDs Light source:14PCSx12 RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/72CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Waterproof rate:IP65 Dimensions: 100*8.8*17cm 7.2kg Packing Size: 105*15*21cm 7.6kg 1pcs
OK-PL-32D	18pcs LED Wall Washer Light		Voltage: AC110-240V, 50/60Hz Power: 180W LED: 18PCS*10W RGBW 4NI LED: 18PCS*15W RGBWA 5NI Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 9/27/72/82CH Dimension:: 1130*150*210mm N.W: 8kg G.W: 8.5kg
OK-PL-32 E	24 PCS 5in1 Led Wall bar		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:24PCS RGBWA/RGBWUV 5in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:7/10/19/37/69CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32 F	24 PCS 6in1 Led Wall bar		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:24PCS RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:8/11/20/38/74CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32G	18PCS 5in1 Led Wall bar (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:18PCS RGBWA 5in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:9/23/94CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm
OK-PL-32H	18PCS 6in1 Led Wall bar (pixelcontroller)		Voltage:AC110-240V 50-60Hz Power consumption:150W Light source:18PCS RGBWAUV 6in1 LEDs Control SignalDMX 512,Master&slaver ,Auto Operate ModeAuto-run mode,MasterSlave mode DMX controller mode:10/23/112CH Each LED can be Controlled individually LCD Display,4 buttons operate Lens degree:40°/25° Dimensions: 100*8.8*17cm








OK-PL-25A	24pcs waterproof LED wash light IP65		Voltage: AC110-240V, 50/60Hz Power: 150W LED: 24PCS*6W RGBW 4IN1 LED: 24PCS*6W RGBWAUV 6IN1 Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 45° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 4/8/28/36CH Dimension: 1050*105*80mm N.W: 4kg G.W: 4.5kg
OK-WL-W0721-IP65	72*3W RGBW LED Wall Washer IP65		Light source: 3W x 72pcs Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:25° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm Weight:7 kg
OK-WL-W0184-IP65	18*10W RGBW 4IN1 Wall Washer IP65, Pixel control		Light source: 10W RGBW 4IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm
OK-WL-W0184-IP65-1	18*10W RGBW 4IN1 Wall Washer IP65, Non-Pixel control		
OK-WL-W0185-IP65	18*12W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA 5IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 5CH /9CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm
OK-WL-W0185-IP65-1	18*12W RGBWA 5IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0186-IP65	18*12W RGBWAUV 6IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWAUV 6IN1 x 18pcs/Pixel Control Voltage: 100V~240V, 50/60Hz Power consumption: 240W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 6CH /10CH Electronic dimming: 0-100% Dimension: 1000 x 85 x150 mm
OK-WL-W0186-IP65-1	18*12W RGBWAUV 6IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0094-IP65	9*12W RGBW 4IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBW 4IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption: 160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 4CH /8CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm
OK-WL-W0094-IP65-1	9*12W RGBW 4IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0095-IP65	9*12W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA 5IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption: 160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out



OK-WL-W0095-IP65-1	9*12W RGBWA 5IN1 Wall Washer IP65, Non-Pixel Control		XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 5CH /9CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm Weight: 3.1kg
OK-WL-W0096-IP65	9*12W RGBWA+UV 6IN1 Wall Washer IP65, Pixel Control		Light source: 12W RGBWA UV 6IN1 x 9pcs Voltage: 100V~240V, 50/60Hz Power consumption: 160W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:40° Display: LED display DMX Channels: 6CH /10CH Electronic dimming: 0-100% Dimension: 520 x 85 x150 mm Weight: 4.3 kg
OK-WL-W0096-IP65-1	9*12W RGBWA+UV 6IN1 Wall Washer IP65, Non-Pixel Control		
OK-WL-W0145-IP65	14*30W RGBWA 5IN1 Wall Washer IP65, Pixel Control		Light source: 30W RGBWA 5IN1 x 14pcs Voltage: 100V~240V, 50/60Hz Power consumption: 320W Control mode: Sound active, Auto, DMX and Master/slave Power sockets: in/out XLR sockets:3-pin XLR IN/OUT Beam angle:45° Display: LED display DMX Channels: 24/10/80/70CH Electronic dimming: 0-100% Dimension: 1000 x 150x170 mm Weight:8.7 kg

LED Effect Light			
Model	Name	Picture	Describe
OK- E100	12PCSCW+ SMD RGB+STROBE TRI LED BAR		Voltage: AC110-240V, 50/60Hz Power: 100W Light Source: 12x5W 6° LED warm white+84x0.5W 5370 LED White+ 106x0.2W 5050 LED RGB Tri-color Control Mode: Auto run, color changing, sound active, DMX-512 Mode, and master slave mode DMX Connection: 3-Pin XLR In/Out DMX Channel: 5/14/75CH Display: LED Display Dimming: Electronic 0-100% Dimension: 110x8x15cm N.W.: 3.5kg
OK-105-36WL	36LED RGBW 4in1 beam light		Voltage: AC110-240V, 50/60Hz Consumption: 150W LED Wash: 36*4W CREE RGBW 4IN1 Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:4/6/9/48CHs, Color: RGB color can be mixed to more than 16.7 million kinds of color. Angle: Beam 1.5° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*9cm NW: 2.25KG /GW:2.65KG
OK-063-12WL	12pcs LED RGB 3in1 wash light & 12pcs LED warm white beam light		Voltage: AC110-240V, 50/60Hz Consumption: 80W LED Wash: 12*3W LED RGB3IN1, LED Beam: 12*3W CREE CW Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:4/6/10/11/48CHs, Color: RGB color can be mixed to more than 16.7 million kinds of color. Angle: Beam 3°+Wash 35° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*7cm

OK-23-144LED	144pcs RGB 3in1 LED pixel light bar		Voltage: AC110-240V, 50/60Hz Consumption: 60W LEDs: 144Pcs (12*12Pcs) SMD 5050 3IN1 RGB LEDs Operation:Operation:Auto,DMX512,Sound,Master/Slave Channel:3/5/8/36/40CHs, Beam Angle: 90° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*5.5*9cm NW: 1.75KG /GW:2.15KG
OK-062-224WL	224pcs RGB 3in1 pixel light bar		Voltage:AC110-240V,50/60HZ Power:60W LED:224PCS SMD 5050 3IN1 RGB Operation:Operation:Auto,DMX512,Sound,Master/Slave DMX Channel:3/5/8/24/48/53 CH Beam Angle: 120° Dimmer: 0-100% linear dimming DMX in/out,Power in & Power out. Dimension: 100*6.5*8.5cm NW: 1.5KG /GW:1.85KG
OK-103-288WL	288pcs RGBW led light bar		Voltage: AC110-240V, 50/60Hz Power: 100W Light Source: 192x0.2W RGB 5050LED, 96x0.5W 5730 white LED DMX channels: 6/9/12/32/64 DMX Connection: 3-Pin XLR In/Out Display: LED Display Dimension: 110x10.2x10.2cm N.W.: 2.5kg
OK-006-384SL	384pcs RGBW led strobe light		Voltage: AC110-240V, 50/60Hz Power: 120W Light Source: 256pcs 5050 RGB LED, 128pcs 5730 white LED Control Mode: Auto run, sound active, DMX-512 Mode, and master slave mode DMX Connection: 3-Pin XLR In/Out DMX Channel: 6/9/64/112CH Dimension: 38x23x12cm N.W.: 2.5kg
OK-PL-54C	Waterproof 2in1 W+RGB STROBE Light		Voltage: AC110-240V, 50/60Hz Waterproof :IP65 Power: 500W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5757LED White, Life: about 50,000 hours Flood angle: 135 ° Channel: 4/16/48CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second
OK-PL-54E	2in1 W+RGB STROBE Moving Head Light		Voltage:AC110-240V,50/60HZ Waterproof :IP65 Power:600W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5757LED White, LED Beam Flood angle: 135 ° Pan movement: Y-axis:270° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode,
OK-PL-1024	Led 1024PCS Strobe		Voltage: AC110-240V, 50/60Hz Power: 400W LED RGBW: 1024*5050 LED RGBW4IN1 Life: about 50,000 hours Color: RGBW4in1 Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/6/9/16/32CH

OK-PL-4326	36 PCS Diamond Beam+Strobe		Voltage: AC110-240V, 50/60Hz Power: 400W LED RGB: 432pcs SMD 5050 RGB3IN1 LED LED Beam: 36pcs 3W CW CREE LED Life: about 50,000 hours Flood angle: 135 ° Beam angle: 2 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode,
OK-VS-67B	2in1 W+RGB STROBE Light		Voltage: AC110-240V, 50/60Hz Power: 500W LED RGB: 864*5050 LED RGB3IN1, LED White: 96*5730LED White, Life: about 50,000 hours Flood angle: 135 ° Channel: 4/11/32/39CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode,
OK-VS-67	8-segment 960pcs 12-segment 1080pcs STROBE Light		Voltage: AC110-240V, 50/60Hz Power: 500W LED: 960/1080*5050 LED Life: about 50,000 hours Color: RGB Flood angle: 135 ° 4-segment Channel: 5/26CH 12-segment Channel: 5/10/38CH Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, 4-segment Channel: 14/16CH 12-segment Channel: 5/10/38CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C
OK-PL-28	Led 1080PCS pixelcontroller Wall Strobe Bar		Voltage: AC110-240V, 50/60Hz Power: 800W LED RGB: 1080*5050 LED 48-segment Life: about 50,000 hours Color: RGB Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/5/6/10/84CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling
OK-PL-28A	2in1 W+RGB Led 1092PCS pixelcontroller Wall Strobe Bar		Voltage: AC110-240V, 50/60Hz Power: 800W LED RGB: 672*5050 LED 24-segment LED White:420*5730 LED 12-segment Life: about 50,000 hours Color: RGB+W Flood angle: 135 ° Dimming: linear dimming 0 ~ 100% smooth dimming and various strobe effects, speed adjustable Strobe: 0 to 25 times / second Operation mode: DMX mode, master-slave mode, Channel: 4/5/6/10/84CH Projection distance: 4-30 meters Ambient temperature: -25 °C ~ 40 °C Cool: forced air cooling
OK-PL-32A	14x3W pixel control LED+SMD light bar		Voltage: AC110-240V, 50/60Hz Power: 80W LED: 14PCS*3W CREE CW White(2600K) 56PCS*5050 SMD RGB Beam Angle: 4° Dimmer: 0-100% linear dimming Operation: Auto, DMX512, Sound, Master/Slave Channel: 6/9/51CH Dimension:: 1050*105*80mm N.W: 4kg G.W: 4.5kg
OK-VS-38	LED STROBE Light		Voltage: AC110-240V, 50/60HZ Power: 80W LED: 168pcs 5730 SMD WHITE LED LED : 72PCS 5050 SMD RGB LED Operation: Auto, DMX512, Sound, Channel: 5/14CH

OK-PL-5SW	mini Strobe white		Voltage: AC110-240V, 50/60Hz Power: 9W LED: 54PCS*0.2W 2835 SMD WHITE Color: RGB color can be mixed to more than 16.7 million kinds of color. Beam Angle: 135° Dimmer: 0-100% linear dimming Operation: Auto,Sound,Remote control
OK-PL-5SR	mini Strobe RGB		Voltage: AC110-240V, 50/60Hz Power: 10W LED: 78PCS*0.2W SMD2835 white 16.7 million kinds of color. Beam Angle: 135° Dimmer: 0-100% linear dimming Operation: Auto,Sound,Remote control
OK-008-72SL	72pcs RGB 3in1 5050LED light bar		Voltage: AC100-240V, 50/60Hz Power: 18W Light Source: 72pcs RGB 3in1 5050LED Control Mode: Auto run, sound active, DMX, remote control DMX channels: 8/24 DMX Connection: 3-Pin XLR In/Out Beam Angle: 120° Housing: aluminum alloy Dimension: 39x6.2x 5.8cm N.W.: 0.9kg
OK-VS-15	Gobo Effect, Ball Effect, Strobe/Chase and green & red laser effect		Voltage: AC110-240V, 50/60Hz Power: 50W LED Strobe:1PCS *20W White LED BALL Effect: 3PCS*3W LED RGB LED Gobo Effect: 6PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 15° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 12CH Dimension:: 450*300*210mm N.W: 4kg G.W: 4.5kg
OK-VS-6	Derby effect Strobe and Laser Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED Strobe:6PCS *3W White LED Derby Effect1: 4PCS*3W LED RGBW LED Derby Effect2: 4PCS*3W LED RGBW Laser Effect: Red 120mw& Green 30mw Operation: Auto,Sound Standalone modes: auto programs, sound programs
OK-VS-37	LED Waterwave Effect Light		Voltage:AC110-240V,50/60HZ Power:80W LED:6x12W CREE RGBW LED Beam Angle:4-35° Operation:Auto,DMX512,Sound, Channel:10CH
OK-VS-80	Derby Matrix Beam Light		Voltage: AC110-240V, 50/60Hz Power: 100W LED:24pcs * 3W RGBW LEDs Beam Angle: 8° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 4/26CH Dimension:: 320*290*290mm N.W: 4kg G.W: 4.5kg
OK-VS-81	Derby and Strobe Effect Light		Voltage: AC110-240V, 50/60Hz Power: 100W Derby LED : 20pcs *3W RGBA Strobe: 12PCS*1W white LEDs Beam Angle: 8° Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 4/28CH Dimension:: 320*350*290mm N.W: 4kg G.W: 4.5kg

OK-VS-82	Derby Matrix Beam Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 90W  LED:24pcs * 3W RGBW LEDs  Beam Angle: 8°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 4/26CH  Dimension:: 320*350*290mm  N.W: 4kg G.W: 4.5kg</p>
OK-VS-83	5-in-1 LED Effect Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 90W  LED:9PCS 4W RGBW 4IN1  LEDs Flower Effect: 84PCS 5mmLED  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 45°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 11/23CH  Dimension:: 320*350*290mm  N.W: 4kg G.W: 4.5kg</p>
OK-VS-84	Ball , Strobe /Chase and Laser		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED Strobe:8PCS *3W RGBA  LED BALL Effect: 6PCS*3W LED RGBWAP  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 15°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 15CH  Dimension:: 350*250*210mm  N.W: 4kg G.W: 4.5kg</p>
OK-VS-85	Gobo Effect, Strobe/Chase and Laser effect		<p>Voltage: AC110-240V, 50/60Hz  Power: 60W  LED Strobe:8PCS *3W RGBW  LED GOBO Effect: 8PCS*3W LED RGBW  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 15°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 17CH  Dimension:: 350*250*210mm  N.W: 4kg G.W: 4.5kg</p>
OK-VS-86	Gobo Effect, Derby Effect, Strobe/Chase and green & red laser effect		<p>Voltage: AC110-240V, 50/60Hz  Power: 100W  LED Strobe:8PCS *3W RGBW  LED GOBO Effect: 8PCS*3W LED RGBW  LED Derby Effect: 4PCS*3W LED RGBW  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 15°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 23CH  Dimension:: 450*300*210mm  N.W: 4kg G.W: 4.5kg</p>
OK-VS-87	Ball, Derby effect Strobe and Laser Light		<p>Voltage: AC110-240V, 50/60Hz  Power: 100W  LED Strobe:8PCS *3W RGBW  LED BALL Effect: 6PCS*3W LED RGBWAP  LED Derby Effect: 4PCS*3W LED RGBW  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 15°  Operation: Auto, DMX512,Sound, Master/Slave  Standalone modes: auto programs, sound programs  Display : 4-digit LED display  Channel: 22CH  Dimension:: 450*300*210mm  N.W: 4kg G.W: 4.5kg</p>

OK-SM10	LED Magic Ball Gobo Light		Voltage: AC110-240V, 50/60Hz Power: 50W LED BALL Effect: 8PCS*3W LED RGBW LED GOBO Effect: 4PCS*3W LED RGBW Operation: Auto, DMX512,Sound, Master/Slave Standalone modes: auto programs, sound programs Display : 4-digit LED display Channel: 8CH Dimension:: 270*260*330mm N.W: 4kg G.W: 4.5kg
OK-VS-5B	3in1 LED Strobe/UV Derby Light		Voltage: AC110-240V, 50/60Hz Power: 60W LED: 2pcs * 10W RGBW 4IN1 CREE LEDs LED: 12pcs UV+WHITE 2IN1 LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 10CH Dimension:: 330*220*200mm N.W: 1.5kg G.W: 2kg
OK-VS-58D	3in1 LED Strobe/UV Derby Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 10CH Dimension:: 230*220*200mm N.W: 1.5kg G.W: 2kg
OK-VS-59A	4in1 LED Strobe/UV Derby Laser Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs Laser Effect: Red 120mw& Green 30mw Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave Laser Effect: Red 120mw& Green 30mw Channel: 12CH Dimension:: 250*230*210mm N.W: 1.5kg G.W: 2kg
OK-VS-16	6IN1 LED LIGHT		Voltage: AC110-240V, 50/60Hz Power: 60W LED BALL: 6pcs * 3W RGB LEDs BEAM:12PCS*3w RGBW UV:8PCS*3W UV LED Strobe:80pcs SMD 5730 LED LED Effect: 8PCS *3W RGBW LED Laser Effect: Red 120mw& Green 30mw Operation: Auto, DMX512,Sound, Master/Slave
OK-VS-17	4IN1 LED LIGHT		Voltage: AC110-240V, 50/60Hz Power: 60W LED BEAM: 4pcs * 10W RGBW CREE LEDs UV:12PCS*3W UV LED Strobe:2pcs *20W COB LED Laser Effect: Red 200mw& Green 80mw Blue:150mw Operation: Auto, DMX512,Sound, Master/Slave
OK-VS-18	5IN1 LED Light		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 6pcs * 3W LEDs LED: 6pcs UV+WHITE 2IN1 LEDs WATERWAVE:1*5W RGBW Laser Effect: Red 120mw& Green 30mw Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave
OK-VS-58-9C	9 Colors LED Derby Light With Plastic Lens		Voltage: AC110-240V, 50/60Hz Power: 30W LED: 9pcs * 3W LEDs Beam Angle: 6° Operation: Auto, DMX512,Sound, Master/Slave,Remote control Channel: 8CH Dimension:: 230*220*200mm N.W: 1.5kg G.W: 2kg

<p><b>OK-VS-59</b></p>	<p><b>Laser Derby Light</b></p>		<p>Voltage: AC110-240V, 50/60Hz  Power: 30W  LED: 9pcs * 3W LEDs  Laser Effect: Red 120mw&amp; Green 30mw  Beam Angle: 6°  Operation: Auto, DMX512, Sound, Master/Slave  Laser Effect: Red 120mw&amp; Green 30mw  Channel: 8CH  Dimension:: 250*230*210mm  N.W: 1.5kg G.W: 2kg</p>