









APPLICATION BY CODE

ROLLED LEAD SHEET BSEN 12588 THICKNESS TO TOLERANCE OF +5%

USES	CODE 3	CODE 4	CODE 5	CODE 6	CODE 7	CODE 8	PREMIUM HOCHOL PRODUCTI 1.02
THICKNESS (MM)	1.32	1.80	2.24	2.65	3.15	3.55	
KG PER M2	14.97	20.41	25.40	30.05	35.72	40.26	
SOAKERS							A
FLASHINGS							A, B, C, D
FLAT ROOFING							A, D, E, F, H, I
PARAPET & TAPPERED VALLEYS							A, D, E, G, H, I
PITCHED ROOFS							A,D,E,F.H,I
VERTICAL CLADDING							A,D,E,F,H,I,J
DORMERS							A,D,E,F.H,I
BAY ROOFS & CANOPIES							A,D,E,F.H,I























PATINATION OIL FLASHPOINT

HALL CLIPS

FIXING STRIPS

RING SHANK NAILS

WOOD CORED ROLL

EXPANSION JOINT

BUILDING PAPER

GEOTEXTILE UNDERLAY

LEAD DOME SET

YOUR COMMITMENT TO **QUALITY**

JOIN THE TOPHAT INITIATIVE FOR EXCLUSIVE MEMBER BENEFITS

