

Declaration Of Performance

EC Construction Products Regulation
EN 12326 Roofing & Cladding Slate



Independent Slate Supplies
6 Gilston Road
Saltash
Cornwall, UK
PL12 6TW
Tel: +44 (0)1752 848 080
Fax: +44 (0)1752 848 084
info@independentslatesupplies.com
www.independentslatesupplies.com



DOP Number:		Westland Grey Green UKCA DOP			
1. Unique identification code of the product-type:		TR 899269 - 899274			
2. Type, batch or serial number or any other element allowing identification of the construction product:		30x20 35x20 40x20 40x25 50x25 60x30			
3. Intended use or uses of the construction product, in accordance with the applicable designated technical specification, as foreseen by the manufacturer:		Slate for discontinuous roofing & cladding			
4. Name, registered trade name or registered trademark and contact address of the manufacturer:		INDEPENDENT SLATE SUPPLIES LTD 6 Gilston Road, Saltash, Cornwall, UK, PL12 6TW			
5. Where applicable, name and contact address of the authorised representative:		N/A			
6. System or systems of assessment and verification of consistency of performance of the construction product:		System 4			
7. In case of the declaration of performance concerning a construction product covered by a designated standard:		The manufacturer has carried out factory production control and determination of product type based upon System 4 within the Assessment of Conformity Tasks.			
8. In case of the declaration of performance concerning a construction product covered by a European Technical Assessment:		N/A			
9. Declared Performance:					
Essential Characteristic for Pitched Roof Coverings:		Performance:		Designated Technical Specification:	
Mechanical Resistance:	Mean MOR:		EN 12326-2:2011		
	Transverse: 53.22 N/mm²	Longitudinal: 53.38 N/mm²			
	Characteristic MOR:				
	Transverse: 42.9 N/mm²	Longitudinal: 35.9 N/mm²			
External Fire Performance:	Deemed to satisfy		EC Decision 2000/553/EC		
Reaction to Fire:	Deemed to satisfy Class A1		EC Decision 96/603/EC as amended		
Dimensional Variation:					EN 12326-2:2011
Slate Type:	Very Flat	Flat	Normal	Non-Flat	
Deviation from flatness:	<0.9%	<1.0%	<1.5%	<2.0%	
Nominal thickness and variation:			6mm +/-35%		
Deviation from declared width:	+/- 5mm				
Deviation from declared length:	+/- 5mm				
Deviation from straightness of edges:	+/- 5 mm				
Deviation from rectangularity:	+/- 1%				
Durability:					EN 12326-2:2011
Water absorption:	Code A1 0.34% (<0.6%)				
Freeze thaw:	Not Required				
Thermal cycle test:	Code T1				
Sulphur dioxide exposure tests:	Code S1				
Non-carbonate carbon content:	0.2% (<2.0%)				
Apparent Mass of Calcium Carbonate	2.5%				
Release of dangerous substances:	None in conditions of use as roofing or external cladding			EN 12326-2:2011	
10. Declaration: The product(s) identified in Points 1 and 2 is in conformity with the declared performance under point 9. This declaration of performance is the sole responsibility of the manufacturer identified in point 4.					
Independent Slate Supplies Ltd 6 Gilston Road Saltash Cornwall PL12 6TW		Name: Wim van der Lugt		Position: Operations Manager	
		Signature:		Date: August 2022	