



A non-breathable alternative to 1F felt.

Sepa Light is a three-layer non-breathable roof underlay for ventilated pitched roofs.

The high-resistance membrane is a strong lightweight alternative to traditional 1F felt, and is the ideal solution when traditional ventilation is preferred.




Features and benefits

- The high-resistance membrane is a strong lightweight alternative for ventilated pitched roofs.
- Absorbent inner layer as recommended in BS 5250.
- High tensile and nail tear strength.

Area of application

- Suitable for use on ventilated pitched roofs.
- Often recommended with fibre cement roof coverings.
- All wind zones with taped headlap.
- Wind zones 1-2 with battened headlap.
(Wind zones shown are for a 345mm batten gauge.)



Related products

- Underlay Support Tray KP973910
- Permo Tape KU0121-1
- Tacto Tape KU0111
- Over Fascia Vent KP965200 / KP964300
- Roll Out Rafter Tray, all sizes.

Approvals and certifications

- CE.
- All products supplied by Klobber Ltd are covered by a 10 year guarantee against manufacturing defect.



Technical guidance

| Material | Nonwoven spunbonded polypropylene |
|--|-----------------------------------|
| Colour | Grey |
| Weight g/m ² EN 1849-2 | 120 |
| Water vapour transmission (SD value) EN 12572 | >25m |
| Resistance to water penetration EN 1928 | W1 |
| Tensile strength MD/CD (N/50mm) EN 12311-1 | 240/220 |
| Nail tear strength MD/CD (N) EN 12310-1 | 120/120 |
| Elongation MD/CD (%) EN 12311-1 | 60/60 |
| Fire rating EN 13501-1 EN11925-2 | E |
| Resistance to temperature | -40°C to +80°C |

*The Underlay can be used to provide temporary weather protection; however an exposed underlay will be subjected to UV light which may lead to premature failure; therefore, the exposure period should be kept to a minimum. An underlay is not a total waterproof barrier and if used as a temporary waterproof covering, some rain penetration may occur. In certain conditions, particularly if there is persistent heavy rainfall combined with subsequent severe freeze/thaw conditions, an underlay should not be exposed for more than a few days. (BBA)

Product information

| Product code | Width m | Length m | m ² | Weight Per Roll kg | Pallet quantity |
|--------------|---------|----------|----------------|--------------------|-----------------|
| KU979145-1 | 1 | 45 | 45 | 5.6 | 42 |