

REBEDDING • REPAIR • NEW CONSTRUCTION • SEALING


# flexim<sup>®</sup>

## Roof Putty<sup>®</sup>



**Ready-to-use**  
**Instantly waterproof**  
**Permanently flexible**  
**Storm-proof**


**Lightweight**  
**Time saving**  
**Choice of colours**  
**Tested and certified**




**Installing ridge caps and hip tiles**



**Adhering tiles or tile pieces to valleys**



**Adhering tiles to roof windows**



**Repair loose tiles**



**Repairing torn lead flashing**



**Sealing of corrugated roofs**



[www.fleximroofputty.com](http://www.fleximroofputty.com)



# flexim® Roof Putty



Flexim Roof Putty is a ready-to-use, storm-proof tile adhesive that stays flexible. Since its introduction in 1984, our roof putty has built a strong reputation and has been used on over 4 million roofs worldwide.

Flexim Roof Putty is the proud winner of the Innovation Award 1990, and has proved itself to be a reliable tile fastener and the best alternative to conventional mortar.

Flexim Roof Putty can be used for new build, re-roofing, repairs and sealing onto concrete, clay and other types of tile, including natural and fibre cement slate.



After installing, Flexim Roof Putty is instantly waterproof and will always retain its flexibility.

Flexim Roof Putty is unaffected by the contraction or expansion of the roof or by any uplift from wind on the tiles.

## Why Flexim?

- Ready-to-use
- Lightweight
- Time saving
- Instantly waterproof
- Permanently flexible
- Storm-proof
- Choice of colours
- Tested and certified



## Tested and certified

Flexim Roof Putty has been comprehensively tested by independent testing organisations. Adhesion and elasticity tests, which included intensive weathering trials, were conducted using several types of tile and slate. In 2011 Flexim also had its product tested and certified by the British Board of Agrément (BBA) to ensure that it met exacting British standards. Flexim Roof Putty also holds the USA Miami Dade certificate. On being tested at wind speeds of 110 miles/hours.



## SUITABLE FOR ALL ROOFING PROJECTS

### Adhering ridge caps and hip tiles



Remove the lightweight, ready-to-use FLEXIM strips from the packaging. Use the cover to carry the strips onto the roof.



Mark the position of the butt-joint with a piece of chalk.



Apply FLEXIM along tile or slate, using the gloves provided. Important: Make sure the joints are completely filled with FLEXIM.



Press ridge-cap, with clean hands, firmly down into the centre of the bar, ensuring that FLEXIM is both inside and outside of the ridge-cap. Keep the joints as tight as possible.





Trowel off all excess FLEXIM with your putty knife. You can reuse the excess FLEXIM. Smooth out the FLEXIM until an even finish is achieved.




Use a spatula, pointing trowel or your finger to tidy up joints. Immediately after use, clean the hands, tools and any contamination on the tiles with a dry cloth.

### Repair ridge caps and loose tiles




## Repairing fixed ridge caps with a porous cement layer



### PREPARATION

Carefully remove all sections of porous cement using a hammer and a stone chisel.


Allow a minimum of 3 cm adhesion space for the application of the Flexim.



### METHOD

Using the gloves provided, remove a Flexim bar from the packaging. With the aid of a trowel or spatula push the Flexim down into the space that has been cleared for adhesion. Use mechanical fasteners.

## Repairing torn lead flashing



### PREPARATION


The torn lead flashing and the foundation must be clean and dry.



### METHOD


Using the gloves provided, remove a Flexim bar from the packaging and apply it to the underlying roof construction beneath the torn lead.

## Installing or securing side wall tiles




### PREPARATION

Ensure a clean, dry foundation.



### METHOD

Using the gloves provided remove the Flexim bars from the packaging and apply to the outside wall.




Apply the side wall tiles to the outside wall.




Press the side wall tile firmly down into the Flexim.

## Adhering tiles or tile pieces to valleys



Ensure a clean, dry foundation.




### METHOD

Using the gloves provided, remove a Flexim bar from the packaging and position it squarely where the tile section is to be applied.

Press the tiles firmly down into the Flexim.

Smooth out the Flexim until an even finish is achieved.


## Waterproof sealing of corrugated roofs



Ensure a clean, dry foundation.

### METHOD

Fill the corrugation rebates between the frame and the corrugated sheeting with Flexim.




Apply the Flexim between the ridge piece and the corrugated sheeting.

### Please note:

- Always read the instructions before use.
- When applied in high humidity and temperatures below 5 degrees Celsius a protective skin will be formed only after 8 to 10 days.
- Never apply in continuous rainfall or on wet tiles.
- Do not hang roof ladders on ridge caps.
- Always use hook ladders.
- Not for internal consumption.
- Keep away from children.
- Not for decoration purposes.
- Apply Flexim Roof Putty continuously along edges, with solid bedding at butt joints as shown.
- To reduce excess use of Flexim in butt joints use pieces of broken tiles/slates.
- Keep the joints as tight as possible.
- Use mechanical fasteners.
- Always trowel off all excess Flexim Roof Putty with a putty knife, to achieve a smooth finish.

### Clean up!











- Remove any remnants of the Flexim Roof Putty from the ridge caps, hands, tools or the roof tiles with a dry cloth.
- If necessary, use a little turpentine.





# flexim® Roof Putty

## Technical information



Product 1

Composition 2

Field of application 3

Packaging 4

Accessories 5

Colours 6

Application 7

Odour 8

Toxicity 9

Operating temperature 10

Corrosion 11

Hazard classification 12

Fire 13

Guidelines 14

CE 15

Storage 16

Stacking 17

Shelf life 18

Strip-packaging 19

Packaging box 20

Warranty 21

Flexim Roof Putty is a flexible, high-grade thixotropic Roof Putty.

Flexim Roof Putty is based on linseed oil putty with featherweight CFC-free polystyrene and fibrous material.

Adhesive for ridge caps, hips, valleys and roof windows.

10 strips per box, total approx. 9 kg.

Flexim Putty knife, Flexim Finishing knife and Flexim Finishing knife holster

Available in red, black, grey, dark-brown and light-brown. Special colours on request. Flexim Roof Putty is paintable.



One box contains ten ready-to-use strips.

The coverage of one box depends on the profile of the tile ranging from 3 to 7 metres.

Minimal.

None.

Tested from - 25 °C to + 80 °C.

None.

Not applicable.

Auto ignition temperature > 300 °C

BBA 11/4810, US Metro Dade PA 100-95, FBC, NEN 6707/Bb.

Year CE 2013. ID Code HS 3214 9000. Cert. Nr. 010713/FLE/01. Standard EN 15824:2010

Inside.

No more than 12 boxes stacked.

In closed strip-packaging a maximum of two years.

The ECO-films for Flexim Roof Putty contain no heavy metals or plasticizers and may be incinerated without producing harmful chemicals. They remain neutral.

The packaging box is disposable (recyclable material).

The manufacturer, warrants Flexim Roof Putty as a sealing and adhesive material. Liability under this warranty is limited to the price of the product as purchased.

This guarantee applies exclusively where Flexim Roof Putty is applied as sealing product for ridge or hip tiles (both ceramic and concrete) when applied in accordance with the instructions in the leaflet.

Distributor



**iBuilding Products Ltd.**

12 Wells Promenade  
Ilkley  
West Yorkshire  
LS29 9LF

**T** 01943 607538

**E** info@ibuildingproducts.co.uk

**W** www.ibuildingproducts.co.uk

[www.fleximroofputty.com](http://www.fleximroofputty.com)

