

Product information

Fast Flash[®] is an environmentally friendly and extremely flexible flashing material which is fast and easy to work with thanks to the self-adhesive back side. Fast Flash[®] has an infinite number of uses, on the roof where a fast and reliable flashing solution is required.

General specifications

Fast Flash[®] is a composite material consisting of a stretchable aluminium grid, embedded in a silane-modified polymer rubber with a butyl coating on the back side.

Thickness	2.3mm -0.1 to +0.3mm
Density	1348 kg/m ³ equivalent to min. 3.4 kg/m ²
Dimensions	Rolls 280 and 370 mm wide, 5000 mm long
Colours	Fast Flash [®] comes in standard Traffic Grey (RAL 7043). For additional colours of Black (RAL 9011) and Tile Red (RAL 8004) please contact our sales department

(*)The sheets are measured using a thickness gauge, 16 hours after production. It should be noted that the sheet thickness changes easily when worked with.

Technical specifications

Temperature	Durable at temperatures between -40° and +90°C
UV and ozone	Fast Flash [®] is UV and ozone proof
Weather proof	Ageing resistant and weather proof
Solubility	Insoluble in water
Tightness	Fast Flash [®] is water tight
Guarantee	10 years replacement guarantee according to specified guarantee provisions

Please note If water travels from copper or bitumen onto Fast Flash[®], FlashSeal must be applied to the Fast Flash[®] surface. If you do not follow the instructions, the warranty becomes void!

Safety and environment

Health hazard class	None
Fire hazard class	Polymer: B2 (EN 13501-1) Aluminium: None Butyl: B2 (EN 13501-1)
Ecolabelling	Polymer: MAL* code 00-1 (component A) and 1-1 (component B (1993) (*Regulation for the labeling concerning inhalation hazards) Aluminium: Highly environmentally friendly material – no ecolabelling Butyl: No ecolabelling