


# Extension

"NO-PULL" SOLUTION

## TERMS FOR FITTING INSTRUCTIONS



Strap in "No-Pull" Solution Position



# Fitting Instructions

Note: Use With Standard Collars

ThunderLeash quickly and easily wraps around your dog's torso using the patented hardware design. When your dog pulls, ThunderLeash will apply safe pressure to the torso. This gentle, consistent feedback lets your dog know to stop pulling.



### READ BEFORE USING YOUR THUNDERLEASH EXTENSION

While the use of a ThunderLeash Extension in the "no pull" configuration applies much less pressure on the neck than connecting directly to a standard collar, the "no-pull" configuration does not eliminate all pressure on the neck or trachea. If your dog shows any signs of distress from pressure on the neck when using a ThunderLeash Extension, stop use and contact us. If your dog has a sensitive neck or trachea, we do not recommend using a ThunderLeash Extension. **DO NOT USE FOR TIE OUT.**

**USE WITH ANY STANDARD DOG COLLAR AND LEASH. CAN BE USED WITH BOTH FIXED-LENGTH LEASHES AND RETRACTABLE LEASHES. CAN NOT BE USED WITH A HARNESS OR OTHER NO-PULL SOLUTION.**

- 1 Clip the Thunderleash Extension onto your dog's collar and slide the extension strap into the **"No-Pull" Solution Position**.
- 2 Wrap the Thunderleash Extension around your dog's torso and slide the extension strap (just below the **D-Ring**) into the **"No-Pull" Solution Slot** (terms defined above).
- 3 Adjust the Sizing Adjustment Buckle until the Thunderleash Extension stays loosely against your dog's torso without tension on the leash. The **D-Ring** should rest near the **"No-Pull Solution Slot"** when adjusted properly. Once adjusted, slide the **Slack Ring** against the hardware to keep the loop from gapping. You should be able to easily slide two fingers between the leash and your dog's chest when your dog is not pulling.
- 4 Adjust the **Safety Buckle** to prevent too much pressure from being applied when the dog pulls. Follow guidelines in the table below to position the **Safety Buckle** properly.
- 5 Attach your normal leash to the **D-Ring** and enjoy your walk!

### SAFETY BUCKLE ADJUSTMENTS

Approximate. Adjust as needed.

DOG WEIGHT	LEASH SIZE	Distance Between Safety Buckle and Slack Buckle
12 - 25 LBS	S	~1.5-2 INCHES
26 - 100 LBS	M/L	~2.5 INCHES