




## “No-Pull” solution


### TERMS FOR FITTING INSTRUCTIONS



Strap in  
Leash Position



Strap in  
“No-Pull” Solution  
Position



“No-Pull”  
Solution  
Slot

Safety  
Buckle

Slack  
Buckle

## Fitting Instructions

Note: Use With Standard Collars



### READ BEFORE USING YOUR THUNDERLEASH

While the use of a ThunderLeash in the “no pull” configuration applies much less pressure on the neck than connecting directly to a standard collar, the “no-pull” configuration does not eliminate all pressure on the neck or trachea. If your dog shows any signs of distress from pressure on the neck when using a ThunderLeash, stop use and contact us. If your dog has a sensitive neck or trachea, we do not recommend using a ThunderLeash.

**DO NOT USE FOR TIE OUT**

### TO USE AS STANDARD LEASH:

Simply Clip to any Standard Dog Collar

### TO USE AS “NO-PULL” SOLUTION:

- Clip ThunderLeash onto your dog’s collar and slide the leash strap into the **“No-Pull” Solution Position**.
- Wrap the ThunderLeash around your dog’s torso and slide the leash strap into the **“No-Pull” Solution Slot** (terms defined above).
- Adjust the **Slack Buckle** until ThunderLeash stays loosely against your dog’s torso without tension on the leash. You should be able to easily slide two fingers between the leash and your dog’s chest when your dog is not pulling.
- Adjust the **Safety Buckle** to prevent too much pressure from being applied when the dog pulls. Follow guidelines in the table below to position the **Safety Buckle** properly.

### SAFETY BUCKLE ADJUSTMENTS

Approximate. Adjust as needed.

DOG WEIGHT	LEASH SIZE	Distance Between Safety Buckle and Slack Buckle
< 12 LBS	XS	~1–1.5 INCHES
12 - 25 LBS	S	~1.5–2 INCHES
26 - 100 LBS	M/L	~2.5 INCHES