



### Key Feature

- Indoor station: 7-inch touch screen, user friendly interface, Plug & Play
- Indoor station: Easy, cost-efficient installation, Wifi & POE Supported
- Indoor station: Receives video call and unlocks on mobile App anywhere, any time
- Indoor station: Supports live view of up to 16 IP cameras
- Door station: High quality imaging with 2MP resolution
- Door station: Easy, cost-efficient installation, Wifi & POE Supported
- Door station: Easy configuration through WEB interface
- Door station: IP65 water resistant, preventing water ingress for outdoor use

### Specification

Door station	
Operation system	Embedded Linux operation system
Flash	32 MB
RAM	256MB
Door station	
Camera	2MP HD camera
Night vision	Low illumination IR supplement mode:3 m
Backlight compensation	Support
Digital noise reduction	Support

WDR	True WDR
Field of view	Horizontal: 131° Vertical: 78°
Video Compression Standard	H.264
Stream	Main stream: 1080p@30fps, 720p@25fps Sub stream: D1@25fps
Motion detection	Support
Flash-avoid frequency	50 Hz, 60 Hz

Door station	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Audio compression standard	G.711 U
Audio compression Rate	64 Kbps
Audio intercom	Two-way audio communication

Door station	
Network protocol	TCP/IP, RSTP
Wired network	10/100 Mbps Ethernet
Door station	
RS-485	1
Alarm input	4
Debugging port	1
Grounding	1

TAMPER switch	1
<b>Door station</b>	
Power consumption	< 10 W
Working temperature	-40° C to 53° C (-40° F to 127.4° F)
Working humidity	10% to 95%
Dimension	138 mm × 65 mm × 27 mm
Installation	Surface mounting
Protection level	IP65
Indicator	2
Power supply	IEEE802.3af, standard PoE 12 VDC

<b>Indoor station</b>	
Operation system	Embedded Linux operation system
Memory	128 MB
Flash	32 MB

<b>Indoor station</b>	
Display screen	7-inch colorful TFT screen
Display resolution	1024 × 600
Operation method	Capacitive touch screen

<b>Indoor station</b>	
Audio input	Built-in omnidirectional microphone
Audio output	Built-in loudspeaker
Audio quality	Noise suppression and echo cancellation
Audio compression standard	G.711 U
Audio compression Rate	64 Kbps

<b>Indoor station</b>	
Wired network	10/100 Mbps self-adaptive
Wireless network	Wi-Fi 802.11 b/g/n
Protocol	TCP/IP, SIP, RTSP
RS-485	1 RJ-45 10/100 Mbps self-adaptive

<b>Indoor station</b>	
RS-485	1
Alarm input	8-ch alarm inputs
Relay output	2
TF card	Max to 32 G, SD 2.0 or lower version

<b>Indoor station</b>	
Power consumption	≤ 6 W
Working temperature	-10 ° C to 55 ° C (14 ° F to 131 ° F)
Working humidity	10% to 90%
Dimension (L x W x H)	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")

## Available Model

DS-KIS603-P(C)

## Accessory

### Optional

**DS-KABV6113-RS**  
Villa Door Station Rain Shield



**Headquarters**

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
www.hikvision.com



Follow us on social media to get the latest product and solution information.



