

SW-2110-P

10-Port PoE Switch

Introduction

SW-2110-P is Fast uplink Switch which provides you with a high-performance, low-cost, easy-to-use, seamless and standard upgrade to boost your old network to 100Mbps. Increase the speed of your network server and backbone connections, making Gigabit connection to a server or uplink a network necessarily.

Its PoE ports can automatically detect and supply power with those IEEE 802.3af/at compliant Powered Devices (PD).

The electrical power is transmitted along with data in one single cable allowing you to expand your network where there are no power lines or outlets, where you wish to fix devices such as AP, IP Cameras or IP Phones, etc.



Key Features

- Multiple working modes to address your business needs: Normal, Secure and Surveillance
- Support port traffic control
- Support for secure mode, all downlink ports can communicate only with uplink ports
- Up to 250m transmission distance on surveillance mode
- Support buffer optimization

- All metal housing, safe and reliable

Specifications

| Model | Description |
|---------------------------------|--|
| Ports | 10×100Mbps network ports (RJ45), including 8 PoE ports |
| Standards | IEEE802.3,IEEE802.3u,IEEE802.3az,IEEE802.3x,IEEE802.3af,IEEE802.3at |
| Switching capacity | 2Gbps |
| Forwarding performance | 1.49Mpps |
| Packet Buffer | 2Mbit |
| MAC | 8K |
| Dimensions (W×D×H) | 220mm x 150mm x 44mm(8.7"×5.9"×1.7") |
| Weight | <1.22kg |
| Power supply | AC: 100-240V, 50/60Hz |
| PoE | 802.3at/af |
| Max. PoE Power | Max capacity: 120W Max capacity for single port: 30W |
| Cooling Fans | 0 |
| Mean Time Between Failure(MTBF) | >50000 hours |
| Operating temperature | 0°C-40°C (32°F-104°F) |
| Operating humidity | 10%~90% (noncondensing) |
| Storage humidity | 5%~90% (noncondensing) |
| Indicator | PWR: Steady on: AC input is normal Off: No AC input |
| | PoE: Off: No PoE power supply Steady on: PoE power supply is normal Flashing: PoE power supply is abnormal |
| | LINK/ACT: Off: No link Steady: Linked at 10/100Mbps Flashing: Transmitting data |
| | Speed: Off: Linked at 10/100Mbps On: Linked at 1000Mbps |
| Working Mode | Default(Normal mode) : All ports can communicate with each other. VLAN(Secure mode): Downlink ports can communicate only with uplink ports. EXTEND(Surveillance mode): Transmission distance up to 250 meters. |

Zhejiang Uniview Technologies Co.,Ltd.

Building No.10, Wanlun Science Park, Jiangling Road 88, Binjiang District, Hangzhou, Zhejiang, China

Email: overseasbusiness@uniview.com; globalsupport@uniview.com

<http://www.uniview.com>

©2018 Zhejiang Uniview Technologies Co.,Ltd. All rights reserved.

*Product specifications and availability are subject to change without notice.