



## Wi-Fi 6 Wireless Mesh Router

WI-AX1800M

## **Overview**

WI-AX1800M is a gigabit dual-band mesh Wi-Fi 6 wireless router, suitable for large apartments, duplex apartments, villas, small and medium-sized shops, and other scenarios. In addition, multiple routers can be quickly connected without cables or configuration, which solves the configuration challenges of multi-device networking and adding new devices. The router supports the next-generation Wi-Fi 6 standard at 2.4 GHz and 5 GHz. The maximum wireless rate is 574Mbps at 2.4 GHz, the maximum wireless rate is 1201Mbps at 5 GHz, and the concurrent rate can reach 1775Mbps. The recommended number of connected wireless terminals is 100, which is 50% more than that supported by Wi-Fi 5.

### **Features**

#### Powerful Mesh Wi-Fi 6

Ultra-fast Wi-Fi with Mesh Wi-Fi 6 technology, the signal is stronger and the capacity is larger in intensive usage scenarios.

#### **Ultra-Fast Wi-Fi 6 Speeds**

Simultaneous 574 Mbps on 2.4 GHz and 1201 Mbps on 5 GHz totals 1775 Mbps Wi-Fi speeds.

#### **Fast Roaming**

Users can move around the Wi-Fi coverage area without service interruption.



#### **SD-LAN**

Support SD-LAN, provide remote network construction experience between headquarters and branches.

#### **Cloud Management**

The free cloud management platform simplifies a lot of equipment management time and reduces network supervision costs for network administrators.





# **Specifications**

Products	WI-AX1800M	
Hardware specifications		
Wireless Standards	IEEE 802.11ax/ac wave2/wave1/n/b/g/a	
Operating Bands	2.4GHz & 5GHz	
Spatial Streams	2.4GHz: 2x2 MIMO 5GHz: 2x2 MIMO	
Signal Rate	Up to 574Mbps at 2.4GHz Up to 1201Mbps at 5GHz	
Interface	(3)10/100/1000M Base-T LAN Ethernet ports (1)10/100/1000M Base-T WAN Ethernet ports	
Power Supply	DC 12V/1.5A	
Power Consumption	<16W	
External Buttons	reset button (long press for 8 seconds to restore the factory default configuration)	
Dimensions	188mm * 133mm * 27mm	
Environment	Operating Temperature: -20°C~55°C Storage Temperature: -40°C~70°C Operating Humidity: 5%~95% (non-condensing) Storage Humidity: 5%~95% (non-condensing)	
Software Features		
Operating Mode	Router Mode	
Operating Mode  Internet Connection Type	Router Mode  Static IP, DHCP, PPPoE Dial-Up	
	Static IP, DHCP, PPPoE Dial-Up	
Internet Connection Type	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate	
Internet Connection Type	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding	
Internet Connection Type	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding  Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired	
Internet Connection Type  Network Security	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding  Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired and wireless networking for multiple devices.	
Internet Connection Type	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding  Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired and wireless networking for multiple devices.  Wi-Fi optimization: Wi-Fi roaming, channel adjustment, power adjustment	
Internet Connection Type  Network Security	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding  Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired and wireless networking for multiple devices.  Wi-Fi optimization: Wi-Fi roaming, channel adjustment, power adjustment  Firewall: Forbid TCP/UDP flood attack	
Internet Connection Type  Network Security	Static IP, DHCP, PPPoE Dial-Up  Guest Wi-Fi; Hide SSID; Wi-Fi Isolate  Parental Control; IP/MAC binding  Wireless Security: WPA-PSK/WPA2-PSK/WPA3-SAE  Mesh: Supports zero-configuration networking of multiple devices, and supports automatic switching between wired and wireless networking for multiple devices.  Wi-Fi optimization: Wi-Fi roaming, channel adjustment, power adjustment  Firewall: Forbid TCP/UDP flood attack  Application: Port Forwarding; SD-LAN; Open VPN;  Software upgrade: Firmware upgrade online or	

# **Package Content**

Welcome to order our products. After purchasing, you will receive:

Items	Quantity
WI-AX1800M	1 pcs
Network Cable	1 pcs
DC Power	1 pcs
Quick Installation Guide	1 pcs



Wireless-Tek Technology Limited

Address: Biaofang Technology Building 402, Bao'an street, Baoan District, Shenzhen City, Guangdong, China

Website:www.wireless-tek.com

Tel:86-0755-32811290

Email:sales@wireless-tek.com

Technical Support:tech@wireless-tek.com







Cloud Management



Company Website