

# D-NVR9704-P4


## Embedded Plug & Play NVR



### Key features

- Third-party network cameras supported
- Up to 6 Megapixels resolution recording
- HDMI and VGA output at up to 1920 × 1080P resolution
- Up to 6TB Hard disk Capacity
- Support NAS, IP SAN Network Storage
- Plug & Play with 4 independent PoE network interfaces
- Support network detection, including network delay, packet loss, etc

### Rear Panel



1. Power Supply
2. Audio In
3. HDMI Interface
4. LAN Network Interface
5. Audio Out
6. VGA Interface
7. USB Interface
8. Ground
9. Power Switch
10. Network Interfaces with PoE Function

D-NVR9704-P4	
<b>Video/Audio input</b>	
IP video input	4-ch
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1kΩ)
<b>Network</b>	
Incoming bandwidth	40Mbps
Outgoing bandwidth	80Mbps
Remote connection	128
<b>Video/Audio output</b>	
Recording resolution	6MP/5MP/3MP/1080P/UXGA/720P/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Frame rate	Main stream: 50 fps (P) / 60 fps (N)
	Sub-stream: 50 fps (P) / 60 fps (N)
HDMI/VGA output	1-ch, resolution: 1920 × 1080P /60Hz, 1600 × 1200 /60Hz, 1280 × 1024 /60Hz, 1280 × 720 /60Hz, 1024 × 768 /60Hz
Audio output	1-ch, RCA (Linear, 1kΩ)
<b>Decoding</b>	
Live view / Playback resolution	6MP/5MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Capability	4-ch
<b>Hard disk</b>	
SATA	1 SATA interface for 1 HDD
Capacity	Up to 6TB for each disk
<b>External interface</b>	
Network interface	1 RJ-45 10 /100 /1000 Mbps self-adaptive Ethernet interface
USB interface	1 × USB 2.0 and 1 × USB 3.0
<b>PoE</b>	
PoE Interface	4 independent 100 Mbps PoE
Max. Power	50W
Standard	AF and AT
<b>Others</b>	
Power supply	48V DC
Consumption (without harddisk)	≤ 10W
Working temperature	-10 ° C ~ +55 ° C (14° F~131° F)
Working humidity	10 % ~ 90 %
Chassis	1U chassis
Dimensions (W × D × H)	315 × 230 × 45mm (12.4 × 9.1 × 1.8 inch)
Weight (without hard disk)	≤ 2 Kg (4.4 lb)