

Great Engineering

BenchMARK Specifications

Labels

Sensor type:

• On edge, no registration mark required

Label savings:

• Up to 2 meters (78.74 inches)per roll during set up

Type:

- Single, front & back, or wrap-around labels.
- Pressure sensitive, die-cut, rollformatted, Fan Folded,
- Opaque, clear, translucent.

Thickness:

• Minimum 0.02mm (0.007 inches)

Length:

• Greater than 25mm (0.98 inch)

Height:

- Minimum 10mm (0.39 inches)
- Maximum 230mm (9.05 inches)

Direction:

• Left Hand Leading Edge (Internal or externally wound)

Roll Diameter:

• Maximum 300mm (11.81 inches)

Roll Core Diameter:

• 38mm (1.49 inches) and 76mm (2.99 inches)

Container & Dimensions

Suitable for round containers

Container Diameter:

- Minimum 50mm (1.96 inches) Minimum 8mm (0.31 inches) with small Bottle Adapter
- Maximum 110mm (4.3 inches) standard

Construction:

- Anodized 6061 Aluminum
- Food grade Stainless steel shafts and bolts

Pack Dimensions:

- 61cm (24 inches) x 59cm (23.2 inches) x 44cm (17.3 inches)
- Weight 33kg (72.7lbs)

