



# Great Engineering

## BenchMAX Specifications

### Labels

**Sensor type:**

- On edge, no registration mark required

**Label savings:**

- Up to 2 meters (78.74 inches) per roll during set up

**Type:**

- Single, front & back, or wrap-around labels.
- Pressure sensitive, die-cut, roll-formatted, Fan Folded,
- Opaque, clear, translucent.

**Thickness:**

- Minimum 0.02mm (0.0007 inches)

**Length:**

- Greater than 25mm (0.98 inch)

**Height:**

- Minimum 10mm (0.39 inches)
- Maximum 230mm (9.05 inches)

**Direction:**

- Left Hand Leading Edge (Internal or externally wound)

**Roll Diameter:**

- Maximum 300mm (11.81 inches)

**Roll Core Diameter:**

- 38mm (1.49 inches) and 76mm (2.99 inches)

### Container & Dimensions

Suitable for round containers

**Container Diameter:**

- Minimum 8mm (0.31 inches)
- Maximum 110mm (4.3 inches) standard  
*maximum 220mm (8.66 inches) with removable or extended handle*

**Construction:**

- Anodized 6061 Aluminum
- Food grade Stainless steel shafts and bolts

**Pack Dimensions:**

- 61cm (24 inches) x 59cm (23.2 inches) x 44cm (17.3 inches)
- Weight 33kg (72.7lbs)

**Removable handle:**

- Works the same as the standard handle for containers up to 110mm (4.3inches), in diameter. Can be removed for larger containers that are pre-filled.

**Extended handle:**

- Will only label large containers from 110mm (4.3inches)- 220mm (8.66inches) in diameter (if needing to label empty).

