

Rywire Race Relay harness

12 position Deutsch (DASH)connector (optional)

- 1 yellow - reverse
- 2 green/red - ELD (electronic load detector)
- 3 orange/blue - EXTRA
- 4 yellow/green - H2O temperature
- 5 green/orange - MIL (mailfunction indication lamp)
- 6 Yellow/red - low oil light
- 7 orange - EXTRA
- 8 blue/white - VSS (speed sensor)
- 9 blue - tach
- 10 white/blue - charge warning light
- 11 green/black - reverse light
- 12 brown/white - SCS (service check signal light)

4 position Deutsch connector

- 1 Red wire Fuel -Pump This wire needs to be run to the (+) side of the fuel pump.
- 2 Red wire Fan -This wire needs to be wired to the (+) side of the fan.
- 3 Red wire Spare -This wire needs to be wired to the (+) side of the aux (pump, motor, etc).
- 4 Red wire Spare switch -This wire needs to be wired to the (+) side of the aux (Light, etc).

12 position Deutsch (switch) connector

- 1 Red - Constant power
- 2 yellow/black - Ignition switch power
- 3 white/black - Starter switch
- 4 green/yellow - Fuel pump relay
- 5 green - Fan relay

6 blue/orange - spare relay switch

7 black - ground

8 red - constant power

9 red - switch

10 X

11 X

12 X

Battery (+) needs to go to the battery via a 4awg wire.