

MYLANDS

MASONRY PAINT FOR EXTERIOR USE

PRODUCT NAME	CODE	SHEEN LEVEL
Masonry Paint (Pure White)	50 745 0001	8-10%

PRODUCT DETAILS

A waterbased acrylic for use on masonry.

NOT suitable over limewash or lime based renders.

This paint is available in white only from stock, but may be tinted to a colour on request.

APPLICATION

- ◆ Ensure all surfaces are clean, dry and free of contamination.
- ◆ If painting over powdery or porous surfaces use stabilising solution.
- ◆ Treat algal/fungal contaminated surfaces with dilute bleach or with a proprietary wash.
- ◆ Do not use in extremes of temperature.
- ◆ Use between 8°C and 30°C.
- ◆ Do not apply if there is likelihood of rain.






THINNING

If necessary to thin, water should be used **up to 10%**.

HEALTH & SAFETY

Refer to Mylands MSDS before use.

PRODUCT BENEFITS

-  **Excellent coverage properties**
-  **Fast drying**
two coats can be applied in one day.
-  **Washable**
-  **Low odour**
-  **Excellent stain and chemical resistance**

COVERAGE

On average per litre **15m²** dependant on substrate exture and porosity.

DRYING TIME

 Touch dry in **1-2 hours.**  Recoat in **4 hours.**

CLEANING

Wash brushes/rollers immediately after use, in warm water containing a little detergent.

STORAGE

This product must be protected from frost. Store at temperature above 5°C.

Use within 12 months.



+5°C

SIZES AVAILABLE



For further information
visit our website: www.mylands.co.uk
or contact us: +44 (0)208 670 9161
sales@mylands.co.uk



By Appointment to Her Majesty Queen Elizabeth II
Manufacturers of French Polishes, Stains and Wax Polishes
John Myland Limited, London

Last updated 01.11.2020