

Stud Work Type	Actual Stud Dims	Frame Assembly	Choose Finished Wall Thickness	Plasterboarding Option		Option	Jamb Kit Needed	Notes		
				On Pocket	On Rest of Wall					
TIMBER STUD	Scant/Softwood Construction Timber 3"x2" / 75x50mm	69/70 x 47*mm	70mm	95mm	One 12.5mm layer each side	One 12.5mm layer each side	1	95mm	BEST FIT - Slimmer finished wall thickness	
	CLS 3"x2" / 75x50mm	63 x 38 mm	70mm	95mm	One 12.5mm layer each side	One 6mm layer on stud work on one side. Followed by 12.5mm board each side.	2	95mm	BEST FIT - Slimmer finished wall thickness	
		63 x 38 mm	70mm	115mm	One 12.5mm layer each side followed by 9mm layer each side.	One 6mm layer on stud work on one side. Followed by 12.5mm board each side then 9mm board each side.	3	115mm	DOUBLE BOARDING OPTION	
		63 x 38 mm	75mm	100mm	One 12.5mm layer each side	One 12.5mm plasterboard layer or one 12mm plywood on stud work on one side. Followed by 12.5mm board each side.	4	100mm	Good option if you only have access to 12.5mm plasterboard	
	Scant/Softwood Construction Timber 4"x2" / 100x50mm	94/95 x 47*mm	100mm	125mm	One 12.5mm layer each side	One 15mm layer each side	5	125mm		
		94/95 x 47*mm	100mm	125mm	One 12.5mm layer each side	One 6mm layer on stud work on one side. Followed by 12.5mm board each side.	6	125mm		
	CLS 4"x2" / 100x50mm	89 x 38mm	90mm	115mm	One 12.5mm layer each side	One 12.5mm layer each side	7	115mm	BEST FIT - Slimmer finished wall thickness	
		89 x 38mm	90mm	140mm	Two 12.5mm layers each side	Two 12.5mm layers each side	8	140mm	DOUBLE BOARDING OPTION	
	METAL STUD	Metal Stud	70mm	70mm	95mm	One 12.5mm layer each side	One 12.5mm layer each side	9	95mm	BEST FIT - Slimmer finished wall thickness
			92mm	90mm	115mm	One 12.5mm layer each side	One 12.5mm layer each side	10	115mm	BEST FIT - Slimmer finished wall thickness

\*This dimension can vary