



INSTALLATION MANUAL

BETTER WEIGH™

with

TOWSENSE™
TECHNOLOGY

BETTERWEIGH™ MOBILE TOWING SCALE SETUP

1. Download the app.

Search 'BetterWeigh' in the Google Play or iOS App Store and install.

2. Installation.

BetterWeigh is compatible with OBD2 compliant vehicles (US 1996 and newer vehicles). Plug BetterWeigh into the diagnostic port, typically located below the steering wheel, near the driver's door.



NOTICE This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates, uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception,

**BETTER
WEIGH™**

which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio / TV technician for help.

 **WARNING**

Never exceed the vehicle manufacturer's recommended towing capacity.