

Project Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Item: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Date: \_\_\_\_\_

Model:  
**DUC48**

Counter:  
2 full doors



**Standard Features:**

- **SILVER LINE**  
is designed with enduring quality that will improve the efficiency and production of your restaurant. Constructed with stainless steel AISI 304/441 interior & exterior.
- **REFRIGERANT GAS**  
Environmentally friendly R404A.
- **REFRIGERATION**  
ventilated - autodefrost -auto evaporation  
- front -breathing
- **FEET**  
unidirectional feet
- **POWER CORD**  
cord and plug supplied
- **SHELVING**  
nr. 1 epoxy coated wire shelf standard,  
installed per full door section.
- **TEMPERATURE CONTROLLER**  
electronic digital controller
- **INSULATION**  
Ciclopentane High density foamed in place  
environmentally friendly.  
Kyoto Protocol Compliant:  
Zer0 ODP (Ozone Depletion Potential)  
Zer0 GWP (Global Warming Potential)  
polyurethane keeps energy costs low.

**DUC48** (in the picture)



Magnetic removable gasket without tools



Internal bottom made in S/S with stamped rounded corners to facilitate the cleaning procedures.



Digital controller

Specification may change without prior notice

**Option:**

- 
- 
- 
- 
- 
- 

| Model                     | Capacity Lt / ft <sup>3</sup> | Ambient temp. °C/°F     | Cabinet / Packing Dimensions |                       |                       | Voltage      | Hp             | Shipping Weight |
|---------------------------|-------------------------------|-------------------------|------------------------------|-----------------------|-----------------------|--------------|----------------|-----------------|
| <b>DUC48-ETL</b>          | <b>260 / 9,18</b>             | 40° / 104°              | mm / inches                  |                       |                       | 220/50       | 1/5            | 90kg/198Lbs     |
| <b>Temp. °C / °F</b>      | <b>Door</b>                   | <b>Absorbed Power W</b> | <b>L</b>                     | <b>D</b>              | <b>H</b>              | <b>Shuko</b> | <b>Shelves</b> | <b>Gas</b>      |
| -2° , 8° C<br>28° , 46° F | 2                             | 230                     | 122 (cm)<br>48 1/32"         | 81,5 (cm)<br>32 5/64" | 91,4(cm)<br>35 63/64" | 1            | 2              | R404a           |
|                           |                               |                         | 74 (cm)<br>29 9/64"          | 85 (cm)<br>33 15/32"  | 100(cm)<br>39 3/8"    |              |                |                 |

Visit Us at: [www.desmon.it](http://www.desmon.it)

Warranty: 2 years on parts



Project Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Item: \_\_\_\_\_ Quantity: \_\_\_\_\_  
 Date: \_\_\_\_\_

**Construction specifications:**

**DESIGN**

Desmon reach-in are manufactured in Italy with enduring ergonomic features to protect your long term investment. Designed using the highest technologies, quality materials and components to provide the user with colder product temperatures, lower utility costs, exceptional food safety and the best value in today's food service marketplace.

**CABINET CONSTRUCTION**

All made in stainless steel AISI 304, unique in the market place. The finest stainless available; latest generation, higher tensile strength for fewer dents and scratches. .

- Higher insulation rates thanks to high-tech environmentally friendly CFC free, Cyclopentane foaming keeping insulation properties longer than other foams. 5% of energy consumption savings guarantee if compared to other CFC free foams.
- Interior - attractive stainless steel Aisi304, ETL Sanitation & CE "rounded corners".

**REFRIGERATION SYSTEM**

- Factory engineered, self-contained, capillary tube system using environmentally friendly (HCFC free) R404A refrigerant.

- Evaporator coil & condenser balanced for low power consumption - holding the widest temperature range in its class: Temperature Range, getting the best in food preservation:
- Coolers adjustable from (-2°C to 8°C / 28 to 46°F).
- Sealed, cast iron, self-lubricating evaporator fan motor(s) and larger fan blades with a more efficient low velocity, high volume airflow design. Ensuring faster temperature recovery and shorter run times in the busiest of food service environments.

**DOORS**

- Stainless steel exterior and interior.
- Door extends full width of cabinet shell.
- Guaranteed door handle.
- Magnet Seal self-closing door.
- Guaranteed door hinges and torsion type closure system.
- Self Closing Hinged Magnetic Doors. Gasket of one piece construction, removable without tools for ease of cleaning.

**SHELVING**

- Nr. 1 heavy duty PVC coated wire included per each door

**MODEL FEATURES**

- 1 digital display adjustable with alarm and control unit standard on every GOLD models.
- Evaporator is epoxy coated to eliminate the potential of corrosion.
- ETL Sanitation and CE "Rounded Corners" compliant for food product.

**ELECTRICAL**

- Unit completely pre-wired at factory and ready for final connection to a dedicated outlet. Cord and plug set included: Voltages:  
 | 115V/60Hz/1 phase -15/20 amp or  
 | 230V/50Hz/1 phase -16 amp or  
 | 230V/60 Hz - 16 amp

**Architect Corner**

