

ELECTRIC COUNTERTOP TILTING ROUND SKILLET

JOB NAME:
ITEM NO.:
NO. REQUIRED:

MODELS

□ R1600E - 16 gallon (60 liter) electric tilting countertop skillet

DESCRIPTION

Shall be a Market Forged Model R-1600E electrically heated countertop tilting round skillet. The skillet shall have one piece coved corner, 10 gauge stainless steel pan with satin finish exterior and polished interior. The pan sides shall slope outward to facilitate access to the cooking surface. Cooking surface shall be 3/8" 10mm thick stainless clad plate, fitted with clamped on 7.5 KW electric heating elements, ensuring even heat distribution over entire cooking surface.

The skillet pan shall be mounted on side pivots to allow tilting for complete removal of contents by means of a tilting handle with a heat proof knob and marine lock. The skillet can be mounted on an optional 30" wide stainless steel stand with a sliding drain pan.

The controls shall be integrally mounted on the stainless steel clad housing and shall include a power switch, thermostat, pilot light and high temperature cut-off.

The skillet operates in a temperature range of 160°F to 450°F (71°C to 232°C)

OPERATION SHALL BE BY:

Electrical heating elements equipped for operation on:

- □ 208 VAC. 1 or 3 Phase. 50-60 Hz
- ☐ 220 VAC, 1 or 3 Phase, 50-60 Hz
- ☐ 240 VAC, 1 or 3 Phase, 50-60 Hz
- □ 220/380, 240/415 VAC, 3 Phase, 4 Wire

SHIPPING WEIGHT

220 lbs (100 kg)



Shown with optional stand, faucet and lift off cover

OPTIONS & ACCESSORIES

(at additional charge)

- Pantry Faucets
 - Double pantry faucet with swing spout.
 - ☐ Single pantry faucet with swing spout.
- □ 380, 415 or 480 VAC, 3 Phase, 50/60 Hz
- Etched gallon or liter marking
- ☐ Stand with sliding drain pan
- Lift off cover







Ε

FOOD SERVICE EQUIPMENT Round Skillet


ELECTRIC COUNTERTOP TILTING ROUND SKILLET

ELECTRICAL CHARACTERISTICS

PHASE	208 VAC		220 VAC		240 VAC		380 VAC		415 VAC		480 VAC	
PHASE	KW	AMP	KW	AMP								
1	7.5	36.0	7.5	34.1	7.5	31.3	-	-	-	-	-	-
3	7.5	20.8	7.5	19.7	7.5	18.1	7.5	11.4	7.5	10.4	7.5	9.0


SERVICE CONNECTIONS

Е	Electrical Connection				
D	Drain - 1-1/2" drain NPT				



DIMENSIONS ARE IN INCHES [MM]

Shown with optional stand and faucet





FRONT OF APPLIANCE

MOUNTING PATTERN



FLANGED FOOT DETAIL 2 EQUALLY SPACED Φ 7/16" [11MM[HOLES ON 2.25" [57MM] B.C.





The manufacturer reserves the right to modify materials and specifications without notice.

PRINTED IN U. S. A. SPEC SHEET: 14-0231 Rev E (4/17)



