


Morris CAT#: 71900B


2' LED Linear Vapor Tight 25 WATT, 3.5K-5K, 120-277V











Features:

- 0-10V Dimming
- Polycarbonate Lens with high flame retardant paint
- Heavy Duty Polycarbonate Housing & Stainless Steel Clips
- High Quality LED chips provide high efficiency

- Surface Mount Brackets
 Included
- 50,000+ Hour LED Life Expectancy
- IP65 Wet Location Rated
- cUlus Listed
- 5 Year Warranty

Part#	Housing Color	Wattage	Lumens	ССТ	Voltage	Beam Angle	Lumens/ Watt	
71900B	White	25	3,375 @4K	3.5K-5K	120-277	90° x 113°	135	

Photometry:

Morris CAT#: 71900B 2' LED Linear Vapor Tight 25 WATT, 3.5K-5K, 120-277V

Technical Specifications:

Electrical:

Input Voltage: 120 thru 277 Current: .0.19A@120V Frequency: 60Hz Power

Factor: ≥.0.9

THD: >.20% @ 120V

Product Parameters:

25 Watts

Efficacy: 135 lumens per watt 3,000 lumens @ 3.5K/5K 3,375 lumens @ 4K

50,000+ LED Life Span

CCT: 3.5K-5K

Chromacity Measurements:

CRI: >80 R9: -2

DUV: 0.0019

Component Specifications:

LED: SMD2835

Driver: 100-277V 50-60HZ

Surge Protection Volts: 1.5KV

Dimming: 0-10V

Operating Temperature:

Minimum Starting -22°F - 104°F

Construction:

Housing: Polycarbonate Housing and Stainless Steel Clasps

IP Rating: IP65 Wet Location

Lens Material: Polycarbonate Diffused/Frosted Lens

Mounting: Surface Mount Brackets Included, Suspension

Chain

Listings: cULus Listed

Carton Qty: 6 Weight: 2.4 lb

Warranty:

Morris Products carries a 5 year warranty from date of purchase against defects in materials and workmanship (assuming normal

and proper usage).