

# NT-5020

## 5" Specular Reflector with White Metal Ring

Type \_\_\_\_\_

Project \_\_\_\_\_

Catalog No. \_\_\_\_\_

Notes \_\_\_\_\_

### FEATURES

**Trim:** Metal trim with adjustable eyeball can be rotated 358° horizontally and 35° vertically. Precision spun 0.040 aluminum baffle with deep grooves to reduce aperture glare. Gimbal ring allows lamp to be mounted on top of the trim. Separate trim ring available in metal, may also be used with custom combination of plastic or metal ring finishes.

**Mounting:** Trim includes two "V" torsion springs to mount trim securely to housing. Replacement "V" torsion springs are available (NRA-86).

### COMPATIBLE HOUSINGS

Compatible with Line Voltage housings. See individual specification sheets for more information.

### LAMP


75W BR/PAR30 Maximum (NFBIC-5INCATA; NHIC-501QAT; NHRIC-504QAT; NH-501Q; NHR-504Q)

### LABELS AND LISTINGS

· cULus Listed for Wet Location when used with compatible housing



### PRODUCT IMAGES AND DIMENSIONS



### 5" Specular Reflector with White Metal Ring

Catalog No. \_\_\_\_\_

**NT-5020B** = Specular Black Reflector with White Metal Ring

**NT-5020C** = Specular Clear Reflector with White Metal Ring

**NT-5020W** = Specular White Reflector with White Metal Ring

### Compatible Housings

Catalog No. \_\_\_\_\_

**NFBIC-5INCATA** = 5" 2-Hour Fire Rated Line Voltage Housing

**NHIC-501QAT** = 5" IC Air-Tight Line Voltage New Construction Housing

**NHRIC-504QAT** = 5" IC Air-Tight Line Voltage Remodel Housing

**NH-501Q** = 5" Non-IC Line Voltage New Construction Housing

**NHR-504Q** = 5" Non-IC Line Voltage Remodel Housing

Example: **NT-5020W** = 5" Specular White Reflector with White Metal Ring