SATCO NUVO

Project Name

Location Prepared By



-		
M	_	•

Status	Active
Watts	14
Fluorescent Equivalent	25-32
Volts	120V-277V
Ballast Type	Type B
Shape	Т8
Base	Medium Bi Pin
ANSI Base	G13
Nominal Length	48
CCT (Kelvin)	6500
Temperature	Daylight
CRI	82
Lumens	1800
Beam Spread	210
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Linear
Technology	LED
Electrical	
Ballasting Requirements	Ballast Bypass; Direct wire 120- 277V line voltage; No ballast or external driver required
Operating Frequency	50/60 Hz
Dimming Type	N/A
Power Factor	0.9
Physical	
MOL	48
MOD	1
Additional Information	
Additional Info	All glass tube; Built-in shock resistant circuit
Tube Guard Use	Approved for use with tube guard

Additional Information		
Additional Info	All glass tube; Built-in shock resistant circuit	
Tube Guard Use	Approved for use with tube guards	
Warranty	5 Year Limited - T8 LED Bulbs - Ballast Bypass	
Compliance		

Compliance	
Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
CEC Status Lawful for sale in California	
RoHS Compliant	Yes







