

## LED Flat Panels

### POWER & CCT SELECTABLE



#### SUGGESTED APPLICATIONS

- New construction or remodel
- Office, schools
- Healthcare facilities
- Institutions and commercial applications

#### FEATURES

- Choose wattage and color temperature at installation for 9 possible configurations
- Low profile and light weight design
- Precision optics provide even and smooth light distribution
- Installs in drop ceiling, suspension, and surface mount applications
- Optional accessories include surface mount kit, sheetrock flange kit, suspended mount cable kit, Emergency LED driver and dimmer



### GENERAL SPECIFICATIONS

Input Voltage: 120-277V  
 Frequency: 50/60Hz  
 Power Factor, THD %: >0.9, <20%  
 Dimmable: 0-10V, down to 1%  
 Efficacy: up to 140 LPW  
 Minimum CRI: 80  
 Beam Angle: 120°

Functional Life (L70): 50,000 hours  
 Location Rating: Damp  
 Ambient Operating Temperature: -4°F to 113°F  
 IC Rated  
 Construction: Steel housing with white powder coat finish, smooth frame, and polystyrene lens

### LED Flat Panels POWER & CCT SELECTABLE

### ITEM SPECIFICATIONS / ORDER INFO

Model #	Order Code	UPC	Size (trade)	Max. Lumens	Wattage	Input Current @120V/277V	CCT	DLC ID*
PL22-35WPCTS-D	72994	751338040281	2' x 2'	3,500	25W	0.28/0.10A	3500K	S-4QB7WM
				4,200	30W*	0.33/0.12A	4000K*	
				4,725	35W	0.39/0.14A	5000K	
PL24-50WPCTS-D	72996	751338040304	2' x 4'	4,200	30W	0.33/0.12A	3500K	S-IZRWQA
				5,600	40W*	0.44/0.16A	4000K*	
				6,750	50W	0.55/0.20A	5000K	

\*Default power and CCT select setting

### NOMENCLATURE

Example: PL22-35WPCTS-D

PL=Panel Luminaire 22=2' x 2' - 35W=35 Watts - P=Power Selectable 25W|30W|35W - CTS=Color Temperature Selectable 3500K|4000K|5000K CCT - D=Dimmable  
 24=2' x 4' - 50W=50 Watts

### ACCESSORIES (SOLD SEPARATELY)

Model #	Order Code	UPC	Product Title/Description
F-L22/FRAME-87	70280	751338035461	2' x 2' Surface Mount Frame Kit
F-L24/FRAME-87	70281	751338035478	4' x 4' Surface Mount Frame Kit
F-L22/FLANGE-87	70277	751338035423	2' x 2' Sheetrock Flange Kit
F-L24/FLANGE-87	70278	751338035447	4' x 4' Sheetrock Flange Kit
F-L22/CABLE/BL-87	70282	751338036017	4' Suspended Mount Cable Kit for use with 2' x 2' Flat Panel
F-L24/CABLE/BL-87	70283	751338036031	4' Suspended Mount Cable Kit for use with 2' x 4' Flat Panel
BEL5/120-277V-92	70585	751338020177	Emergency LED Driver 120-277V
WD-DS710	70605	-	Dimmer 0-10V

### ENERGY SAVINGS Based on 12 hours/day and \$0.11/kWh

Model #	LED Wattage	Fluorescent Replacement Wattage	Watts Saved	Yearly Savings	5 Year savings
PL22-35WPCTS-D	25W	2x32T8 UBEND LBF	19W	\$9	\$46
PL22-35WPCTS-D	30W	2x32T8 UBEND NBF	28W	\$13	\$67
PL22-35WPCTS-D	40W	2x32T8 HBF	25W	\$12	\$60
PL24-50WPCTS-D	30W	3x32T8 NBF	57W	\$27	\$137
PL24-50WPCTS-D	40W	3x32T8 NBF	47W	\$23	\$113
PL24-50WPCTS-D	50W	4x32T8 HBF	50W	\$24	\$120


### NOTES

\*DLC Primary Use Designation: PL22-35WPCTS-D = 2x2 Luminaires for Ambient Lighting of Interior Commercial Spaces, PL24-50WPCTS-D = 2x4 Luminaires for Ambient Lighting of Interior Commercial Spaces  
 Dimming with standard 0-10V control system or wall dimmers. Dimming complies with IEC60929 Annex E. Fixture may not be compatible with all dimmers.  
 Dimming performance may vary based on selected dimmer. Visit [www.topaz-usa.com/led-dimmer-compatibility](http://www.topaz-usa.com/led-dimmer-compatibility) for up-to-date dimmer compatibility information.  
 This device complies with Part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.  
 FIVE (5) YEAR LIMITED WARRANTY: SOUTHWIRE COMPANY, LLC. For details visit: [www.topaz-usa.com/warranty](http://www.topaz-usa.com/warranty)  
 Specifications subject to change without prior notice. Replacement wattage shown depends on application and fixture.

## LED Flat Panels POWER & CCT SELECTABLE

### DIMENSIONS/WEIGHT

Model #	A	B	C	Weight
PL22-35WPCTS-D	23.74"	23.74"	1.67"	5.1 Lbs.
PL24-50WPCTS-D	23.74"	47.72"	1.67"	8.4 Lbs.
F-L22/FRAME-87	24"	24"	4.3"	6.6 Lbs.
F-L24/FRAME-87	24"	48"	4.3"	7.6 Lbs.
F-L22/FLANGE-87	24"	24"	1.8"	5.8 Lbs.
F-L24/FLANGE-87	26"	48"	2.9"	8.5 Lbs.



**2' x 4' Sheetrock  
Flange Kit**

**2' x 4' Frame Kit**

**2' x 2' Sheetrock  
Flange Kit**

**2' x 2' Frame Kit**

