


FUME BOSS



PORTABLE FUME EXTRACTOR

With 6.5' capture arm
800 CFM



Ensure cleaner indoor air with the Fume Boss Portable Fume Extractor.

Designed for easy transport and positioning, the Fume Boss removes weld fumes, dust and other toxins at source. Capturing airborne contaminants as small as 0.5 micron, the Fume Boss comes equipped with a Merv 15 rated Nanofiber filter. Its 6.5' internally articulated capture arm allows for easy positioning so workers can perform tasks safely and comfortably.

Outperforming the competition, the Fume Boss' high-suction capture velocity extracts and filters dust and fumes further from the hood. A cleaner air facility is guaranteed.

Features:

- Flexible 6.5' internally articulated capture arm
- 1.5HP, 1750 RPM, TEFC motor producing 800 CFM at the hood
- 18" easy-to service Nanofiber filter (MERV 15)
- Rotary starter with 15' power cord and casters

Benefits:

- Compact, portable and easy to maneuver 120 volt, single phase
- Capture-at-source for cleaner air
- Compliant with OSHA guidelines for controlling weld fumes

FUME BOSS

Primary Filter

Comes with:

Nanofiber

MERV 15 efficient cartridge filter captures particles at the submicron level, and surface-loading technology allows dust to be easily dislodged during cleaning with compressed air.



S-FB-14NF

EFFICIENCY:
FILTER MEDIA:
MEDIA AREA:
COATING:
END CAP:
CLEANING METHOD:
MAX TEMP:
FLANGE:

MERV 15
NANOFIBER
128 SQ.FT.
FIRE RETARDANT
OPEN/CLOSED
COMPRESSED AIR
180° F / 82° C
NONE



Dimensions

| Model | Arm Length (ft.) | Arm Diameter (in.) | Net Weight (lbs.) | Product Dimensions (in.) | | |
|--|------------------|--------------------|-------------------|--------------------------|------------|------------|
| | | | | Width [a] | Height [C] | Length [b] |
| FUME BOSS with articulated capture arm | | | | | | |
| FB-06-120V | 6.5 | 6 | 287 | 23 | 34 | 35 |

Technical Specifications

| Model | Motor (H.P.) | RPM | Power | | Airflow (CFM) | Cord Length (ft.) | Arm Length (ft.) |
|--|--------------|------|------------|--------------|---------------|-------------------|------------------|
| | | | Phase (hz) | @120V (amps) | | | |
| FUME BOSS with articulated capture arm | | | | | | | |
| FB-06-120V | 1.5 | 1750 | 1P/60Hz | 13.2 | 800 | 15 | 6.5 |

CONTACT US

984 Farewell St S, Unit #3
Oshawa, ON L1H 6N6
Phone: (416) 276-9211
Email: info@ccmechanical.ca