



MODEL ST-15CF

Energy Consumption Guide (based on a 24 hour time period)

Room Temp (Below)	+38°F (+3°C)	+0°F (-18°C)
70°F (21°C)	185 WHR	458 WHR
90°F (32°C)	295 WHR	705 WHR

Tested at 12VDC - Tested with no door openings



SUNSTAR Features

- 4.6 in. Polyurethane walls
- Double lid gasket
- Interior lid light
- Air cooled condenser for fast cool-down
- Coated steel interior for aesthetics & easy cleaning
- Two in one thermostat (refrigerator or freezer)
- Portable: heavy duty castors on each corner

Solar Freeze Description

Total Volume	425 Liters / 15 cu ft
Cooling System	Direct Cooling
Temperature Control	Mechanism
Rated Operating Voltage	12V9.6 - 17V / 24V21.3 - 31.5V
Fuse Rating (A)	30/15 Amp 12/24 VDC
Typical Power Draw	90 Watt
Refrigeration Agent	R134A
Blowing Agent	Polyurethane
Product Dimension (in)	W 64 / H 37.5 / D 30.75
Carton Box Dimension (in)	W 67 / H 41 / D 32
Weight Per Carton / Net Weight	215 lb / 190 lb
Performance Warranty	2 yr.