



SADE FR

001 Pristine

©Andriali 2023

Usage



CHARACTERISTICS

- Composition :** Vinyl/Urethane Topcoat
- Backing:** 100 % Polyester
- Weight:** 750 gr/m² ± 5%
- Abrasion Resistance:** >200.000 Rubs (ISO 12947-2)
- Color Fastness to Rubbing:** ISO 105 X12 (Grey Scale) ≥5
- Uv Resistance:** 1000 hours (Blue Wool Scale) ≥6/7

FLAMMABILITY

- BS 5852 Part 1 Ignition Source 0,1 (Cigarette & Match)
- EN 1021 Part 1 and 2
- BS 7176 Low Hazard
- IMO FTP Code Annex 1 Part 8
- DIN 4102 B2
- French NFP 92 503 (M2)
- US: CAL TB 117-2013, Section E
- AT: ÖNORM B 3825, Gruppe 1
- AT: ÖNORM A 3800 Teil 1
- FMVSS 302 (FR Standart of Motor Vehicles)
- *Optional DIN 4102 B1 and French NFP 92 503 (M1)
- MOQ 500 mt/Color

PERFORMANCE

- Antibacterial:** ISO 22196 Measurement of Antibacterial Activity
- Antimicrobial:** AATCC 147 Antibacterial Activity Assessment
- Antifungal:** ASTM G 21 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
- Waterproof:** BS 3424 Part 26 > 1 meter
- Safety of Toys:** EN 71-3 Safety of toys part 3: The migration of Some Elements
- Migration:** 0.1 % by mass of the plasticized material in toys and childcare articles
- Urea Resistance:** BS 3424 Part 19 After 24 hours , No Significant Deterioration
- Easy Clean:** Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach or alcohol.

SUSTAINABILITY

- STANDARD 100 by OEKO-TEX® Annex 4 product class IV Edition
- NSO-NAP 7:2018 Vegan & Vejetarian Standard

Notes

- » _____
- » _____
- » _____



1110 Brickell Avenue, Suite 300,
Miami, FL 33131
team@andrialicontract.com
andrialicontract.com