



WESTERN FR 5

001 Pristine

©Andriali 2023

Usage



CHARACTERISTICS

Composition : Vinyl/Urethane Topcoat
Backing: 100 % Viscose
Weight: 700 gr/m² ± 5%
Abrasion Resistance: >300.000 Rubs (ISO 12947-2)
Color Fastness to Rubbing: ISO 105 X12 (Grey Scale) ≥5
Uv Resistance: 1000 hours (Blue Wool Scale) ≥6/7

FLAMMABILITY

BS 5852 Part 1 Ignition Source 0,1 (Cigarette & Match)
 EN 1021 Part 1 and 2
 BS 5852 Part 1 Ignition Source 5
 BS 7176 Low Hazard
 DIN 4102 B2
 French NFP 92 503 (M2)
 UNI 9175 CLASSE 1M
 IMO FTP Code Annex 1 Part 5
 IMO FTP Code Annex 1 Part 8
 ECE R 118.03 Annex 6,7,8
 US: CAL TB 117-2013, Section E
 US: FAR 25/853
 AT: ÖNORM B 3825, Gruppe 1
 AT: ÖNORM A 3800 Teil 1
 FMVSS 302 (FR Standart of Motor Vehicles)
 *Optional DIN 4102 B1 and French NFP 92 503 (M1)
 MOQ 500 mt/Color

PERFORMANCE

Antibacterial: ISO 22196 Measurement of Antibacterial Activity
Antimicrobial: AATCC 147 Antibacterial Activity Assessment
Antifungal: ASTM G 21 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
Bleach Cleanable: ISO 105 E03 color change 4 for dilution factor 1:4 chlorine solution (Grey Scale) ≥4
Waterproof: BS 3424 Part 26 > 1 meter
Safety of Toys: EN 71-3 Safety of toys part 3: The migration of Some Elements
Migration: 0.1 % by mass of the plasticized material I in toys and childcare articles
Urea Resistance: BS 3424 Part 19 After 24 hours , No Significant Deterioration
Easy Clean: Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo.
 For deeper cleaning use bleach or alcohol. Full details can be found in our cleaning and maintenance guide.

SUSTAINABILITY

STANDARD 100 by OEKO-TEX® Annex 4 product class IV Edition
 NSO-NAP 7:2018 Vegan & Vegetarian Standard

Notes

- » _____
- » _____
- » _____



1110 Brickell Avenue, Suite 300,
 Miami, FL 33131
 team@andrialicontract.com
 andrialicontract.com