



©Andriali 2023

OASIS FR 5

013 Pale Nantucket

Usage



CHARACTERISTICS

Composition : Vinyl/Urethane Topcoat
Backing: 100 % Viscose
Weight: 750 gr/m² ± 5%
Abrasion Resistance: >100.000 Rubs (ISO 12947-2)
Color Fastness to Rubbing: ISO 105 X12 (Grey Scale) ≥5
Uv Resistance: 1000 hours (Blue Wool Scale) ≥6/7

FLAMMABILITY

IMO FTP Code Annex 1 Part 8
IMO FTP Code Annex 1 Part 5
BS 5852 Part 1 Ignition Source 0,1 (Cigarette & Match)
EN 1021 Part 1 and 2
BS 5852 Part 1 Ignition Source 5
BS 7176 Medium Hazard
DIN 4102 B2
French NFP 92 503 (M2)
UNI 9175 CLASSE 1M
ECE R 118.03 Annex 6,7,8
US: CAL TB 117-2013, Section E
US: FAR 25/853
AT: ÖNORM B 3825, Gruppe 1
AT: ÖNORM A 3800 Teil 1
FMVSS 302 (FR Standart of Motor Vehicles)

PERFORMANCE

Antibacterial: ISO 22196 Measurement of Antibacterial Activity
Antimicrobial: AATCC 147 Antibacterial Activity Assessment
Antifungal: ASTM G 21 Standard Practice for Determining Resistance of Synthetic Polymeric Materials to Fungi
Bleach Cleanable: ISO 105 E03 color change 4 for dilution factor 1:4 chlorine solution (Grey Scale) ≥4
Waterproof: BS 3424 Part 26 > 1 meter
Safety of Toys: EN 71-3 Safety of toys part 3: The migration of Some Elements
Migration: 0.1 % by mass of the plasticized material in toys and childcare articles
Urea Resistance: BS 3424 Part 19 After 24 hours , No Significant Deterioration
Easy Clean: Wipe with a damp cloth using soap and water or use proprietary upholstery shampoo. For deeper cleaning use bleach or alcohol.

SUSTAINABILITY

STANDARD 100 by OEKO-TEX® Annex 4 product class IV Edition
NSO-NAP 7:2018 Vegan & Vegetarian Standard

Notes

- » _____
- » _____
- » _____



1110 Brickell Avenue, Suite 300,
Miami, FL 33131
team@andrialicontract.com
andrialicontract.com