

DESIGN MICHELLE ENGEL BENCKSO TEC

TECHNICAL EDITOR KELLY BOWSER

© CLOUD9 FABRICS 2014 | FOR PERSONAL USE ONLY CLOUD9FABRICS.COM

MATERIALS

PARCEL QUILT FEATURING CIRRUS SOLIDS

1 FQ each of 19 Cirrus Solids: Amazon, Amber, Ash, Bark, Coral, Fuchsia, Grass, Iris, Lagoon, Lava, Ocean, Petal, Rain, Sand, Shadow, Sky, Sprout, Turquoise, Twig, Limestone

4¼ yards Limestone for Background 4½ yards for Backing ¹/₂ *yard* Limestone for Binding

CUTTING DIRECTIONS

Cutting dimensions include 1/4" seam allowances.

From each FQ of Cirrus Solids:

1-9" x WOF strip

2-9" x WOF strips of Cirrus Solids Bark

Subcut into 9" x 4¾" rectangles:

- 2- *from each:* Amazon, Amber, Iris, Lagoon, Lava, Ocean, Shadow, Sprout, Turquoise
- 4- *from each:* Ash, Coral, Fuchsia, Grass, Petal, Rain, Sand, Sky
- 6- from Bark

Subcut into 9" x 1¼" rectangles:

- 1- from each: Bark, Coral, Fuchsia, Grass, Ocean, Petal, Sand, Sky, Turquoise, Twig
- 2- from each: Amazon, Amber, Ash, Lava, Shadow
- 3- from each: Iris, Lagoon, Rain, Sprout

From Limestone:

- 6-9" x WOF strips subcut each into:
- 88- 9" x 2¼" rectangles (there will be extra)
- 7- 2¹/₂" x WOF strips
 - Piece strips together to form:
 - 2 strips- 2¹/₂" x 68¹/₂" (side borders)
 - 2 strips- 2¹/₂" x 56¹/₂" (top & bottom borders)

14- 4¾" strips x WOF strips subcut each into:

• 112- 4¾" squares

8- 2" x 8½" rectangles

ASSEMBLY DIRECTIONS

BLOCK ASSEMBLY

1. Mark a diagonal line from corner to corner on all of the (112) 4³/₄" squares. [fig 1a]

2. Place a $4\frac{3}{4}$ " background square on the corner of a 9" x $4\frac{3}{4}$ " rectangle. Sew along the line. [fig 1b] Press and trim bottom two layers leaving a $\frac{1}{4}$ " seam allowance.[fig 1c] Repeat, adding a $4\frac{3}{4}$ " background square to other side. [fig 1d] Makes 56 flying geese blocks in total.

3. Sew a 9" x 2¼" background rectangle to the side of each flying geese block. [fig 2]

4. Refer to QUILT DIAGRAM for color placement and sew a 9" x $1\frac{4}{4}$ " colored rectangle to 32 of the flying geese blocks. [fig 3]

ASSEMBLING THE QUILT

5. Start top horizontal row with a 2" x $8\frac{1}{2}$ " rectangle. Sew to Block B. Sew Block A to Block B. Sew a 9" x $2\frac{1}{4}$ " rectangle to Block A. Finish row according to [fig 4].

6. Repeat horizontal rows alternating the direction of the flying geese. Alternate starting and ending each row with a $2" \times 8\frac{1}{2}"$ rectangle per **QUILT DIAGRAM**.

7. Sew horizontal rows together per the **QUILT DIAGRAM**.

8. Sew the $2\frac{1}{2}$ " x $68\frac{1}{2}$ " sashing to each side of the quilt. Sew the $2\frac{1}{2}$ " x $56\frac{1}{2}$ " sashing to the top and to the bottom of quilt.

9. Layer the backing, batting and quilt top. Baste, quilt and bind.



QUILT DIAGRAM



