



Compact
power in
elegant
gloss black

The SB8 subwoofer is the perfect companion for any home theater or compact music system, and it makes an ideal match for any Atlantic soundbar. But don't let its petite size fool you, the SB8 shares the same high-end features found on our top of the line subwoofers.

Its down-firing design takes advantage of the acoustic benefits of woofer-to-floor acoustic coupling for exceptionally powerful response.

The down-firing ported design allows for a compact cabinet size, thereby increasing its placement flexibility. Additionally, the SB8 can squeeze into tight spots behind furniture and in cabinets with no concern of its output being muffled.

Small, unobtrusive and deceptively simple-looking, the SB8 has a rugged 8" long-throw driver with an oversized surround for exceptionally long excursion and low distortion, even at very high output levels.

Its high-current, equalized 125-watt amplifier and massive finned heat sink are proof of the power that lurks beneath its glossy surface. The SB8 has a low-end extension of 32 Hz (-3 dB) and its solid, muscular sound surprises and delights listeners every time.



SB8 High-Performance Powered Subwoofer



High-quality gloss black finish



Powerful 8" long throw driver



Features include bass management, auto-on, phase control and more...



Ported design for lower bass extension in a compact enclosure

Small but Feature Rich

Just because the SB8 is our smallest home theater sub doesn't mean we skimped on its features or hookup flexibility. Like all of our subs, the SB8 has an adjustable crossover, a crossover bypass setting for use with electronics that have built-in bass management, auto-on signal sensing, phase control, and a detachable AC power cord, and special proprietary distortion-detection circuitry that prevents the SB8 from emitting objectionably-distorted sound, regardless of how hard it's pushed.



Specifications

Bass Driver	8" long-throw
Output Power	125W RMS
Distortion (amplifier)	<0.5%
Frequency Response	32Hz - 200kHz (\pm 3dB)
Peak Output	103dB SPL into 2000 cubic feet
Inputs	Stereo line level RCA inputs Speaker level tension connectors
Outputs	Speaker level tension connectors
Dimensions (DxWxH)	10 $\frac{3}{4}$ " X 13 $\frac{1}{8}$ " X 13 $\frac{1}{16}$ " (277 X 334 X 332mm) add 1 $\frac{3}{4}$ " (45mm) H for feet add 1 $\frac{1}{2}$ " (38mm) D for knobs & grille
Weight	(unpacked) 28lbs (12.7kg)
Power Requirements	110-120/220-240V, 50/60Hz, 250W Max