


X12STW-F



WIO

Key Features

Intel® Xeon® E-2300 Processor, 10th Generation Intel® Pentium® Processor, Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 95W TDP

Intel® C256

Up to 128GB Unbuffered ECC UDIMM, DDR4-3200MHz

1 PCIe 4.0 x16 Left Riser Slot

1 PCIe 3.0 x4 (in x8, Right Riser slot)

M.2 Interface: 1 PCIe 4.0 x4 and 1 PCIe 3.0 x4

M.2 Form Factor: 2280/22110

M.2 Key: M-Key Double Height Connector

Dual LAN with Intel® i210 Gigabit Ethernet Controller

Intel® C256 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10

1 VGA port

4 USB 3.2 Gen1 ports (2 rear + 2 via headers)

1 USB 3.2 Gen2 port (1 Type A)

6 USB 2.0 ports (2 rear + 4 via headers)

Specifications

Product SKUs

MBD-X12STW-F

Physical Stats

Form Factor

Proprietary WIO

Dimension

8" x 13" (20.32cm x 33.02cm)

Processor

CPU

10th Generation Intel® Pentium® Processor, Intel® Xeon® E-2300 Processor

Single Socket LGA-1200 (Socket H5) supported, CPU TDP supports Up to 95W TDP

Core

Up to 8 cores, 16 threads

System Memory

Memory Capacity

4 DIMM slots

Up to 128GB Unbuffered ECC UDIMM, DDR4-3200MHz

Memory Type

3200/2933/2666 MT/s SDRAM

DIMM Sizes

4GB, 8GB, 16GB, 32GB

Memory Voltage

1.2V

Error Detection

Corrects single-bit errors

On-Board Devices

Chipset

Intel® C256

SATA

Intel® C256 controller for 8 SATA3 (6 Gbps) ports; RAID 0,1,5,10

IPMI

ASPEED AST2600 BMC

Graphics

1 ASPEED AST2600 BMC port(s)

Network Controllers

Dual LAN with Intel® Ethernet Controller I210-AT

Input / Output

SATA

8 SATA3 (6Gbps) port(s)

LAN

2 RJ45 Gigabit Ethernet LAN ports

USB

6 USB 2.0 port(s) (4 via header; 2 rear)

4 USB 3.2 Gen1 port(s) (2 via header; 2 rear)

1 USB 3.2 Gen2 port(s) (1 rear type A)

Video Output

1 VGA port(s)

Serial Port

2 COM Port(s) (1 header; 1 rear)

DOM

2 SATA DOM (Disk on Module) power connector support

TPM

1 TPM Header

Expansion Slots

PCIe

1 PCIe 4.0 x16 Left Riser Slot,

1 PCIe 3.0 x4 (in x8 slot)

M.2

M.2 Interface: 1 PCIe 4.0 x4; 1 PCIe 3.0 x4

Form Factor: 2280/22110

Key: M-Key

Double Height Connector

System BIOS

BIOS Type

256MB UEFI

BIOS Features

ACPI 6.0

SMBIOS 3.3

Plug and Play (PnP)

RTC (Real Time Clock) Wakeup

UEFI 2.7

USB Keyboard support

PCI 3.0

Management

Software

[Redfish API](#), [Supermicro Server Manager \(SSM\)](#),

[Supermicro Update Manager \(SUM\)](#), [SuperDoctor® 5](#),

[Super Diagnostics Offline](#), [KVM with dedicated LAN](#), [IPMI](#)

[2.0](#)

System Management Software

IPMI (Intelligent Platform Management Interface) v1.5 / 2.0 with KVM support

Power Configurations

ACPI Power Management

Security

Hardware

Trusted Platform Module (TPM) 2.0

PC Health Monitoring

Voltage

VBAT, System level control, Supports system management utility, Monitors CPU voltages, Chipset Voltage, Chassis intrusion header, 6 -fan status, +5V standby, +5V, +3.3V, +12V, Memory Voltages

LED

UID/Remote UID

CPU / System Overheat LED

Temperature

Monitoring for CPU and chassis environment

CPU thermal trip support

Thermal Monitor 2 (TM2) support

PECI

FAN

6x 4-pin fan headers (up to 6 fans)

Thermal control tachometer fan connectors

Fan speed control

6 fans with tachometer status monitoring

Overheat LED indication

Other Features

WOL, UID, Node Manager Support, M.2 NGFF connector, CPU thermal trip support for processor protection, Control of power-on for recovery from AC power loss, Chassis intrusion header, Chassis intrusion detection, ACPI power management

Operating Environment

Operating Temperature Range

0°C - 50°C (32°F - 122°F)

Non-Operating Temperature Range

-40°C - 70°C (-40°F - 158°F)

Operating Relative Humidity Range

8% - 90% (non-condensing)

Non Operating Relative Humidity Range

5% - 95% (non-condensing)

Parts List

Standard Parts (Bulk Package)

I/O CablesPart Number CBL-0044L • [eStore](#)

Qty 2

Description 57.5CM SATA FLAT S-S PBF

Standard Parts (Retail Package)

I/O CablesPart Number CBL-0044L • [eStore](#)

Qty 4

Description 57.5CM SATA FLAT S-S PBF

QRG

Part Number MNL-2354-QRG

Qty 1

Description Motherboard Quick
Reference Guide

Optional Parts

TPM security module

Part Number	AOM-TPM-9670V	AOM-TPM-9671H	AOM-TPM-9670H	AOM-TPM-9671V
Qty	1	1	1	1
Description	SPI capable TPM 2.0 with Infineon 9670 controller with vertical form factor	SPI capable TPM 1.2 with Infineon 9670 controller with horizontal form factor	SPI capable TPM 2.0 with Infineon 9670 controller with horizontal form factor	SPI capable TPM 1.2 with Infineon 9670 controller with vertical form factor