



60 MINUTES **FIRE**  
PROTECTION WITH  
**CERTIFIED BURGLARY**  
RESISTANCE



# DUPLEX

FIRE-RESISTANT DOCUMENT PROTECTION



## KEY FEATURES


- High-quality cabinet certified to protect documents from fire for up to one hour (EN 15659 – 60 Paper)
- EN 14450 Level S2 ECB•S certified against burglary attacks to protect confidential or sensitive documents
- Available in three sizes with capacities ranging from 446 to 773 litres with double doors for all models
- Designed for the office environment. The small model with a low-height size is perfectly suited for installation under the windows to adapt to any building environmental configuration
- One high-security key lock fitted as standard (certified EN 1300, Class A)
- Designed to be anchored: the cabinet is supplied with two anchoring bolts
- Since opening the doors 90° will provide full access, several cabinets can be placed directly next to each other
- Durable powder coating in standard RAL 7035
- Customisable with a wide range of fittings, including shelves or pull-out file frame. The internal ladder-style racking allows the interior fittings to be adjusted as needed

# DUPLEX


## PRODUCT SPECIFICATIONS

Model	External height (mm)	External width (mm)	External depth* (mm)	Internal height (mm)	Internal width (mm)	Internal depth (mm)	Volume (litres)	Weight** (kg)	No. of doors	No. of shelves***
450	1200	1250	585	1030	1110	390	446	440	2	2
550	1950	940	585	1760	800	390	550	460	2	4
775	1950	1250	585	1785	1110	390	773	650	2	4

\* Projection of handle (40mm) not included. \*\* Product weight can fluctuate +/- 10%. \*\*\* Shelves are designed to accept hanging folders.



1.



2.

## INTERNAL FITTINGS

1. Pull-Out Filing Frame
2. Filing shelf

## LOCK OPTIONS



A high-security key lock – certified Class A in accordance with European standard EN 1300 – is fitted as standard.

Alternative locking options are available at additional costs.

## CONSTRUCTION

The insulation material used to provide fire resistance is so effective that the thickness of the cabinet walls has been kept to a minimum to maximise storage capacity.

When opened to 90°, the doors allow full access to the contents of the cabinet. This means several cabinets can be placed next to each other without restricting access.



Approved by the Association of Insurance Surveyors

Authorised dealer

## CERTIFICATION

### S2 BURGLARY PROTECTION



Certified by ECB•S in accordance with the EN 14450 standard for burglary protection to Level S2

### FIRE TESTING

Chubb safes Duplex has been approved in accordance with EN 15659 in fire class 60 Paper. This means the cabinet will protect paper documents for up to one hour. The certification was awarded by ECB•S (European Certification Board•Security System).

### TEST PROCEDURE



Stage 1.  
The cabinet is heated in accordance with the ISO 834 standard time/temperature heating curve in line with the requirements of EN 15659. After 60 minutes the furnace temperature is almost 1000 °C.

### Stage 2.

At the end of the heating period, the cabinet is removed from the furnace. At no time during the test did the internal temperature exceed 170 °C.

[www.chubbsafes.com](http://www.chubbsafes.com)