

CDe120

Ultra Efficient Conveyor Dishwasher
W 1755mm x D 765mm x H 1835mm

CDe120 is engineered to maximise efficiency with our lowest power and water consumption. Since 1981 Washtech dishwashers have been constructed in New Zealand from heavy-duty stainless steel, and are engineered specifically for the unique Australian conditions and regulations. Backed by the most extensive service network and spare parts inventory in the region, your CDe120 will not let you down.

Special Features:

- Integrated heat recovery unit which significantly reduces steam emissions and energy consumption
- SEED certified for installation without an extraction canopy in most situations
- 3-stage EcoRinse for exceptional rinse performance and minimal water usage

Standard Features:

- Capacity of up to **120 racks per hour** (2,160 plate equivalents)
- Low cold water consumption of **180 litres per hour**
- Heavy-duty stainless steel construction and wash manifold
- Full thermal and acoustic insulation
- Full width, easily removable stainless steel wash filter trays for easy cleaning
- Removable upper and lower heavy-duty stainless steel wash arm cassettes
- Powerful drive with safety clutch allows the machine to wash heavy items with ease
- Automatic start/stop minimises operating costs by halting operation when no rack is present
- 1200mm wash module featuring 3-stage EcoRinse
- Dual speed drive
- Will wash items up to 400mm high, and taller with suitable operator procedures
- Digital temperature gauges for easy HACCP reporting
- In-house CAD design service for every site layout
- Watermark approved backflow prevention
- Comprehensive Moffat 5-2-1 warranty

Includes:

- 2 x 500mm dish rack (600 70028)
- 2 x 500mm cup rack (600 70029)
- 2 x cutlery container (C660503)
- 1 x cutlery basket (C660508)

Optional Accessories include:

- Dryer modules
- Straight and curved roller tables
- Pre-rinse troughs
- Setdown benches
- Custom scrap/sort stations
- Sideload tables
- Inlet and outlet corner pawl drives
- Heavy duty roller table limit switch



CDe120



moffat.com.au
washtech.com.au

Moffat Pty Limited

VIC/TAS/SA

70 Springvale Road
Mulgrave, Victoria 3170
Telephone 03-9518 3888
Fax 03-9518 3833
vsales@moffat.com.au

NSW

Telephone 02-8833 4111
nswsales@moffat.com.au

QLD





Telephone 07-3630 8600
qldsales@moffat.com.au

WA

Telephone 08-9413 2400
wasales@moffat.com.au

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.

© Copyright Moffat Ltd
Version: WCDE120XXXX 2109



A – Hot Water and D – Cold Water *

Hot Temp 65°C
Cold Temp <25°C
Connections 3/4" male
Pressure 200-350kPa
Flow 20 litres per min
Quality Potable - refer table
Backflow Prevention DCV
Consumption 180 litres per hour **

B - Waste

Connection 1.5" BSP male
Line 2.0" / 50mm minimum

C - Electrical	V	Hz	A/phase	Max kW
Three Phase	415	50	35	26.00

Dimensions

	Machine	Packed
Width (mm)	1755	2300
Depth (mm)	765	1000
Height (mm)	1835	1950
Weight (kg)	245	325
Volume (m ³)		4.49

Water Quality

	Min	Max
pH	7	8
Hardness (ppm)	20	100
Cl-		100
SO ₄		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl ₂		0.1

G – Air Outlet

No direct connection permitted. Certified for installation without extraction subject to min. background ventilation of 1.1m² free area opening **OR** 350L/sec mechanical ventilation **OR** air change. Consult with a ventilation engineer.

* Cold water inlet required. Additional hot water inlet recommended for best performance.

** Water consumption rates may vary based on site conditions.

Isolating switch must be within 1m of, and not directly behind the machine.

Refer to operator manual for installation instructions.



an Ali Group Company

