





### STANDARD FEATURES

1, 2 and 3 minute dishwashing cycles
2.2L per cycle water consumption
Compatible with 500mm racks
Washes up to 1,080 dishes per hour
Adjustable benchgap of 595mm to 640mm
Washtech hybrid controls
Easy change to higher power / rapid rinse recovery mode

Hands-free auto-drain with drain pump

1.0HP wash pump and dual chemical pumps

Hands duty stainless stool wash manifold and scrap trave

Heavy duty stainless steel wash manifold and scrap trays Stainless steel wash and drain filter

#### Includes

1x 500mm dish rack (600 70028) 1x 500mm cup rack (600 70029) 1x cutlery container (C660503)

# Quick connection kit (all hoses and 15A plugset)

## **SPECIFICATIONS**

| A - Hot Water       |                            |
|---------------------|----------------------------|
| Temperature         | 65°C                       |
| Connection          | 3/4" male, hose supplied   |
| Pressure            | 200-350kPa                 |
| Flow                | 20L per minute             |
| Backflow prevention | Atmospheric vacuum breaker |
| Consumption         | 2.2L per cycle*            |
|                     |                            |


### D - Drainage


| Drain p | oump flexi-h | nose | 25mm |
|---------|--------------|------|------|
|---------|--------------|------|------|

| C - Electrical | V       | Hz | A/ph | Max kW |
|----------------|---------|----|------|--------|
| Single phase   | 230-240 | 50 | 15   | 3.25   |
| Single phase   | 230-240 | 50 | 25   | 5.75   |
| Three phase    | 400-415 | 50 | 15   | 7.50   |

\*Water consumption rates my vary based on site conditions Isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions


In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.











| Dimensions  | Machine | Packed |
|-------------|---------|--------|
| Width (mm)  | 730     | 760    |
| Depth (mm)  | 710     | 820    |
| Height (mm) | 1530    | 1460   |
| Weight (kg) | 94      | 125    |
| Volume (m3) |         | 0.91   |
|             |         |        |

| Water Quality | Min | Max  |
|---------------|-----|------|
| рН            | 7   | 8    |
| TDS           | 1   | 135  |
| CI-           |     | 100  |
| SO4           |     | 400  |
| Fe            |     | 0.1  |
| Mn            |     | 0.5  |
| Cu            |     | 0.05 |
| Cl2           |     | 0.1  |

Corner installation: machine must face left for access to controls; allow 300mm front clearance for service access; and splashback return <150mm.

Inline installation: front panels can be adjusted to 605mm leaving upper 80mm sill only at 650m; for sites requiring full cabinet <650mm, order WXP0031.









an Ali Group Company

