






STANDARD FEATURES

1 and 2 minute dishwashing cycles 2.2L per cycle water consumption Compatible with 500mm racks Washes up to 1,080 dishes per hour Washtech hybrid controls Hands-free auto-drain 0.5HP wash pump Dual chemical pumps Drain pump Stainless steel wash and drain filter

Includes

1x 500mm dish rack (600 70028)
1x 500mm cup rack (600 70029)
1x cutlery container (C660503)
Quick connection kit (all hoses and 15A plugset)



SPECIFICATIONS

A - Hot Water	
Temperature	65°C
Connection	3/4" male, hose supplied
Pressure	200-350kPa
Flow	20L per minute
Backflow prevention	Atmospheric vacuum breaker
Consumption	2.2L per cycle*
D - Drainage	
Drain pump flexi-hose	25mm

C - Electrical	V	Hz	A/ph	Max kW
Single phase	230-240	50	15	3.37

Dop ()	000	000
Height (mm)	840	940
Weight (kg)	54	64
Volume (m3)		0.37
Water Quality	Min	Max
рН	7	8
TDS	1	135
CI-		100
SO4		400
Fe		0.1
Mn		0.5
Cu		0.05
Cl2		0.1

Machine

570

600

Dimensions

Width (mm)

Depth (mm)

*Water consumption rates my vary based on site conditions Isolating switch must be within 1m of, and not directly behind, the machine Refer to operator manual for installation instructions

In line with policy to continually develop and improve its products, Washtech reserves the right to change specifications and design without notice.





Packed

605

660





an Ali Group Company

