

TECHNICAL DATA SHEET

Ceramic Wall Tile – Babylon

Product

Ceramic wall tile is the name given to a dry pressed, glazed ceramic tile with a high-water absorption rate. These tiles are usually single fired, and thanks to their technical characteristics, they are particularly suited as an indoor wall covering in residential and commercial premises.

Technical Data

Material: Ceramic Tile

Water absorption: 10%

Shade variation: V3 Moderate

Cutting

The ceramic tile can be cut on a continuous rim or suitable segmented diamond blade suitable for ceramic tile on a wet saw. Eye protection and a good quality mask should be used when cutting ceramic tiles.

Adhesive and Grout

We recommend contacting your preferred adhesive supplier for suitable adhesives and grouts. We recommend setting with a minimal grout joint.

Babylon Wall Tiles Sealing

These products feature a transparent crackle glaze. All glazes are subject to crazing, however, due to the deep transparent nature, craze lines can discolour the product over time, particularly on light-coloured tiles. To prevent this, particularly in harsh environments such as showers or behind a sink, we recommend that the product be sealed prior to cutting and grouting.

We recommend the Miracle 511 Porous Plus Penetrating Sealer. The sealer will keep the tiles in pristine condition. Follow the manufacturers recommendation for sealer application.

Cleaning and Maintenance

Remove loose dust and dirt with a damp cloth or sponge. Use a ph. neutral, non-abrasive cleaner suitable for ceramic tiles. Remove the cleaning solution with a clean damp cloth or sponge.

Applications

The product is suitable for most internal wall surfaces and wet areas (shower wall coverings). The product is not recommended for areas subject to water immersion ie swimming pools etc.