

# THIXO-TROP

## Thixo-Trop: Advanced Thixotropic Water Based Coating



### Brief Description:

Thixo-Trop is an advanced, water-based, thixotropic acrylic coating solution, delivering a refined semi-gloss finish in a sleek black hue.

### Technical Description:

Thixo-Trop is a water-based coating with a semi-gloss, black finish that leans toward matte without being flat. Its thixotropic properties mean it retains its shape until brushed, allowing for precise use. Additionally, Thixo-Trop offers three different ways to utilize its protective benefits.

### Usage Instructions:

#### Direct-to-Metal Applications:

1. Clean the surface to remove oil and contaminants.
2. Eliminate loose rust via wire wheeling.
3. Apply a 6-10 mil wet film of Thixo-Trop using a brush or roller.
4. For a second coat, wait at least 1 hour; longer in damp or cold conditions.

#### With Rusts Gone:

1. Follow Rusts Gone application directions, ensuring surface is dry.
2. Apply a 6-10 mil wet film of Thixo-Trop using a brush or roller.
3. For a second coat, wait at least 1 hour; longer in damp or cold conditions.

#### With Optional Zinc Powder:

1. Add 1-3 packets of zinc to a gallon of Thixo-Trop, mixing until a consistent gray color is achieved.
2. Follow the directions for direct-to-metal applications (For maximum results, apply directly to bare metal and avoid using over an existing primer or paint).
3. Use zinc-free Thixo-Trop for topcoat.

### Dilution and Mixing:

Thixo-Trop should not be diluted. Ensure the product is thoroughly stirred before application. For enhanced protection, there is an option to mix in zinc with Thixo-Trop.

### Features and Benefits:

**Consistency:** Maintains its thickness until subjected to friction, like brushing.

**Zinc Integration:** Incorporating zinc offers added cathodic protection.

### Frequency of Use:

Thixo-Trop is a coating formulated for repeated applications as required.

### Health and Safety:

HMIS RATING	
Health :	0
Flammability :	0
Reactivity :	0
Personal Protection :	A

### Available Packaging:

- 1 Gallon
- 5 Gallon Pail
- 55 Gallon Drum

### Contact Information:

- Address: 1927-A County Rd. 129, Pearland, TX 77581
- Phone: 832-242-1147
- Email: [info@saltsgone.com](mailto:info@saltsgone.com)
- Website: <https://saltsgone.com>

Full SDS is available as a separate document.

[www.saltsgone.com](http://www.saltsgone.com)