

2 Ton Electric Sit Down Rider Tow Tractor

Superlift SLXT20 2 Ton Electric Sit Down Rider Tow Tractor is mainly used for towing and order picking, and it is especially suitable for goods that move in the continuous flow. It is widely used for industries that where just-in-time principles are needed.

FEATURES

- Wheelbase provides a tight turning radius for maximum maneuverability and control in confined work environments.
 - Rear bridge drive unit provides this 4 ton tow tractor with excellent power and gradeability.
 - Ergonomically designed compartment allows easy operation of all controls and pedals to help reduce operators' fatigue.
 - This electric tow tractor is equipped with forward lever or reverse lever and floor-mounted accelerator pedal which provide fast and easy direction control changes.
 - 2 ton tow tractor is installed with heavy duty suspension seat with arms, multi-angle back support, sliding base and safety belt. This can improve operator's comfort and safety.
 - Low step height allows for easy entry and exit.
 - Small-diameter steering wheel
- 
- provides effortless steering of this electric tow tractor.
 - Motorbike handle: The electric tugger is equipped with a motorbike style handle which is intuitive and familiar to control. The operation is easy and turning is highly flexible.
 - Comfortable seat: The wide and comfortable seat is designed to relieve the fatigue of the operators.

2 Ton Electric Sit Down Rider Tow Tractor

SPECIFICATIONS

Identification	1	Product Model		SLXT20
	2	Power supply		Electric
	3	Operating type		sitting on
	4	Load capacity	Q t	2
	5	Traction weight	F N	686
	6	Wheelbase	Y mm	1030
weight	1	Weight	kg	584
Wheel	1	Tires		PU
	2	Tire size drive end	mm	3.50-5-6PR
	3	Tire size load end	mm	4.00-8-6PR
	4	Wheels number (x=drive wheel) drive end/load end		1/2x
	5	Tread width drive end	mm	-
	6	Tread width load end	mm	680
Dimensions	1	Total height	h1 mm	1330
	2	Draw hook Height	h2 mm	259/309/334/384
	3	Overall length	L mm	1645
	4	Overall width	W mm	800
	5	Minimum ground clearance	h3 mm	82.5
	6	Turning radius	R mm	1805
Performance	1	Travel speed loaded/unloaded	km/h	8/9
	2	tractive effort loaded/unloaded 60min	N	686
	3	Max tractive effort loaded/unloaded 5min	mm/s	1783
	4	Max gradeability loaded/unloaded	%	5/8
	5	Service brake		hydraulic
Electric Motor	1	Drive motor rating	kw	2.5
	3	Battery voltage / nominal capacity	V/Ah	24/180
	4	Battery weight	kg	180
Others	1	Type of drive control		AC curtis
	2	Noise level at operator's ear	dB(A)	<70

2 Ton Electric Sit Down Rider Tow Tractor

DRAWINGS

