

DOUBLE SCISSOR LIFTS

OPTIONS

- Rotating Platforms
- Safety Skirts
- Roller Conveyor
- Tilting Platforms
- Self Propelled
- Ball Transfer

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



60" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-60-20	2,000	30 x 48	30 x 48	10	70	35 sec	1	1,800
DSL-60-40	4,000	30 x 48	30 x 48	14	74	70 sec	1	1,800
DSL-60-60	6,000	30 x 48	30 x 48	16	76	90 sec	1	1,900
DSL-60-80	8,000	30 x 48	30 x 48	16	76	35 sec	3	1,900
DSL-60-100	10,000	30 x 48	30 x 48	16	76	40 sec	3	2,000

DOUBLE SCISSOR LIFTS

- Stainless Steel and Galvanized
- Toe Guards
- A/C / AIR / DC Power Options
- Portable Units
- Custom Sizes

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



72" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-72-20	2,000	30 x 60	30 x 60	10	82	45 sec	1	2,000
DSL-72-40	4,000	30 x 60	30 x 60	14	86	90 sec	1	2,100
DSL-72-60	6,000	30 x 60	30 x 60	16	88	110 sec	1	2,200
DSL-72-80	8,000	30 x 60	30 x 60	16	88	40 sec	3	2,300
DSL-72-100	10,000	30 x 60	30 x 60	16	88	50 sec	3	2,400

Triple and Quad Lifts available to 300" Travel and 100,000 lbs capacity

SuperLift/UltraLift

69 Penelope Drive, Kitchener, Ontario
N2N 3C5 • Fax: (519) 895-2017

DOUBLE SCISSOR LIFTS

OPTIONS

- Rotating Platforms
- Safety Skirts
- Roller Conveyor
- Tilting Platforms
- Self Propelled
- Ball Transfer

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



84" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-84-20	2,000	30 x 72	30 x 72	10	94	35 sec	1	2,500
DSL-84-40	4,000	30 x 72	30 x 72	14	88	70 sec	1	2,600
DSL-84-60	6,000	30 x 72	30 x 72	16	90	40 sec	3	2,700
DSL-84-80	8,000	30 x 72	30 x 72	16	90	50 sec	3	2,800
DSL-84-100	10,000	30 x 72	30 x 72	16	90	70 sec	3	3,000

- Stainless Steel and Galvanized
- Toe Guards
- A/C / AIR / DC Power Options
- Portable Units
- Custom Sizes

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



96" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-96-20	2,000	48 x 84	48 x 72	10	106	60 sec	3	3,000
DSL-96-40	4,000	48 x 84	48 x 72	14	110	70 sec	3	3,100
DSL-96-60	6,000	48 x 84	48 x 72	16	70	60 sec	5	3,200
DSL-96-80	8,000	48 x 84	48 x 72	16	72	70 sec	5	3,300
DSL-96-100	10,000	48 x 84	48 x 72	16	74	75 sec	5	3,500

Triple and Quad Lifts available to 300" Travel and 100,000 lbs capacity

SuperLift/UltraLift

69 Penelope Drive, Kitchener, Ontario
N2N 3C5 • Fax: (519) 895-2017

DOUBLE SCISSOR LIFTS

OPTIONS

- Rotating Platforms
- Safety Skirts
- Roller Conveyor
- Tilting Platforms
- Self Propelled
- Ball Transfer

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



120" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-120-20	2,000	48 x 96	48 x 96	14	134	30 sec	5	3,000
DSL-120-40	4,000	48 x 96	48 x 96	14	134	35 sec	5	3,200
DSL-120-60	6,000	48 x 96	48 x 96	16	136	35 sec	5	3,800
DSL-120-80	8,000	48 x 96	48 x 96	16	136	50 sec	5	4,400
DSL-120-100	10,000	48 x 96	48 x 96	16	136	60 sec	5	4,800

DOUBLE SCISSOR LIFTS

- Stainless Steel and Galvanized
- Toe Guards
- A/C / AIR / DC Power Options
- Portable Options
- Custom Sizes

FEATURES

- Strong welded hollow structural tube frames with steel plates laminated to sides for stability
- Heavy duty hydraulic cylinders
- Velocity fuses on cylinders
- 1 year warranty
- Spherical bearings with grease fittings
- Overload protection with built in pressure relief valves
- Heavy Duty cam followers



144" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Up Speed	Motor HP	Shipping Wt. lbs
DSL-144-20	2,000	54 x 108	54 x 108	16	160	60 sec	5	3,200
DSL-144-40	4,000	54 x 108	54 x 108	16	160	60 sec	5	3,400
DSL-144-60	6,000	54 x 108	54 x 108	18	162	60 sec	5	3,550
DSL-144-80	8,000	54 x 108	54 x 108	20	164	60 sec	5	4,000
DSL-144-100	10,000	54 x 108	54 x 108	20	164	60 sec	5	4,200

Triple and Quad Lifts available to 300" Travel and 100,000 lbs capacity

SuperLift/UltraLift

69 Penelope Drive, Kitchener, Ontario
N2N 3C5 • Fax: (519) 895-2017