

# STANDARD SCISSOR LIFTS

## OPTIONS

- Platforms to 8' Wide and 16' Long
- Turn Tables, Manual and Powered
- Self Propelled
- Conveyor
- Ball Transfer
- Safety Skirts

## FEATURES

- Life time no lubrication DU bearings
- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



### 24" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL24-20	2,000	24 x 36	24 x 36	8	31	1	450
SL24-40	4,000	24 x 36	24 x 36	8	32	1	610
SL24-60	6,000	24 x 36	24 x 36	8	32	1	790
SL24-80	8,000	24 x 36	24 x 36	12	36	3	900
SL24-100	10,000	24 x 36	24 x 36	12	36	3	1,000

- Photo Eyes
- Electro-mechanical Toe Guards
- Tilts
- Low Profile
- Stainless Steel and Galvanized
- Custom Paint
- Portable Units

## FEATURES

- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Life time no lubrication DU bearings
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



### 30" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL30-20	2,000	24 x 48	24 x 48	8	38	1	490
SL30-40	4,000	24 x 48	24 x 48	8	39	1	725
SL30-60	6,000	24 x 48	24 x 48	8	39	1	850
SL30-80	8,000	36 x 48	24 x 48	12	42	3	975
SL30-100	10,000	36 x 48	24 x 48	12	42	3	1,010

We build standard Scissor Lifts to 300" Travel and 100,000 lbs capacity

## SuperLift/UltraLift

69 Penelope Drive, Kitchener, Ontario  
N2N 3C5 • Fax: (519) 895-2017

# STANDARD SCISSOR LIFTS

## OPTIONS

- Platforms to 8' Wide and 16' Long
- Turn Tables, Manual and Powered
- Self Propelled
- Conveyor
- Ball Transfer
- Safety Skirts

## FEATURES

- Life time no lubrication DU bearings
- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



### 36" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL36-20	2,000	24 x 48	24 x 48	8	43	1	550
SL36-40	4,000	24 x 48	24 x 48	8	45	1	800
SL36-60	6,000	24 x 48	24 x 48	8	45	1	925
SL36-80	8,000	36 x 48	24 x 48	12	48	3	1,050
SL36-100	10,000	36 x 48	24 x 48	12	48	3	1,120

STANDARD SCISSOR LIFTS

- Photo Eyes
- Electro-mechanical Toe Guards
- Tilts
- Low Profile
- Stainless Steel and Galvanized
- Custom Paint
- Portable Units

## FEATURES

- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Life time no lubrication DU bearings
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



### 40" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL40-20	2,000	24 x 60	24 x 60	8	47	1	625
SL40-40	4,000	24 x 60	24 x 60	8	49	1	850
SL40-60	6,000	24 x 60	24 x 60	8	49	1	1,000
SL40-80	8,000	36 x 60	36 x 60	12	52	3	1,100
SL40-80	10,000	36 x 60	36 x 60	12	52	3	1,200

We build standard Scissor Lifts to 300" Travel and 100,000 lbs capacity

**SuperLift/UltraLift**

69 Penelope Drive, Kitchener, Ontario  
N2N 3C5 • Fax: (519) 895-2017

Page 6

sales@superlift.net

1-800-884-1891

www.superlift.net

# STANDARD SCISSOR LIFTS

## OPTIONS

- Platforms to 8' Wide and 16' Long
- Turn Tables, Manual and Powered
- Self Propelled
- Conveyor
- Ball Transfer
- Safety Skirts

## FEATURES

- Life time no lubrication DU bearings
- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



## 48" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL48-20	2,000	24 x 72	24 x 72	8	56	1	825
SL48-40	4,000	24 x 72	24 x 72	8	57	1	1,000
SL48-60	6,000	24 x 72	24 x 72	8	57	1	1,275
SL48-80	8,000	36 x 72	36 x 72	12	60	3	1,350
SL48-100	10,000	36 x 72	36 x 72	12	60	3	1,395

- Photo Eyes
- Electro-mechanical Toe Guards
- Tilts
- Low Profile
- Stainless Steel and Galvanized
- Custom Paint
- Portable Units

## FEATURES

- Life time no lubrication DU bearings
- Velocity Fuses on all cylinders
- Overload Protection with built in pressure relief valves
- Reinforced Platforms
- Rugged Welded Frames
- Heavy Duty Cam Followers
- North American Components
- Heavy Duty hard chromed hydraulic cylinders
- 1 Year Warranty



## 60" Lift

Model	Capacity lbs	Platform Size In.	Base Size In.	Lower Ht. In.	Raised Ht. In.	Motor HP	Shipping Wt. lbs
SL60-20	2,000	24 x 88	24 x 88	8	68	1	910
SL60-40	4,000	24 x 88	24 x 88	8	69	1	1,150
SL60-60	6,000	24 x 88	24 x 88	8	69	1	1,300
SL60-80	8,000	36 x 88	36 x 88	12	72	1	1,500
SL60-100	10,000	36 x 88	36 x 88	12	72	3	1,600

We build standard Scissor Lifts to 300" Travel and 100,000 lbs capacity

## SuperLift/UltraLift

69 Penelope Drive, Kitchener, Ontario  
N2N 3C5 • Fax: (519) 895-2017