

HSK – Ihr Partner für Kunststoffschweiß- und Biegetechnik
HSK – Your partner for plastic welding – and bending technology

Hand welding extruder HSK10 DE compact



BASIC EXTRUDER

- Extrusion welding from PEHD, PP and PVC
- temperature probe, location in the melt chamber
- rod feeding, no additional gearing
- Control units for actual / desired mass temperature
- Cold start protection
- Rod diameter 4 mm
- 1 pce nozzle blank included

TECHNICAL DATA

Output	1,0 kg/h (with PEHD rod 4 mm)
Heating extruder	300 W / air 1500 W
Drive	500 W
Voltage	230 V / 50Hz
Weight	4.4 kg
Guarantee	screw and cylinder 24 months

HSK10 DE (WITH HOT AIR BLOWER)

- Works as basic extruder, without external air supply
- Hot air blower controlled (air quantity 300 l/min)
- Technical data see basic extruder
- Heating hot air blower 1500 W

ADDITIONAL EQUIPMENT

- | | | |
|----------------------|----------------------------|---------------|
| ▪ Welding nozzles | Extruder nozzle preheating | Angle adaptor |
| ▪ Transportation box | Prolongation | Air compactor |
| ▪ Welding rod | Widen | |

Technical execution subject to modifications