Electronic Test Instruments



Digital Multimeter — For Volts, Amps, Ohms and Temperature



Design Features

- * True RMS Autoranging DMM
- * Type K thermocouple built in for air or water temperature measurements
- * Input fuse protection and misconnection warnings
- * Data Hold for AC/DC voltage and current
- * Relative function for establishing a baseline reference
- * Advanced measurements include Capacitance, Frequency and Duty Cycle
- * Low current capability measure down to 0.1µA
- * CE, UL, CAT III 600V
- * 3-year warranty

Resistance: 0.1 to $40M\Omega$

Specifications -

Display: 4000 counts, backlit Basic Accuracy: $\pm 0.3\%$ DC Voltage: 0.1mV to 1000V AC Voltage: 0.1mV to 750V DC Current: $0.1\mu\text{V}$ to 20A

Capacitance: 0.01 nF to $100 \mu F$ Frequency: 0.001 Hz to 10 MHzTemperature Type K: -4° to $1382^{\circ}F$ $(-20 \text{ to } 750^{\circ}C)$

Duty Cycle: 0.1 to 99.9% **Diode/Continuity:** Yes

AC Current: 0.1μ V to 20A

Part Number: EMV00018

Complete with CAT III test leads, multi-position tilt stand and velcro strip for hanging, protective holster with test lead holder, bead wire temperature probe and 9 Vdc battery.

All Items Available from Stock

400 Amp Clamp-On Multimeter with Temperature and Non-Contact Voltage Detector



Part Number: EMV00060

The EMV00060 is the perfect meter for plant maintenance or HVAC repair. Besides the standard voltage current and resistance, the additional functions of temperature, capacitance, frequency and duty cycle make this the perfect all-in-one service tool.

Design Features

- * Built-in Non-Contact Voltage Detector with LED alert
- * 4000 count, backlit LCD display
- * 1.2" jaw size for conductors up to 350MCM
- * Relative Mode for Capacitance Zero and Offset Adjustment
- * Data Hold
- * Auto Power Off
- * Complete with test leads, general purpose Type K bead wire temperature probe, two AAA batteries, and carrying case

Specifications	Range	Maximum Resolution	Basic Accuracy
Display Counts:	4000		
AC Current:	40.00A, 400.0A	0.01A	$\pm (2.5\% + 8d)$
AC Voltage:	4.00V, 40.00V, 400.0V, 600V,	0.001V	$\pm (1.8\% + 8d)$
	400.0mV, 4.000V, 40.00V, 400.0V		
DC Voltage:	600V	0.1mV	$\pm (0.8\% + 2d)$
Resistance:	400.0Ω , 4.000 k Ω , 40.00 k Ω , 400.0 k Ω	0.1Ω	$\pm (0.8\% + 2d)$
	$4.000M\Omega$, $40.00M\Omega$		
Frequency:	10Hz to 10kHz	0.01Hz	$\pm (1.5\% + 2d)$
Capacitance:	40.00nF, 400.0nF, 40.00uF, 100.0uF	0.01nF	$\pm (3.0\% + 5d)$
Temperature:	Type K tc, -4° to 1400°F (-20° to 760°C)	0.1°	$\pm (3.0\% + 9^{\circ} \text{F or } 5^{\circ} \text{C})$
Duty Cycle:	0.5 to 99.0%	0.1%	$\pm (1.2\% + 2d)$
Diode Test:	Yes		
Continuity Test:	Yes		
Dimensions:	$7.9" \times 2.6" \times 1.5" (200 \times 66 \times 37 \text{ mm})$		
Weight:	7.2oz. (205g)		



Electronic Test Instruments

Megohmmeter/Insulation Tester

Design Features:

- * Three test ranges: 200M /1000VDC 200M /500VDC 200M /250VDC
- * Power lock for 3-minute test
- * Auto power off and Data Hold
- * No voltage drop at low resistance
- * Full function indication and Overload Protection
- * Measures resistance to 200 and Volts to 750VAC
- * 1mA test current ensures 1000V/500V/250V rating
- * Complete with 6 AA batteries, test leads and case with neck strap



Part Number: EMM00010

Specifications	Range	
Insulation Voltage:	250/500/1000	
Insulation Resistance (accuracy):	$200/2000M\Omega (3\% + 5 \text{ digits})$	
Output short circuit current:	≤ 2.5mA	
Resistance (accuracy):	200Ω (1% reading)	
Overload Protection:	2200 V (<1 min)	
Dimensions:	$3.8" \times 6.3" \times 2.3" (97 \times 160 \times 58 \text{mm})$	

All Items Available from Stock



AC Line Separator/Splitter

Design Features

- * Provides an easy and safe measurement of current without the need to cut off the plug and separate the conductors.
- * Two clamp-on positions: ×1 for direct readings ×10 for actual reading multiplied by 10
- * Dimensions: $5.25'' \times 2'' \times 1'' (133 \times 51 \times 25mm)$

Part Number: EMV00065