



QUADRUPLE PROPAGATOR H2 (21) **Operating Instructions**



COMPONENTS

100-watt Heated Tray 38" x 15"	1
Heat Mat Thermostat	1
Seed Trays and Covers	4

Your Quadruple Propagator has been supplied with the Heat Mat Thermostat ready to be connected to the Heated Tray.

USING THE PROPAGATOR

The Heated Tray should be used with the side marked "Top" to the top! (The other side has an insulated layer to direct the heat upwards). The Seed Trays can be used directly on top of the Heated Tray or if you prefer on top of a layer of Water Matting to increase the humidity level.

The Thermostat can be mounted onto your greenhouse wall (or similar) - the thin brown lead has a thermistor on the end to sense temperature - see enclosed Thermostat instructions for full details.

Place the Thermistor in the most temperature critical position e.g. use the sucker included to fix to the inside of one of the seed tray covers. Do not position it directly onto the Heated Tray as this will give a surface temperature reading and not the important temperature inside the seed trays.

REPLACING THE PLUG

The propagator is connected to a 3-amp fused plug. Should you need to replace this plug be sure that you rewire correctly i.e.:

- BROWN wire to live terminal (L)
- BLUE wire to neutral terminal (N)
- GREEN/YELLOW wire to earth terminal (E)