TeleEye



Specifications





Features

- 4MP AHD IR Vari-Focal Bullet
- 1/3" 4MP CMOS sensor
- Up to 1200TVL resolution
- f=3.3-12mm Vari-Focal Lens
 Angle of view 85.7°-33.6°
- 20~30M IR illumination range
- IP66 weather proof

Dimension

Unit: mm





MODEL		AF465
VIDEO	IMAGE SENSOR	1/3" 4MP CMOS
	RESOLUTION	2560x1440
	Video Output	AHD (BNC)
	Frame Rate	30fps(60Hz), 25fps(50Hz)
	Minimum Illumination	0Lux (IR ON)
	IR LED / IR Distance	20~30M
	Lens	f=3.3mm ~12mm vari-focal lens
	Angle of view	85.7°-33.6°
	Electronic Shutter	Auto; 1/25s~1/50000s(PAL); 1/30s~1/50000s(NTSC)
	S/N Ratio	≥52dB (AGC OFF)
FUNCTION	Function Control	OSD (COC Control)
	Day & Night	ICR
	Digital WDR	Yes
	Digital NR	Yes (2D DNR)
	AGC	Yes
	Auto White Balance	Yes
	BLC	Yes
	Edge Brightness Compensation	Yes
	Defogging	Yes
	HLC	Yes
	Sharpness	Yes
	Image Setting	Yes
POWER	Power Supply	12VDC
	Power Consumption	Day: < 1W; Night: < 4W
OPERATING ENVIRONMENT	Ambient Temperature	- 20 °C ~ 50 °C
	Relative Humidity	10%-90%
MECHANICAL DESIGN	Weather Proof	IP66
	Dimension	Ф 87mm x 220mm
	Weight	570g

TeleEye GroupHong Kong China Malaysia Philippines
South Africa Sri Lanka Turkey U.K.

DISTRIBUTED BY:

www.TeleEye.com