

- Max. resolution: 1920 x 1080
- H.265
- 3 independent video streams
- Support Micro SD card
- Small Size:
- 30mm x30mm x29.5mm

## MP283 - HD

## 1080p Network Pinhole Camera

TeleEye Pinhole Camera with a 4.3mm pinhole lens delivers a high resolution (1920 x 1080), provides 3 independent video streams and, supports H.265 video compression. Such a small size camera (30mm x 30mm x 29.5mm), is ideal for the use in ATMs, vending machines and retail stores.



Model MP283-HD

1 VIDEO

COMPRESSION

**DESIGN** 

IMAGE SENSOR 1/3" 2MP CMOS

**RESOLUTION** 1080P ( 1920 × 1080 ), 720P ( 1280 × 720 ), D1

FRAME RATE Up to 25/30fps

MINIMUM ILLUMINATION Color: 0.1Lux / F1.2; B/W: 0.01Lux / F1.2

**LENS** 4.3mm pinhole lens

**ELECTRONIC SHUTTER** 1 / 25 s ~ 1 / 100000 s

ROI, Saturation, Brightness, Chroma, Contrast, VIDEO SETTINGS

Wide Dynamic, Sharpen, NR,etc.

ANALOG VIDEO OUTPUT CVBS video output (BNC × 1)

AUDIO – INPUT One built-in microphone

NETWORK INTERFACE RJ-45

TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE,

H.265 / Enhanced H.264

NETWORK PROTOCOL

DDNS, SMTP, FTP

CONNECTIVITY CONCURRENT USERS

WEB SERVER Built-in
ONVIF Profile S

┌ VIDEO COMPRESSION H.265 / En

VIDEO STREAMING 3 Independent Streams

EDGE RECORDING - TF Card Max. 128GB


POWER 12VDC


MAX. RATING 2W

OPERATING ENVIRONMENT AMBIENT TEMPERATURE -20°C ~ 50°C RELATIVE HUMIDITY 10%-90%

MECHANICAL DIMENSION 30mm x 30mm x 29.5mm

WEIGHT 97g





Terms & Conditions 使用細則
Design and specifications are subject to change without prior notice. Copyright © 2018 Signal Communications Limited. TeleEye is a trademark of Signal Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners

