


- 1/3" 4MP CMOS sensor
- f=2.8mm fixed lens Angle of view: 100°
- 30-50m IR illumination range
- H.265 / H.264 compression
- AI Detection:


Face detection

Human / Vehicle detection

- IP67 Water proof
- Power over Ethernet
- ONVIF Profile S

Unit: mm





Accessories



Junction Box: JB0301

Terms & Conditions 使用細則 Design and specifications are subject to change without prior notice. Copyright © 2019 Signal Communications Limited. TeleEye is a trademark of Signal Communications Limited and is registered in China, European Community, Hong Kong, U.S. and other countries. All other trademarks are the property of their respective owners.

TeleEye Group

Hong Kong China Malaysia Philippines South Africa Sri Lanka United Kingdom



MP4052AE 4MP Network IR Fixed Bullet with AI Detection



| MODEL | |
|-------|--|

| MODEL | | | MP4052AE |
|----------------------------|---|----------------------|--|
| | г | IMAGE SENSOR | 1/3" 4MP CMOS |
| VIDEO | | RESOLUTION | 4MP(2560×1440), 3MP(2304×1296), 1080P(1920 ×1080), 720P(1280×720), D1, CIF, 480×240 |
| | | FRAME RATE | Up to 25/30fps |
| | | MINIMUM ILLUMINATION | 0.005 lux @F1.6, AGC ON; 0 lux with IR |
| | | IR DISTANCE | 30~50M |
| | | LENS | f=2.8mm @F1.6 fixed lens |
| | | ANGLE OF VIEW | 100° |
| | | ELECTRONIC SHUTTER | 1 / 30 s ~ 1 / 100000 s |
| | L | VIDEO SETTINGS | ROI, Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc |
| AUDIO | — | INPUT | 1CH Audio input |
| CONNECTIVITY | ſ | NETWORK INTERFACE | RJ45 × 1, 10M / 100M self-adaption |
| | | NETWORK PROTOCOL | TCP / IP, UDP, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP,HTTP, 802.1x, UPnP, HTTPs, QoS |
| | | CONCURRENT USERS | 4 |
| | | WEB SERVER | Built-in |
| | L | ONVIF | Profile S |
| COMPRESSION | Г | VIDEO COMPRESSION | H.265 / H.264 |
| | | VIDEO STREAMING | 3 Independent Streams |
| | L | AUDIO COMPRESSION | G711A/U |
| FUNCTION | Г | AI DETECTION | Face detection; Human detection; Vehicle detection |
| | | SMART ALARM | Intrusion detection; Line crossing detection; Video Exception; Motion detection |
| | L | ACTION | Snap, Recording, Email |
| EDGE RECORDING POWER | _ | MICRO SD Card | Max. 128GB |
| | Г | VOLTAGE | 12VDC |
| | | MAX. RATING | <9.5W |
| | L | POE | YES, IEEE802.af |
| OPERATING ENVIRONMENT | [| AMBIENT TEMPERATURE | 30°C ~ 60°C |
| | | RELATIVE HUMIDITY | Less than 95% (non-condensing) |
| MECHANICAL DESIGN | [| WATER PROOF | IP67 |
| | | DIMENSION | 218mm x 80.5 mm x 80.5mm |
| | | WEIGHT | 700g |